

The EB-L630U fixed lens laser projector offers 6,200 lumens and is ideal for education, corporate, retail and visitor attractions.

As the market leader in 3LCD technology, Epson continues to improve its high brightness laser projectors with even smaller and more compact display solutions. The EB-L630U delivers even more effective, practical and creative display applications across a number of different industries.

Bright, cost-effective display solutions

Providing bolder, brighter, more engaging and impactful displays even in brightlylit environments, the EB-L630U offers impressive 6,200-lumen brightness and WUXGA Full HD resolution at an affordable price. This means that users can upgrade to laser performance and reliability, with reduced power consumption, without paying a premium. It also features: 4K input support, detail enhancement technology, edge blending and wide lens shift to fit challenging installation environments. The EB-L630U is capable of up to 500-inch displays, without any reduction in clarity or vivid detail.

Enhanced connectivity

This display solution offers many different ways to connect, show multiple sources simultaneously and present wirelessly. The EB-L630U comes equipped with futureproofed connectivity options including HDMI and HDBaseT with 4K signal support, 5GHz wireless with enterprise security, upgraded Miracast, built-in media player and support for Epson's ELPWP10 wireless presentation system.

Easy and flexible installation

This stylish and compact projector supports 360 degree installation without compromising the display quality and supports 16:6 ultra-widescreen, HDMI output and edge blending for multi-projector installs.

KEY FEATURES

• 6,200-lumen brightness

Crisp images and bright colours, even in well-lit rooms

- WUXGA resolution Sharp Full HD images for excellent clarity
- Futureproofed connectivity options 4K input support, HDMI, HDBaseT, integrated Wi-Fi and screen mirroring
- Easy, flexible installation Lightweight and compact design with wide lens shift
- Support social distancing Scalable display size of up to 500 inches



EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0,67 inch with C2 Fine
IMAGE	
Color Light Output	6.200 Lumen- 4.340 Lumen (economy) In accordance with IDMS15.4
White Light Output	6.200 Lumen - 4.340 Lumen (economy) In accordance with ISO 21118:2012
Resolution	WUXGA, 1920 x 1200, 16:10
High Definition	Full HD
Aspect Ratio	16:10
Contrast Ratio	Over 2.500.000 : 1
Light source	Laser
Laser Light source	20.000 hours Durability High, 30.000 hours Durability Eco
Keystone Correction	Manual vertical: ± 30 °, Manual horizontal ± 30 °
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1,35 - 2,20:1
Zoom	Manual, Factor: 1 - 1,6
Lens	Optical
Lens Shift	Manual - Vertical ± 50 %, horizontal ± 20 %
Screen Size	50 inches - 500 inches
Projection Lens Focus	Manual
CONNECTIVITY	
Interfaces	USB 2.0 Type A, USB 2.0 Type B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T),
	Wireless LAN IEEE 802.11a/b/g/n/ac, Wireless LAN b/g/n (2.4GHz), Wireless LAN a/n (5GHz),
	VGA in (2x), VGA out, HDMI out, HDBaseT, Miracast, Stereo mini jack audio out, Stereo mini
	jack audio in (2x), HDMI (HDCP 2.3) (2x), USB 2 Type A playback
Network Protocol	HTTPS, IPv6, SNMP, ESC/VP.net, PJLink
ADVANCED FEATURES	
Video Color Modes	Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Multi Projection
GENERAL	
Power consumption	345 Watt, 258 Watt (economy), 0,3 Watt (standby)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	440 x 339 x 136 mm (Width x Depth x Height)
Product weight	8,4 kg
OTHER	
Warranty	36 months Carry in

LOGISTICS INFORMATION

SKU	V11HA26040
EAN code	8715946695310
Country of Origin	Philippines

EB-L630U

T'S IN THE BOX

- ver cable
- note control incl. batteries
- ole cover
- er guide
- rranty Documents
- n unit

IONAL ACCESSORIES

- on ELPWP10 Wireless Presentation System HA41040
- on ELPWT01 Wireless Transmitter HA43040
- oter ELPAP11 Wireless LAN (5GHz) H005A01
- ilter ELPAF56 L600/EB-14XX Series H134A56
- ng Mount (White) ELPMB22 -1003B22
- ng Mount (Low profile) ELPMB30 H526040
- ng Pipe (450mm) ELPFP13 H003P13
- ng Pipe (700mm) ELPFP14 H003P14
- ty Wire ELPWR01 H003W01



Epson Deutschland GmbH Otto-Hahn-Str. 4 D-40670 Meerbusch Info-Line: 02159 92 79 500 Telefax: +49 (0) 2159/538-3000 www.epson.de

Epson in Österreich Info-Line: 01 253 49 78 333 www.epson.at Epson in der Schweiz Info-Line: 022 592 7923 www.epson.ch

Alle Marken und eingetragenen Warenzeichen sind das Eigentum der Seiko Epson Corporation oder der jeweiligen Rechteinhaber.

Diese Produktinformationen können ohne vorherige Ankündigung geändert werden.

