





Local distributor code: 422503745 SBP1500RM

			W	

Lead time

#### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60320 C14
Number of rack unit	2U
Cable length	1.98 m
Number of cables	1
Provided equipment	User manual Rack mounting brackets

#### **Physical**

Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	7.6 cm
Net weight	2 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted

### Input

Network frequency	50/60 Hz
Permissible voltage	220240 V
Max line current	10 A
Input current limits	10 A
Load capacity	1500 VA
Power factor	01

### Output

Max current draw	10 A
Number of power socket outlets	6 IEC 60320 C13 1 IEC Jumpers
Number of power socket outlets	6
Protection type	Circuit breaker
Power cable length	1.22 m
Efficiency	99 %

#### Conformance

Product certifications	VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

#### **Environmental**

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	015000 ft
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m

## **Packing Units**

Package 1 Height	15.1 cm
Package 1 Width	46.3 cm
Package 1 Length	29.5 cm
Package 1 Weight	3.5 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	56
Package 2 Height	113 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	195.608 kg

# Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## **Contractual warranty**

Warranty	2 years repair or replace

#### Recommended replacement(s)