



7.5m Standard HDMI Cable, Anthra Line

Part No.: 36966

Description

- Superior performance and design Standard HDMI 2.0 cable
- Supports UHD resolutions up to 4096x2160@60Hz 4:2:0 8bit
- Robust PVC housing, gold plated connectors and contacts
- Triple shielded cable, corrosion resistant bare copper 24AWG conductors
- HDMI 2.0 compliant, 3D, 4K, 10.2Gbps, HEC, ARC, CEC, Dolby® True HD, DTS-HD Master Audio; 10 year warranty

From the Lines cable connectivity concept developed by Lindy, Anthra Line HDMI cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line HDMI cables are premium connections that feature triple shielded with 24AWG copper conductors for performance and corrosion resistance. High quality gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:2:0 8bit are supported. Anthra Line HDMI cables are also capable of transmitting 32 channel audio and Dolby® True HD.

These HDMI 2.0 cables support 10.2Gbps bandwidth capacity in cable lengths from 7.5m up to 20m.

Anthra Line HDMI cables are available in lengths from 0.3m to 20m.

Technical details

Connectors

- Connector A: HDMI Type A MaleConnector B: HDMI Type A Male
- Housing Material: PVCConnector Plating: Gold
- Pin Construction: Phosphor Bronze
- Pin Plating: Gold
- Dimensions (approx.) WxDxH: 21.4x41.44x12.7mm (0.84x1.63x0.5in)

Cable Construction

Length: 7.5m (24.61ft)Standard: HDMI Standard

Colour: BlackType: Round

• Jacket Diameter: 9.8mm (0.39in)

Jacket Material: PVC

Conductor Material: Bare Copper

Conductor Gauge: 24AWG

Shielding: Aluminium Magnesium Alloy 55%

Specifications

- Supported Bandwidth: 10.2Gbps
- Maximum Resolution: 4096x2160@60Hz 4:2:0 8bit
- Nominal Attenuation:
 - o 300kHz-825MHz --- 15dB
 - 825MHz-2.475GHz --- 15 29dB
 - o 2.475GHz-4.125GHz --- 29 44dB
 - o 4.125GHz-5.1GHz --- 44 48dB
- Minimum Band Radius: 98mm (3.86in)
- Operating Temperature: -20°C 80°C (-4°F 176°F)
- Storage Temperature: -25°C 85°C (-13°F 185°F)

Miscellaneous

Packaging Type: PolybagWarranty (Years): 10

Certificated: RoHS, REACH, UL

Purchasing Information

• No.: 36966

EAN: 4002888369664

- 36966 7.5m (24.61ft)
- 36967 10m (32.81ft)
- 36968 15m (49.21ft)
- 36969 20m (65.62ft)

© LINDY 2020