

Rittal – The System.

Faster – better – everywhere.

CMC III CAN bus connection cable – DK 7030.094

Date : Jul 12, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



CMC III CAN bus connection cable – DK 7030.094

created: 12.07.2021 on www.rittal.com/com-en



Product description

Description: For connecting the PU to the CAN bus sensors III, units III and control units III as a bus, also for cabling together. Because it is available in different lengths, the CMC III system can be adapted to various applications and built to a custom design.

Applications: For connecting the CAN bus units.
Information and power transfer of the individual CAN bus units.

Product description

Dimensions: Length: 5 m

Operating temperature: Operation (environment): +0 °C...+55 °C

Ambient humidity (non-condensing): Operation (environment): 5 % - 95 %

Interfaces/connections: Connector (type): RJ45
Connector (type): RJ45

Packs of: 1 pc(s).

Weight/pack: 0.2 kg

Copper weight (kg per piece): 0

EAN: 4028177659452

Customs tariff number: 85444290

ETIM 7.0: EC000313

ETIM 6.0: EC000313

eCl@ss 8.0/8.1: 27189253

eCl@ss 6.0/6.1: 27189253

Product description: DK CMC III CAN bus connection cable, L: 5 m, type: RJ45

Approvals

Certificates: NA