

# Product datasheet

Specifications



## Power Cord Kit (6 ea), Locking, C13 to C14, 1.8m

AP8706S-WW

### Overview

Presentation	This Series of Rack Power Distribution Units (PDU) comes with Locking IEC Receptacles. The output and input connections are C13 to C14. The cord length is 1.8m. Locking IEC system allows the use of optional locking IEC power cords for added power cord security and enhanced reliability. No tools are required to disengage the locking feature and remove the plug from the locking receptacle.
--------------	--

Lead time

### Main

Input Connection Type	IEC 60320 C14
Cable length	1.83 m
Number of cables	6

### Physical

Colour	Black
Height	24 cm
Width	7.5 cm
Depth	5.5 cm
Net weight	1.35 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

### Input

Max line current	10 A
Input current limits	10 A

### Output

Max current draw	10 A
Number of power socket outlets	1 IEC 60320 C13
Power cable length	1.83 m

### Conformance

Product certifications	CCC PSE VDE
------------------------	-------------------

Environmental

Ambient air temperature for operation	0...70 °C
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...75 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24 cm
Package 1 Width	5.5 cm
Package 1 Length	7.5 cm
Package 1 Weight	1.35 kg
Number of Units in Package 3	300

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------