



Active holder for fixed installation

With USB Type-C. 2 USB ports: Type-A and Type-C, QC 3.0A + 2.4A. With tilt swivel. 12/24 Volt.

Item no: 727380

EAN Number: 7320287273809

Keep your phone's battery fully charged in an active holder, always within easy sight and reach! Neat, discreet and convenient. Custom made with a perfect, firm fit. For fixed installation. The holder is to be connected inside the dashboard, providing an elegant installation without any cables hanging over the interior. The charging box has two USB ports: QC 3.0A + 2.4A. You have full access to the camera and all buttons when the device is in the holder. It is easy to slide the phone in place in the holder so it connects to the charging, and to take it out of the holder when leaving the vehicle.

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing, or switch between portrait and landscape mode. Tilts 17° and swivels 360°. Mounting plate 42x50 mm with 4 mm AMPS-holes. Made of high grade black ABS/Acetal plastic. Made in Sweden. Connect the power cable with a 2A fuse. Professional installation recommended. Attach onto a ProClip mounting platform.

Fits the following models:

Samsung Galaxy XCover 7

For a complete list, see

www.brodit.com/en/product/727380

Measurements:

Height 104 mm

Width 84 mm

Depth 55 mm

Volume 480 cm³

Weight 267 g

Charging specifications:

- Output Connector Type: Dual USB, Type-A and Type-C Female.
- Output Voltage: 5V, 9V, 12V(Nominal)
- Output Current:
- USB Port 1: TYPE-C PD: 3.6V ~ 6V/3A 6.2-9V/2A 9.2-12V/1.5A(Under full Load).
- USB Port 2: TYPE-A, QC3.0. 3.6V ~ 6V/3A 6.2-9V/2A 9.2-12V/1.5A(Under full Load).
- Output Voltage Ripple: 300mV pk-pk at Max Load
- Input Voltage Range: DC 12--24V DC, Input can handle 40V Load dump transient events
- Input Current: 3.0 A DC Max
- Input Current with No device attached: 0.005A
- DC-DC Conversion Efficiency: Over 86% Typical
- Rated Power:
- USB Port 1: TYPE-C 18Watts Max
- USB Port 2: TYPE-A 18Watts Max