

Product datasheet

Specifications



Rack PDU, Basic, 1U, 22kW, 400V, (6) C19

AP7526

Overview

Lead time

Main

Main Input Voltage	400 V 3 phases
Main Output Voltage	230 V
Input Connection Type	IEC 60309 32 A 3P + N + PE
Number of rack unit	1U
Cable length	2.44 m
Number of cables	1
Provided equipment	Installation guide

Physical

Colour	Black
Height	4.4 cm
Width	43.7 cm
Depth	25.4 cm
Net weight	4.84 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Permissible voltage	200...250 V
Max line current	32 A
Input current limits	32 A
Load capacity	22000 VA
Network frequency	47...63 Hz

Output

Number of power socket outlets	6 IEC 60320 C19
--------------------------------	-----------------

Conformance

Product certifications	CE GOST VDE
------------------------	-------------------

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.1 cm
Package 1 Width	55.9 cm
Package 1 Length	50.2 cm
Package 1 Weight	6.965 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------