

# Product datasheet

Specifications



## Rack PDU, Basic, 0U/1U, 100-240V/20A, 220-240V/16A, (13) C13

AP6020A

### Overview

|                     |   |
|---------------------|---|
| <b>Presentation</b> | Reliable rack power distribution designed to increase manageability and efficiency in the data center. The output and input connections are (13) C13. Real-time remote monitoring of connected loads. User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment. |
|---------------------|---|

### Lead time

### Main

|                              |  |
|------------------------------|--|
| <b>Main Input Voltage</b>    | 100 V<br>120 V<br>200 V<br>208 V<br>230 V<br>240 V |
| <b>Input Connection Type</b> | IEC 60320 C20                                      |
| <b>Number of rack unit</b>   | 1U   |
| <b>Provided equipment</b>    | Installation guide<br>Safety guide                 |

### Physical

|                            |                    |
|----------------------------|--------------------|
| <b>Colour</b>              | Black              |
| <b>Height</b>              | 38.8 cm            |
| <b>Width</b>               | 4.4 cm             |
| <b>Depth</b>               | 9.3 cm             |
| <b>Net weight</b>          | 1.5 kg             |
| <b>Mounting location</b>   | Front<br>Rear      |
| <b>Mounting preference</b> | Lower              |
| <b>Mounting mode</b>       | Not rack-mountable |
| <b>USB compatible</b>      | No                 |

### Input

|                             |             |
|-----------------------------|-------------|
| <b>[In] rated current</b>   | 16 A        |
| <b>Permissible voltage</b>  | 100...240 V |
| <b>Max line current</b>     | 20 A        |
| <b>Input current limits</b> | 20 A        |

|                   |          |
|-------------------|----------|
| Load capacity     | 3300 VA  |
| Network frequency | 50/60 Hz |

## Output

|                                |                  |
|--------------------------------|------------------|
| Number of power socket outlets | 13 IEC 60320 C13 |
|--------------------------------|------------------|

## Conformance

|                        |  |
|------------------------|--|
| Product certifications | cUL listed<br>CE<br>EAC<br>IRAM<br>PSE<br>UL listed<br>VDE |
|------------------------|--|

## Packing Units

|                              |                |
|------------------------------|----------------|
| Unit Type of Package 1       | PCE            |
| Number of Units in Package 1 | 1              |
| Package 1 Height             | 43.6 cm        |
| Package 1 Width              | 7.6 cm         |
| Package 1 Length             | 21 cm          |
| Package 1 Weight             | 2.02 kg        |
| Number of Units in Package 3 | 100            |
| SCC14                        | 10731304327803 |

## Offer Sustainability

|                             |  |
|-----------------------------|--|
| Sustainable offer status    | Green Premium product                            |
| REACH Regulation            | <a href="#">REACH Declaration</a>                |
| EU RoHS Directive           | Compliant<br><a href="#">EU RoHS Declaration</a> |
| Lead free                   | Yes  |
| Optimized Energy Efficiency | Energy efficient product                         |
| Take-back                   | Take-back program available                      |

## Contractual warranty

|          |                           |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|