

# AXIS P3935-LR Network Camera

Best-in-class dome with IR for advanced onboard surveillance

Specifically designed for onboard surveillance, AXIS P3935-LR complies with all relevant transportation industry regulations including EN50155, EN45545, and NFPA 130. Featuring Axis Lightfinder and Axis Forensic WDR, it delivers true colors and great detail in challenging light or near darkness. It includes built-in invisible IR LEDs (940 nm) for video surveillance in complete darkness. Enclosed in an IK10-, IP66-, IP67-rated metal casing, this robust, vandal-resistant camera features a built-in microphone for audio surveillance and detection. Furthermore, enhanced security features prevent unauthorized access and safeguard your system.

- > **Vandal-resistant, metal casing**
- > **Complies with EN50155, EN45545, and NFPA 130**
- > **Lightfinder and Forensic WDR**
- > **Invisible IR LEDs, built-in microphone, and EIS**
- > **Enhanced security features**



# AXIS P3935-LR Network Camera

|                                |   |  |  |
|--------------------------------|---|--|--|
| <b>Models</b>                  | AXIS P3935-LR RJ45<br>AXIS P3935-LR M12   | <b>System integration</b>                |  |
| <b>Camera</b>                  |   | <b>Application Programming Interface</b> | Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at <a href="https://axis.com">axis.com</a><br>AXIS Video Hosting System (AVHS) with One-Click Connection<br>One-click cloud connection<br>ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S and ONVIF® Profile T, specification at <a href="https://onvif.org">onvif.org</a>   |
| <b>Image sensor</b>            | 1/2.9" Progressive scan RGB CMOS  | <b>Event conditions</b>                  | Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, shock detected, storage failure, system ready, within operating temperature<br>Edge storage: recording ongoing, storage disruption<br>I/O: manual trigger, virtual input<br>MQTT subscribe<br>Scheduled and recurring: scheduled event<br>Video: average bitrate degradation, day-night mode, live stream open, tampering |
| <b>Lens</b>                    | 2.8 mm, F1.6<br>Horizontal field of view: 110°<br>Vertical field of view: 62°<br>M12 mount, fixed iris<br>See <b>Optional accessories</b> for exchangeable lenses   | <b>Event actions</b>                     | Day-night mode<br>Defog<br>Guard tours<br>Upload images or video clips: FTP, HTTP, HTTPS, SFTP, email and network share<br>Notification: HTTP, HTTPS, TCP and email<br>Overlay text<br>Preset positions<br>Record video: SD card and network share<br>SNMP trap messages<br>WDR mode<br>MQTT publish   |
| <b>Day and night</b>           | Automatically removable infrared-cut filter   | <b>Data streaming</b>                    | Event data   |
| <b>Minimum illumination</b>    | Color: 0.06 lux at 30 IRE F1.6<br>B/W: 0.01 lux at 30 IRE F1.6, 0 lux with IR illumination on<br>Color: 0.12 lux at 50 IRE F1.6<br>B/W: 0.02 lux at 50 IRE F1.6, 0 lux with IR illumination on  | <b>Built-in installation aids</b>        | Pixel counter  |
| <b>Shutter speed</b>           | 1/33500 s to 2 s  | <b>Analytics</b>                         |  |
| <b>Camera angle adjustment</b> | Pan: ±30°<br>Tilt: 15-90°<br>Rotation: ±175°  | <b>Applications</b>                      | <b>Included</b><br>AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard<br>AXIS Video Motion Detection, active tampering alarm <sup>d</sup> , blocked view detection <sup>e</sup> , shock detection, audio detection<br>Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="https://axis.com/acap">axis.com/acap</a>   |
| <b>System on chip (SoC)</b>    |   | <b>General</b>                           |  |
| <b>Model</b>                   | ARTPEC-7  | <b>Casing</b>                            | IP66/67-, NEMA 250 4X- and IK10-rated aluminum casing, polycarbonate clear dome  |
| <b>Memory</b>                  | 1 GB RAM, 512 MB Flash  | <b>Sustainability</b>                    | PVC free   |
| <b>Video</b>                   |   | <b>Mounting</b>                          | Inside vehicles and rolling stock  |
| <b>Video compression</b>       | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles<br>H.265 (MPEG-H Part 2/HEVC) Main Profile<br>Motion JPEG   | <b>Memory</b>                            |  |
| <b>Resolution</b>              | 1280x960 to 160x120<br>1920x1080 to 160x90  | <b>Power</b>                             | Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3<br>IR illumination on: typical 6.6 W, max 11.8 W   |
| <b>Wide dynamic range</b>      | Forensic WDR  | <b>Connectors</b>                        | RJ45: male, 10BASE-T/100BASE-TX<br>M12: female, rugged, D-coded with rotatable coupling nut<br>All connectors support PoE<br>3.5 mm audio in connector, mono<br>I/O 4-pin, 1 input, 1 output + 12 V DC/15 mA   |
| <b>Frame rate</b>              | Up to 25/30 fps (50/60 Hz) in all resolutions<br>45 fps in 720p<br>Capture mode 2MP 1920x1080 (16:9) @25/30 fps<br>Capture mode 1MP 1280x720 (16:9) @45 fps   | <b>IR illumination</b>                   | Optimized IR with power-efficient, long-life 940 nm IR LEDs<br>Range of reach 15 m (49 ft) or more depending on the scene  |
| <b>Video streaming</b>         | Multiple, individually configurable streams in H.264, H.265 and Motion JPEG<br>Axis Zipstream technology in H.264 and H.265<br>Controllable frame rate and bandwidth<br>VBR/ABR/MBR H.264 and H.265<br>Video streaming indicator  | <b>Storage</b>                           | Support for microSD/microSDHC/microSDXC card with UHS Speed Class U1<br>Support for SD card encryption (AES-XTS-Plain64 256bit)<br>Support for recording to network-attached storage (NAS)<br>For SD card and NAS recommendations see <a href="https://axis.com">axis.com</a>  |
| <b>Multi-view streaming</b>    | Up to 8 individually cropped out view areas   | <b>Operating conditions</b>              | Normal, IR off: -40 °C to 55 °C (-40 °F to 131 °F)<br>Normal, IR on: -40 °C to 45 °C (-22 °F to 113 °F)<br>Maximum (intermittent): 70 °C (158 °F)<br>Arctic Temperature Control: start-up at -40 °C (-40 °F)<br>Humidity: 10-100% RH (condensing)  |
| <b>Image settings</b>          | Compression, brightness, sharpness, contrast, white balance, Forensic WDR, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 90°, 180°, 270° including Corridor Format, dynamic overlay, 20 individual polygonal privacy mask, mirroring of images, defogging, electronic image stabilization <sup>a</sup><br>Scene profiles: forensic, vivid, traffic overview | <b>Storage conditions</b>                | -40 °C to 65 °C (-40 °F to 149 °F)   |
| <b>Pan/Tilt/Zoom</b>           | Digital PTZ, preset positions, guard tour, control queue  | <b>Approvals</b>                         | EMC<br>EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A,   |
| <b>Audio</b>                   |   |  |  |
| <b>Audio streaming</b>         | Audio in, simplex   |  |  |
| <b>Audio encoding</b>          | AAC- LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz<br>Configurable bit rate  |  |  |
| <b>Audio input/output</b>      | External microphone input or line input, built-in microphone  |  |  |
| <b>Network</b>                 |   |  |  |
| <b>Security</b>                | Password protection, IP address filtering, HTTPS <sup>b</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>b</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, firmware with Long Term Support (LTS) firmware <sup>c</sup>  |  |  |
| <b>Supported protocols</b>     | IPv4, IPv6 USGv6, HTTP, HTTPS <sup>b</sup> , HTTP/2, TLS <sup>b</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)  |  |  |

KCC KN32 Class A, KN35, EN 50121-4, EN 50121-3-2, IEC 62236-4, ECE R10 rev.05 (E approval), EN 50498  
**Safety**  
 IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, EN 45545, UN ECE R118, NFPA 130, IEC 62471, IS 13252  
**Environment**  
 IEC/EN 61373 Category 1 Class B, IEC/EN 60529 IP66, IEC/EN 60529 IP67, parts of NEMA 250 Type 4X (ingress of water and gasket test), IEC/EN 62262 IK10, IEC 60721-3-5 Class 5M3 (vibration and shock), EN 50155:2017 OT2/ST2, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78  
**Network**  
 NIST SP500-267

|                             |  |
|-----------------------------|--|
| <b>Dimensions</b>           | Height: 49.4 mm (1.94 in), ø 110 mm (4.33 in)  |
| <b>Weight</b>               | RJ45: 400 g (0.88 lb)<br>M12: 410 g (0.90 lb)  |
| <b>Included accessories</b> | Installation guide, Windows® decoder 1-user license, drill hole template, lens tool, Resistorx® L-key  |
| <b>Optional accessories</b> | <b>Lenses</b><br>Lens M12 2.1 mm F1.8 IR: horizontal field of view 145°<br>Lens M12 3.6 mm F1.8 IR: horizontal field of view 87°<br>Lens M12 6 mm, F1.9 IR: horizontal field of view 56° |

Lens M12 8 mm F1.8 IR: horizontal field of view 40°

**Other**

AXIS T94D02S Curved Mount Bracket, network coupler IP66, network cable coupler indoor  
 For more accessories, see [axis.com](http://axis.com)

|                                  |  |
|----------------------------------|--|
| <b>Video management software</b> | AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a> |
| <b>Languages</b>                 | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese  |
| <b>Warranty</b>                  | 5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>  |

- Use this function only when camera is directed to capture scenes outside of the vehicle
- This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([openssl.org](http://openssl.org)), and cryptographic software written by Eric Young ([eyay@cryptsoft.com](mailto:eyay@cryptsoft.com)).
- In the LTS track for firmware upgrades, improvements are focused on cybersecurity and stability. New features are available in the firmware from the Active track
- For detection of tampering attempts in static and non-crowded scenes.
- For detection of tampering attempts in onboard environments.

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)