



1m USB 3.2 Type A to C Cable, 90° Right Angle, 10Gbps

32013

TITLE EN

1m USB 3.2 Type A to C Cable, 90° Right Angle, 10Gbps

SUBTITLE EN

USB Type A Male to C Male

SHORT DESCRIPTION EN

<ul style="list-style-type: none">• Entry level USB 3.2 Type A to C cable for home and small office applications• USB Type C plug angled at 90°• Supports data rates of up to 10Gbps• Robust PVC housing with nickel-plated contacts• 10 year warranty <p>LINDY USB 3.2 Type A to C cables feature double shielded construction with copper conductors for premium performance and corrosion resistance. Nickel connectors and gold plated contacts maintain signal integrity and reliability.</p> <p>USB cables with angled plugs protect the USB ports of your devices by reducing pressure and preventing cable breakage, making them ideal for confined spaces and hard-to-reach ports.</p> <p>Data transfer speeds up to 10Gbps are supported for the quick and effortless transfer of large data volumes.</p> <p>USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.</p> <p>USB 3.2 Type A to C, 90° Right Angle cables are available in the following lengths: 0.5m, 1m, 1.5m.</p>	
---	--

Connectors

- Connector A: USB 3.2 Type A Male
- Connector B: USB 3.2 Type C Male 90° Right Angle
- Housing Material: PVC
- Shielding in head shell: -
- Connector Plating: Nickel
- Pin Construction: Copper
- Pin Plating: Gold
- Dimensions (approx.) WxDxH:
 - USB Type A: 7.8x26.5x14.25mm (0.31x1.04x0.56in)
 - USB Type C: 11.1x25.8x24.2mm (0.44x1.02x0.95in)

Cable Construction

- Length: 1m (3.28ft)
- Standard: USB 3.2 Gen 2 (USB 3.1 Gen 2, USB 3.1)
- Power Delivery: -
- Max. Power: 15W (3V 5A)
- Colour: Black
- Type: Round
- Jacket Diameter: 3.8mm (0.15in)
- Jacket Material: PVC
- Conductor Material: Copper
- Conductor Gauge Power: 24 AWG
- Conductor Gauge Data: 28 AWG
- Shielding: Aluminium Foil 110%

Specifications

- Supported Bandwidth: 10Gbps
- Nominal Attenuation: 0.5Mhz- 400Mhz < 5.8db
- Minimum Bend Radius: 38mm (1.5in)
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: 0°C - 70°C (32°F - 158°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Product Compliance: RoHS, REACH, California Proposition 65

Purchasing Information

- No.: 32013
- EAN: 4002888320139

This product is also available in other lengths

- 32012 - 0.5m (1.64ft)
- 32013 - 1m (3.28ft)
- 32014 - 1.5m (4.92ft)