

# Product datasheet

Specifications



## Galaxy VS UPS 30kW 400V for External Batteries, Start-up 5x8

GVSUPS30KHS

### Overview

Presentation	Highly efficient, easy-to-deploy 30kW, 400V 3-phase uninterruptible power supply (UPS) that brings best-in-class power protection to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Compact design, high-density technology and modular architecture keep total cost of ownership low and operational efficiency at the highest levels. Galaxy VS reduces your energy losses by up to 66% with the patented EConversion mode – reaching up to 99% efficiency levels and delivering more energy savings than even our industry-leading 97% efficiency in normal operating mode. The UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management via your smartphone. Includes 5x8 start-up service. For battery runtime details, see the runtime charts published under the Documents tab.
--------------	---

### Lead time

### Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in W	30 kW
Rated power in VA	30 kVA
Output connector type	Hard wire 5-wire (3P + N + E) 1
Battery type	External battery system Li-Ion (Lithium-Ion) VRLA
Provided equipment	Dust filter Installation guide Integrated network management Power modules ship installed Start-up service Top and bottom cable entry

### General

Bypass voltage tolerance	+/- 10 %
Max bypass input current	48 A
Redundant	No

### Physical

Colour	White
Height	148.5 cm

Width	52.1 cm
Depth	84.7 cm
Net weight	206 kg
USB compatible	No

### Input

Network frequency	40...70 Hz
Number of input connectors	1 hard wire 4-wire (3P + E) 1 hard wire 5-wire (3P + N + E)
Input voltage limits	340...460 V 400 V
Maximum input current	56 A
Max short time withstand current	65 kA
Input harmonic distortion	Less than 3 % for full load
Load power factor	From 0.7 leading to 0.7 lagging without any derating
Input Power Factor at Full Load	0.99

### Output

Maximum configurable power in W	30 kW
Harmonic distortion	Less than 3 %
Output frequency	50 Hz sync to mains 60 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest factor	2.5
Wave type	Sine wave
Output voltage tolerance	+/-1% after 50ms
Output harmonic distortion	< 1% linear load and < 3% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Bypass type	Built-in static bypass
Maximum configurable power in VA	30 kVA

### Conformance

Standards	CSA C22.2 No 107.3 EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 FCC part 15 class A IEC 60721-4-2 level 2M2 UL 1778 5th edition
-----------	---

### Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3281 ft
Ambient air temperature for storage	-25...55 °C
Storage Relative Humidity	10...80 % non-condensing
Storage altitude	0.00...15240.00 m

Acoustic level	65 dBA
Heat dissipation	2922.4 Btu/h
IP degree of protection	IP21
<b>Batteries &amp; Runtime</b>	
Number of battery filled slots	0
Number of battery free slots	0
Battery voltage	384...576 V DC
Discharge battery voltage	307 V DC
Max current discharge	102 A
Battery power in VAH	0 VAh runtime
Extended runtime	0
<b>Communications &amp; Management</b>	
Free slots	1
Control panel	Touch screen LCD user interface
Alarm	Audible and visible alarms prioritized by severity
<b>Packing Units</b>	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	168 cm
Package 1 Width	99 cm
Package 1 Length	64 cm
Package 1 Weight	235 kg
<b>Offer Sustainability</b>	
Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available
<b>Contractual warranty</b>	
Warranty	1 year on-site repair or replace with factory authorized Start-Up
<b>Recommended replacement(s)</b>	