


imagePROGRAF PRO-1000

Great quality printing to match your passion

A desktop size printer to serve professional photographers and aspiring amateurs. Print in stunning quality with a 12-ink pigment based system up to A2.



- Bring your images to life with stunning prints that reproduce the detail and colour you work so hard to capture.
- Print up to A2 with colour calibration on a variety of paper, including glossy, matte, fine art or canvas.
- Using LUCIA PRO pigment inks, colours are richer and blacks are deeper, producing prints that are faithful to your images.
- With compatibility for a full range of devices and platforms, print your images with ease from PCs, smartphones, or the cloud.
- The Print Studio Pro plugin lets you print effortlessly from professional editing software such as Adobe Lightroom®, Photoshop®.

PRO-1000
A2
CUT SHEET

LUCIA PRO 12 INKS

CHROMA OPTIMIZER

1.28" PRINT HEAD

2,400 x 1,200 DPI

INBUILT COLOUR
CALIBRATION

PRINT PLUG-IN FOR
PHOTO APPLICATIONS

WI-FI & ETHERNET
CONNECTIVITY

USER-FRIENDLY COLOUR
DISPLAY

Canon

Technical Specifications

imagePROGRAF PRO-1000

PRODUCT SPECIFICATION

Class	17"
Ink Type	12 x Pigment : MBK/PBK/C/M/Y/PC/PM/GY/PGY/R/B/CO
Maximum Print Resolution ^[1]	2,400 x 1,200 dpi
Printing Speed ^[2]	A2 (LU-101 colour): Approx. 3 min 35s A2 (PT-101 colour or mono): Approx. 6 min
Dimensions, Weight	Approx. 723 x 433 x 285 mm Weight approx. 32 kg (including print head and inks)
Power Supply	AC 100-240V (50-60Hz) Power consumption (approx 37W) ^[3] Standby consumption (approx 2.5W) Power off (approx 0.4W)
Operational Environment	Temperature: 5-35°C, Humidity: 10-90%RH (no dew condensation) ^[4]
Acoustic Noise	approx. 41.0 dB(A) - Photo (4 x 6") ^[5] approx. 40.8 Db(A) - Document (A4, B/W), Quiet Mode OFF ^[6] approx. 40.4 Db(A) - Document (A4, B/W), Quiet Mode ON
Operation Panel Display	3.0" (320 x 240 TFT LCD), Key x 13, LED x 2

21 Languages Selectable: Japanese / English / German / Italian / Spanish / Portuguese / Dutch / Polish / Russian / Danish / Norwegian / Swedish / Finnish / Czech / Simplified Chinese / Traditional Chinese / Hungarian / Thai / Indonesian / French / Turkish

Memory 1GB

INTERFACE TYPE & SOFTWARE

Interface	Hi Speed USB Type: Built-in USB 2.0 High-Speed Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer
Wireless LAN	Wi-Fi IEEE802.11n IEEE802.11g IEEE802.11b
Ethernet	Type Built-in: IEEE 802.3 10base-T IEEE 802.3u 100base-TX Auto-Negotiation
Smart device & Cloud apps	Canon PRINT app (iOS or Android) Pro Gallery Print app (iPad only) PIXMA Cloud Link Apple AirPrint Google Cloud Print
Camera direct	Wi-Fi PictBridge
Software	Print Studio Pro, Quick Utility Toolbox, Media Configuration Tool, Account Manager, Device Management Console

PRINT HEAD

Type	Canon Bubblejet on Demand
Head Configuration	12 colors integrated type (4 colors chips x 3)
Nozzle Pitch	600dpi x 2
Nozzle per Chip	1,536 nozzles x 12 colors, includes Non-firing nozzle detection and compensation system
Droplet Size	4 Picoliter per colour

INK TANK

Model	LUCIA PRO Ink Tanks: PFI-1000 MBK/PBK/C/M/Y/PC/PM/GY/PGY/R/B/C
--------------	--

Page yield (4 x 6" PT-101) ^[7]	Number of 10cm x 15cm photos Matte Black (MBK): 5490 photos* Photo Black (PBK): 2205 photos* Grey (GY): 1465 photos* Photo Grey (PGY): 3165 photos* Photo Cyan (PC): 5140 photos* Cyan (C): 5025 photos* Photo Magenta (PM): 3755 photos* Magenta (M): 5885 photos* Yellow (Y): 3365 photos* Red (R): 5355 photos* Blue (B): 4875 photos* Chroma Optimizer (CO): 680 photos
--	---

* Estimated Supplemental Yield

Page yield (A2 PT-101) ^[7]

Number of A2 colour photos Matte Black (MBK): 1600 photos* Photo Black (PBK): 256 photos* Grey (GY): 106 photos* Photo Grey (PGY): 270 photos* Photo Cyan (PC): 600 photos* Cyan (C): 675 photos* Photo Magenta (PM): 374 photos* Magenta (M): 965 photos* Yellow (Y): 329 photos* Red (R): 935 photos* Blue (B): 545 photos* Chroma Optimizer (CO): 97 photos*

* Estimated Supplemental Yield

MEDIA HANDLING

Media Feeding	Rear tray / Manual feed slot
Media Type	Plain Paper, Photo Paper Plus Glossy II, Photo Paper Pro Platinum, Photo Paper Pro Luster, Photo Paper Plus Semi-gloss, Photo Paper Pro Premium Matte, Matte Photo Paper, Other Fine Art, Canvas and Glossy Photo Papers
Media size	A5, A4, A3, A3+, A2, B5, B4, B3, 4 x 6", 5 x 7", 8 x 10", 10 x 12", 14 x 17", 17 x 22", LTR, LGL, LDR
Media Thickness	Rear tray: Plain paper 64-105g/m ² , Canon specialty paper Max. 300 g/m ² , Rear tray thickness: 0.1-0.3 mm Manual feed slot: Canon specialty paper Max. 400 g/m ² , Manual feed thickness: 0.1-0.7 mm
Media Width	Rear tray: 89-432 mm, Manual feed slot: 203.2-432 mm
Minimal Printable Paper Length	Rear tray: 127 mm Manual feed slot: 254 mm
Maximum Printable Paper Length	594 mm
Margins (Top, Bottoms, Sides)	Recommended - Top margin: 57 mm, Bottom margin: 55 mm, Left / Right: 3.4 mm (LTR / LGL: Left margin 6.4 mm, Right margin 6.3 mm) Printable area - Top margin 3 mm, Bottom margin 3 mm, Left / Right margin 3.4 mm (LTR / LGL: Left margin 6.4 mm, Right margin 6.3 mm)
Maximum Width for Borderless Printing ^[8]	A4, A3, A3+, A2, 4 x 6", 5 x 7", 8 x 10", 10 x 12", 14 x 17", 17 x 22", LTR

WHAT'S IN THE BOX?

imagePROGRAFPRO-1000
Power Cord
Print Head
12 individual ink tanks
Sample Media, LU-101 A3 x 5
Head alignment media MP-101 A4 x 2
Setup CD-ROM (CD only for Windows - Mac drivers available
online*)
Starter guide

*All drivers and mobile apps are available online at <http://www.canon.com/ijsetup>

CONSUMABLES

Ink Tank	PFI-1000 MBK/PBK/C/M/Y/PC/PM/GY/PGY/R/B/CO (80 ml)
Maintenance Cartridge	MC-20

Disclaimer

- ^[1]Ink droplets can be placed with a pitch of 1/2400 inch at minimum.
- ^[2]Print speed is based on the default setting using ISO/JIS-SCID N5 and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- ^[3]When printing ISO/JIS-SCID N2 pattern on A4 size Photo Paper Pro Platinum (PT-101) using default settings.
- ^[4]The performance of the printer may be reduced under certain temperature and humidity conditions.
- ^[5]When printing ISO/JIS-SCID N2 pattern on Photo Paper Pro Platinum using default settings.
- ^[6]Acoustic Noise is measured based on ISO7779 standard.
- ^[7]Minimum system requirements is according to that of OS and application software used.
- ^[8]Declared yield value in accordance with ISO/IEC 29103. Values obtained by continuous printing. Specifications are subject to change without notice.
- ^[9]Paper types NOT supported for borderless printing are as follows: Photo Stickers

Specifications are subject to change without notice.

