

# Product datasheet

Specifications



## APC SERVICE BYPASS PDU, 230V 16AMP Hardwire



SBP3000RMHW

### Overview

Lead time

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Output connector type	Hard wire 3-wire (H N + E) 1
Number of rack unit	2U
Provided equipment	User manual Rack mounting brackets

### Physical

Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	7.6 cm
Net weight	2.27 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted

### Input

Network frequency	50/60 Hz
Permissible voltage	220...240 V
Max line current	16 A
Input current limits	16 A
Load capacity	3000 VA
Power factor	0...1

### Output

Max current draw	16 A
Number of power socket outlets	1 IEC Jumpers

Protection type	Circuit breaker
Power cable length	1.00 m
Efficiency	99 %

### Conformance

Product certifications	VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

### Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

### Packing Units

Package 1 Height	15.1 cm
Package 1 Width	46.3 cm
Package 1 Length	29.5 cm
Package 1 Weight	3.45 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	64
Package 2 Height	135 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	225.28 kg

### Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

### Recommended replacement(s)