

3m Cat.6A S/FTP TPE Cable, Grey
Part No.: 47634



Description

- Twisted Pair Patch Cable with RJ45 connectors
- Cat.6A S/FTP PIMF
- Integrated snagless connector for latch protection
- Gold plated pins for better conductivity and elimination of signal loss
- 10 year warranty

Cat.6A S/FTP network cable with support for bandwidth up to 500MHz and features a snagless design with gold plated contacts for ethernet standards up to 10GBase-T.

The TPE Jacket is a non-toxic alternative to PVC allowing it to be used in a variety of environments, as well as being more flexible than its counterpart with a flex rating of 10 million it has high impact and tear resistance making it a very durable jacket material.

Cat.6A cable for operating frequencies up to 500MHz in shielded version with braid as overall shield and foil shield for the individual wire pairs (S/FTP). Cat.6A cables are widespread throughout the professional sector. They are ideal for Gigabit Ethernet or AV extension applications. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The TPE used as a sheath material provides increased flexibility and easy handling of cables.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m.

Technical details

Connectors:

- Connector A: RJ45 Male Cat.6A
- Connector B: RJ45 Male Cat.6A
- Housing Material: Polycarbonate
- Connector Plating: Nickel
- Pin Construction: Copper Alloy
- Pin Plating: Gold plated
- Dimensions (approx.) WxDxH: 11.6x22.8x8.3mm (0.46x0.90x0.33in)

Cable Construction:

- Length: 3m
- Colour: Grey
- Type: Cat.6A
- Jacket Diameter: 6.2mm (0.24in)
- Jacket Material: TPE
- Conductor Material: Copper
- Conductor Gauge: 28AWG
- Shielding: Aluminium Braid

Specifications:

- Supported Bandwidth: 500MHz
- Nominal Attenuation: 49.3dB/100m @500MHz
- Minimum Band Radius: 74mm (2.91in)
- Operating Temperature: -10°C - 60°C (14°F - 140°F)
- Storage Temperature: -20°C - 75°C (-4°F - 167°F)

Miscellaneous:

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: RoHS, REACH, UL, California Proposition 65

Purchasing Information:

- No.: 47634
- EAN: 4002888476348

This product is also available in other lengths

- 47630 - 0.3m (0.98ft)
- 47631 - 0.5m (1.64ft)
- 47632 - 1m (3.28ft)
- 47629 - 1.5m (4.92ft)
- 47633- 2m (6.56ft)
- 47634 - 3m (9.84ft)
- 47635 - 5m (16.44ft)
- 47636 - 7.5m (24.61ft)
- 47637 - 10m (32.81ft)
- 47638 - 15m (49.21ft)
- 47639 - 20m (65.62ft)
- 47640 - 30m (98.43ft)