

| TS-431XeU-8G | |
|--------------------------------------|---|
| CPU | AnnapurnaLabs Alpine AL-314 32-bit ARM® Cortex-A15 quad-core 1.7GHz processor |
| CPU Architecture | 32-bit ARM |
| Floating Point Unit | Yes |
| Encryption Engine | Yes |
| System Memory | 8 GB SODIMM DDR3 (1 x 8 GB) |
| Maximum Memory | 8 GB (1 x 8 GB) |
| Memory Slot | 1 x SO-DIMM DDR3 |
| Flash Memory | 512MB (Dual boot OS protection) |
| Drive Bay | 4 x 3.5-inch |
| Drive Compatibility | 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives |
| Hot-swappable | Yes |
| SSD Cache Acceleration Support | Yes |
| Gigabit Ethernet Port (RJ45) | 2 |
| 10 Gigabit Ethernet Port | 1 x 10GbE SFP+ |
| Jumbo Frame | Yes |
| USB 3.0 port | 4 |
| Form Factor | 1U Rackmount |
| LED Indicators | HDD 1-4, Status, USB, LAN1-3 |
| Buttons | Power, Reset |
| Dimensions (HxWxD) | 44 × 439 × 291 mm |
| Weight (Net) | 4.15 kg |
| Weight (Gross) | 5.78 kg |
| Operating temperature | 0 - 40 °C (32°F - 104°F) |
| Relative Humidity | 5~95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | Open-frame 100W, Input: 100V-240V ~ / 3.5A, 50Hz-60Hz |
| Power Consumption: HDD Sleep Mode | 14.42 W |
| | |

| Power Consumption: Operating Mode, Typical | 30.99 W |
|---|------------------------------|
| | With drives fully populated |
| Fan | 3 x 4 cm system fan (12V DC) |
| Sound Level | 20.3 db(A) |
| System Warning | Buzzer |
| Kensington Security Slot | Yes |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

Designs and specifications are subject to change without notice.

^{*} Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.