



Highlights

- Capacities up to 12TB¹ in proven air-based HDD platform design
- Delivers high IOPS to data intensive applications
- Superior reliability of field-proven hardware and firmware designs
- Seamless integration with existing applications & environments

Target Audience

- Data Center Architects
- IT Administrators
- Data Center Managers
- AI System Administrators

Ideal for

- Hyperscalers and High Performance Computing (HPC)
- Artificial Intelligence training pools
- Converged infrastructures
- Cloud and hybrid cloud environments

Ultrastar® DC HA340 Data Center HDD

Ultrastar® Data Center HA340 hard drives are medium capacity air-filled HDDs that deliver high IOPS to support data intensive applications with proven durability and reliability.

Delivers High IOPS with Proven Technology

A unique combination of **field-proven hardware** with the latest innovative technologies enables these air-filled drives to deliver high IOPS to data intensive applications.

Optimized Performance and Durability

Performance-optimized to deliver **higher access densities (IOPS/TB)** to data intensive applications with proven durability.

Rapid Qualification and Integration

Leveraging hardware designs from **generations of highly successful products** ensures easy qualification, seamless integration and rapid adoption.

Reliability You Can Trust

Built off the same platform that is **deployed in thousands of data centers around the world**, these drives deliver superior dependability and field-proven reliability for hassle free data storage.

Protected Against Vibration & Shock

Our exclusive **Rotational Vibration Safeguard (RVS)** uses dual sensors to anticipate and counteract disturbances, maintaining peak performance in high-vibration environments. Combined with **Dynamic Fly Height technology**, Western Digital offers exceptional drive reliability and protection from unexpected shock events.

Trusted Reliability, Quality and World-Class Support

As an **industry-leading hard drive manufacturer**, Western Digital stands behind their Ultrastar hard drives with the assurance of a **2.0M-hour MTBF rating, a 5-year limited warranty⁸** and world-class support services to help create environments for data to thrive.



Specifications

Ultrastar DC HA340 HDD Models			
Capacity ¹ (TB)	Part Number	Model Number	
12TB	0B47061	WUS721212BLE604	
	0B47063	WUS721212BLE6L4	
	0B47060	WUS721210BLE604	
10TB	0B47062	WUS721210BLE6L4	
	0B46951	WUS721208BLE604	
8TB	0B47078	WUS721208BLE6L4	
	0B46950	WUS721206BLE604	
6TB	0B47077	WUS721206BLE6L4	
	0B46940	WUS721204BLE604	
4TB	0B47076	WUS721204BLE6L4	

Configuration			
Interface	SATA 6Gb/s		
Format: Sector size (bytes) ²	512e: 512		
Areal density (Gbits/sq. in.)	6-12TB	1022	
	4TB	834	

Performance			
Data buffer ³ (MB)	10-12TB	512	
	4-8TB	256	
Rotational speed (RPM)	7200		
Latency average (ms)	4.16		
Interface transfer rate (max)	6 Gb/s		
Sustained transfer rate ⁴ (MB/s, max) / (MiB/s, max)	267 / 255		
Random Read ⁴ IOPS (4K, QS16)	10-12TB	150	
	4-8TB	154	
Random Write ⁴ 4KB IOPS (4K, QS16)	10-12TB	465	
	4-8TB	425	

Environmental Specifications (Operating)	
Temperature	5° C to 60° C
Shock (half-sine wave 2 ms, G)	70
Vibration (G RMS 5 to 500 Hz)	0.67 (XYZ)

Environmental Specifications (Non-Operating)		
Ambient Temperature	-40° to 70° C	
Shock (half-sine wave, G)	10-12TB	250
	4-8TB	300
Vibration (G RMS 2 to 200 Hz)	1.04 (XYZ)	

¹ One MB is equal to one million bytes, one GB is equal to one billion bytes and one TB equals 1,000GB (one trillion bytes). Actual user capacity may be less due to operating environment.

² Advanced Format drive: 4K (4096-byte) physical sectors.

³ Portion of buffer capacity used for drive firmware.

⁴ Based on internal testing; performance may vary depending on host environment, drive capacity, logical block address (LBA), and other factors. The location of the max rate is at approximately 10% into the capacity of the HDD. 1MiB = 1,048,576 bytes (2²⁰), 1MB = 1,000,000 bytes (10⁶).

⁵ This product has an AFR specification rating based on typical workload and temperatures. The AFR specification is based on a sample population and is estimated by statistical measurements and acceleration algorithms under typical operating conditions at 40°C device reported temperature. Derating of AFR and max rated workload will occur above these parameters. AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.

⁶ Idle specification is based on use of Idle_A.

⁷ 5°C ambient temperature, 60°C device reported temperature.

⁸ See <http://support.wd.com/warranty> for regional specific warranty details.



5601 Great Oaks Parkway
San Jose, CA 95119, USA
www.westerndigital.com

© 2024 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the Western Digital design, the Western Digital logo and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. All other marks are property of their respective owners. References in this publication to Western Digital products, programs, or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications that are subject to change and do not constitute a warranty. Please visit the Support section of our website, www.westerndigital.com, for additional information on product specifications. Pictures shown may vary from actual products.

Ultrastar DC HA340 HDD Models	
Reliability	
Error rate (non-recoverable, bits read)	1 in 10 ¹⁶
Load/Unload cycles (at 40°C)	600,000
Availability (hrs/day x days/wk)	24x7
MTBF (hours, projected)	2,000,000
Annualized Failure Rate ⁵ (AFR, projected)	0.44%
Limited Warranty	5 Years

Power Management		
Requirement	+5 VDC, +12VDC	
Operating (W, typical) ⁷	10-12TB	9.2
	6-8TB	8.0
	4TB	7.0
Idle ⁶ (W)	10-12TB	8.4
	6-8TB	6.7
	4TB	5.8
Power consumption efficiency at idle (W/TB)	12TB	0.7
	8-10TB	0.84
	6TB	1.12
	4TB	1.45

Physical Dimensions		
Height (max)	1.028 in. (26.1 mm) max	
Length (max)	5.787 in. (147.0 mm) max	
Width (max, ± .01 in.)	4.0 in. (101.6 mm)	
Weight (max, ± 10%)	10-12TB	1.65 lb. (750 g)
	4-8TB	1.58 lb. (715 g)

Acoustics		
Idle/Operating (Bels, typical)	10-12TB	3.4 / 3.9
	4-8TB	2.9 / 3.6

How to Read the Ultrastar Model Number

WUS721212BLE6y4

W = Western Digital
U = Ultrastar
S = Standard (vs. H for Helium)
72 = 7200 RPM
12 = Full capacity (12TB)
12 = Capacity this model (12TB)
B = Generation code
L = 26.1 z-height (mm)

xx = Interface
E6 = 512e SATA 6 Gb/s
y = Power Disable Pin 3 status
0 = Power Disable Pin 3 support
L = Legacy Pin 3 config - no Power Disable support
z = Data Security Mode
4 = Base (SE)*: No Encryption.
Sanitize Overwrite only.