



0.5m USB 3.2 Type C Cable, 90° Right Angle, 10Gbps

32017

TITLE EN

0.5m USB 3.2 Type C Cable, 90° Right Angle, 10Gbps

SUBTITLE EN

USB Type C Male to Male

SHORT DESCRIPTION EN

- Entry level USB 3.2 Type C cable for home and small office applications
 - One USB Type C plug angled at 90°
 - Supports data rates of up to 10Gbps
 - Robust PVC housing with nickel-plated contacts
 - 10 year warranty
- LINDY USB 3.2 Type C cables feature double shielded construction with copper conductors for premium performance and corrosion resistance. Nickel connectors and gold plated contacts maintain signal integrity and reliability.
- USB cables with angled plugs protect the USB ports of your devices by reducing pressure and preventing cable breakage, making them ideal for confined spaces and hard-to-reach ports.
- Data transfer speeds up to 10Gbps are supported for the quick and effortless transfer of large data volumes.
- USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.
- USB 3.2 Type C, 90° Right Angle cables are available in the following lengths: 0.5m, 1m, 1.5m.

Connectors

- Connector A: USB 3.2 Type C Male
- Connector B: USB 3.2 Type C Male 90° Right Angle
- Housing Material: PVC
- Shielding in head shell: -
- Connector Plating: Nickel
- Pin Construction: Copper
- Pin Plating: Gold
- Dimensions (approx.) WxDxH:
 - USB Type C: 6.4x38x12.3mm (0.25x1.5x0.48in)
 - USB Type C: 11.1x25.8x24.2mm (0.44x1.02x0.95in)

Cable Construction

- Length: 0.5m (1.64ft)
- Standard: USB 3.2 Gen 2 (USB 3.1 Gen 2, USB 3.1)
- Power Delivery: PD 2.0
- Max. Power: 60W
- Colour: Black
- Type: Round
- Jacket Diameter: 5mm (0.2in)
- Jacket Material: PVC
- Conductor Material: Copper
- Conductor Gauge Power: 22 AWG
- Conductor Gauge Data: 28 AWG
- Shielding: Aluminium Foil 110%

Specifications

- Supported Bandwidth: 10Gbps
- Nominal Attenuation: 0.5Mhz- 400Mhz < 5.8db
- Minimum Bend Radius: 50mm (1.97in)
- Operating Temperature: 0°C - 40°C (32°F - 104°F)
- Storage Temperature: 0°C - 70°C (32°F - 158°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Product Compliance: RoHS, REACH, California Proposition 65, UL (Raw Cable)

Purchasing Information

- No.: 32017
- EAN: 4002888320177

This product is also available in other lengths

- 32017 - 0.5m (1.64ft)
- 32018 - 1m (3.28ft)
- 32019 - 1.5m (4.92ft)