

4x4 USB 3.2 Gen 1 Type A/C Matrix Switch

No.: 43429

Share 4 USB devices between 4 computers

Description

- Supports USB 3.2 Gen 1 (USB 3.0), USB 2.0/1.1 backwards compatibility
- Switching between computers with buttons, TCP/IP, web GUI or RS-232 commands
- Matrix switch with presets function
- Plug & Play, no software required
- 3 year warranty

The Lindy 4x4 USB 3.2 Gen 1 Type A/C Matrix Switch provides a flexible and efficient solution for routing and sharing USB devices across multiple systems. It enables up to four host computers to access two USB Type A and two USB Type C devices in a wide range of configurations, controlled directly from the front panel, via an intuitive web-based GUI, or through RS-232 commands for system automation and integration.

Users can store up to eight preset configurations and easily rename connected hosts and devices for organized and efficient workflows. This ensures quick device switching and seamless operation in complex setups.

Designed for professional environments, the matrix switch is ideal for sharing peripherals such as printers, external drives, and webcams in offices, conference rooms, or industrial systems. It supports the full USB 3.2 Gen 1 bandwidth with transfer rates up to 5Gbps, while maintaining compatibility with USB 2.0 and 1.1 devices, ensuring reliable performance across PCs and Macs.

Information about USB 3.0, 3.1 & 3.2
USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.
USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.
USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Technical details

Specifications

- USB Standard: USB 3.2 Gen 1
- Supported Bandwidth: 5 Gbps
- Chipset: -
- Compatibility: USB equipped computers
- Power Delivery: -
- Special Features: Switching by buttons; web GUI, RS-232 commands

Connectors

- Inputs: 2 x USB 3.2 Type B (Female), 2 x USB 3.2 Type C (Female)

Outputs: 2 x USB Type A (Female), 2 x USB Type C (Female)
Control ports: RJ-45 (Female), RS-232 3-Pin Terminal Block
Power: 5.5/2.1mm

Physical Properties

Dimensions WxDxH: 270x166x30mm (10.63x6.54x1.18in)
(Fixed) Cable Length: -
Housing Material: Metal
Net Weight: 1.16kg (2.56lb)
Operating Temperature: 0°C - 40°C (32°F - 104°F)
Storage Temperature: -20°C - 60°C (-4°F - 140°F)
Humidity: 10 - 90% RH (non-condensing)
Power Requirements: 24V 3.75A
Colour: Black

Miscellaneous

Packaging Type: Carton box
Packaging Dimensions: 350x235x90mm (13.78x9.25x3.54in)
Gross Weight: 2.2kg (4.85lb)
Warranty (Years): 3
Product Compliance: CE, FCC, RoHS & REACH, California Proposition 65

Package Contents

4x4 USB 3.2 Gen 1 Type A/C Matrix Switch
IR Remote
IR Receiver Cable, 1.5m
2x USB 3.2 Gen 1 Type A-B Cable, 1.8m
Mounting Ears
Multi-country Power Supply (UK, EU, US & AUS)
Lindy Manual

Purchasing Information

No.: 43429
EAN: 4002888434294

© LINDY 2026