



30W USB Type A & C Charger UK Plug

73425

TITLE EN

30W USB Type A & C Charger

SUBTITLE EN

Charge two devices simultaneously with PD support

SHORT DESCRIPTION EN

- Charges and powers two devices simultaneously via a USB Type C and a USB Type A port
- 30W Power Delivery via the USB Type C port provides fast charging for smartphones, tablets, laptops and other mobile devices
- Compact design for maximum mobility
- Built-in safety features such as overvoltage and overcurrent protection
- 2 year warranty

The Lindy 30W USB Type A & C PD Charger can charge two devices simultaneously. 30W Power Delivery are supported by the USB Type C port while the USB Type A port provides fast charging with up to 18W. When both ports are used in parallel a maximum power of 15W will be provided.

Featuring both a USB Type C female and a USB Type A female port this charger is ideal for use with most popular smartphones and iOS devices. Supporting power delivery of 30W, connected devices can be provided with faster charging than what is possible from a standard Type C or A charger supplied with many devices.

For safe charging the device includes overcharge, overcurrent, overtemperature and short circuit protection. As this charger is rated at Level 6 for efficiency, it also meets the highest current level of energy efficiency standards.

LONG DESCRIPTION EN

Connectors

- Input: UK Plug
- Output: 1x USB Type A Female, 1x USB Type C Female

Specifications

- Power Input: 100-240VAC, 50/60Hz 0.6A
- Power Output
 - USB Type A: 5V 3A, 9V 2A, 12V 1.5A
 - USB Type C: 5V 3A, 9V 3A, 12V 2.5A, 15V 2A, 20V 1.5A, PPS33 11V 2.7A, PPS33 16V 1.88A
 - USB Type A & C: 5V 3A
- USB Power Delivery: PD 3.0 (USB Type C port)
- Max. Total Power: 30W
- Output Voltage Accuracy: $\pm 5\%$
- Average Active Efficiency: 81.38%
- Efficiency at Low Load (10%): 80.06%
- No-load Power Consumption: 0.1 W
- Additional Features: Overcurrent, overvoltage, overtemperature and short-circuit protection

Physical Properties

- Dimensions (approx.) WxDxH: 26.80x85.30x41.60mm (1.05x3.35x1.63in)
- Connector Material: Copper
- Housing Material: PVC
- Net Weight: 0.04kg (0.09lb)
- Operating Temperature: 0°C - 25°C (32°F - 77°F)
- Operating Humidity: 20 – 90% RH (non-condensing)
- Storage Temperature: -20°C - 70°C (-4°F - 158°F)
- Storage Humidity: 20 – 90% RH (non-condensing)
- Colour: White

Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 80x100x45mm (3.15x5.12x1.77in)
- Gross Weight: 0.06kg (0.13lb)
- Warranty (Years): 2
- Product Compliance: CE, RoHS, REACH, ErP, UKCA

Package Contents

- 30W USB Type A & C PD Charger
- Lindy Manual

Purchasing Information

- No.: 73425
- EAN: 4002888734257