

# Rittal – The System.

Faster – better – everywhere.

## Door-operated switch for LED system light – SZ 2500.460

Date : Jun 16, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Door-operated switch for LED system light – SZ 2500.460

created: 16.06.2021 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



| Product description                      |  |
|--|--|
| Design:                                  | With connection cable  |
| Description:                             | For time-saving and simple installation of the LED system light. |
| Colour:                                  | Black  |
| Protection category<br>IP to IEC 60 529: | IP 40  |
| Supply includes:                         | Assembly parts   |

| Product description          |   |
|------------------------------|---|
| Dimensions:                  | Width: 31 mm<br>Height: 78 mm<br>Depth: 30 mm<br>Length: 800 mm |
| Rated operating<br>voltage:  | 230 V<br>24 V (DC)  |
| Cross-section:               | 0.75 mm <sup>2</sup><br>AWG 18                                  |
| For rated current<br>(max.): | 1 A   |
| Packs of:                    | 1 pc(s).  |

|                                      |   |
|--------------------------------------|---|
| <b>Weight/pack:</b>                  | 0.12 kg   |
| <b>Copper weight (kg per piece):</b> | 0   |
| <b>EAN:</b>                          | 4028177809178   |
| <b>Customs tariff number:</b>        | 85365080  |
| <b>ETIM 7.0:</b>                     | EC002626  |
| <b>ETIM 6.0:</b>                     | EC002626  |
| <b>eCl@ss 8.0/8.1:</b>               | 27189266  |
| <b>eCl@ss 6.0/6.1:</b>               | 27119116  |
| <b>Product description:</b>          | SZ Door-operated switch, with connection wire, L: 800 mm, black |
| <b>Approvals</b>                     |   |
| <b>Approvals:</b>                    | CCC<br>CQC  |
| <b>Certificates:</b>                 | EAC   |
| <b>Declarations:</b>                 | Declaration of conformity                                       |