

# ML750i

Powerful Projection in the Palm of Your Hand



- **Ultra-portable and travel-ready – Big screen power in a compact design for work or play**
- **Seamless sharing and smart controls – Mirror, cast, and control from any device, no PC required**
- **Instant setup made easy – Get a clear, aligned picture in seconds with auto keystone and focus**
- **Compact & Lightweight 0.84 lbs**

Small in size, huge on performance—the ML750i ultra-portable LED projector is your go-anywhere, do-anything display solution. Weighing less than 1 pound (0.88 lbs) and compact enough to fit in your hand, it's perfect for travel between home, office, or wherever inspiration strikes. Whether you're gaming, streaming movies, or pitching the next big idea, the ML750i delivers stunning image quality without compromise.

Experience bright, razor-sharp visuals with wide XGA resolution and projection sizes from 50" to 100" for big-screen impact anywhere. With built-in memory, media player, office viewer, and speaker, you can project without a laptop. Just plug in a USB drive or microSD card—or stream straight from your device via HDMI.

Quick setup is a breeze thanks to auto keystone and focus adjustment. Game lag-free with a blazing 16.6ms response time at 1080p60. Personalize your interface and cast wirelessly with Android 9.0 and Creative Cast. Includes 3.5mm audio out, RS232 via mini USB, and FOTA support. Ready when you are.

# Specifications

EAN: 5055387668324, Colour: White+Gray

UPC: 796435 44 746 5, Colour: White+Gray



## Display/image

Display technology	DLP®
Resolution	WXGA (1280x800)
Brightness (HK/ANSI)	700/450
Contrast ratio	20,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	85%
Screen size	0.76m ~ 2.03m (30" ~ 80") diagonal

## Lamp info

Light source type	LED
LED life	20,000 hours

## Optical

Throw ratio	1.5:1
Projection distance (m)	0.55m - 3.23m
Zoom type	Fixed
Focal length (mm)	14.95
Native offset	100%

## Connectivity

Connections	<b>Inputs</b> 1 x HDMI 1.4b, 1 x microSD card, 1 x USB-A reader <b>Outputs</b> 1 x Audio 3.5mm <b>Control</b> 1 x RS232 (via mini USB connector)
-------------	--

## General

Noise level (min)	29dB
Noise level (max)	32dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz)
3D compatibility	SVGA 120Hz, XGA 120Hz
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	12 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
360° operation	Yes
Operating conditions	0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500m
Remote control	Card style
Speaker count	1
Watts per speaker	2W
In the box	Carry bag Universal I/O cable AC power cord Remote control 1x CR2032 Battery Basic user manual 1x RS232 Mini-USB adaptor
Input lag	16.00ms
Optional wireless models	EZC-USB

## Power

Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	23W
Power consumption (max)	67W

## Weight and dimensions

Dimensions (W x D x H) mm	105 x 106 x 39
Gross weight	1.31 kg
Net weight	0.425 kg