



---

**INFORMATION**

---

## 27" IPS monitor with 120Hz performance and eye comfort features



The ProLite X2791HS features a 27" Full HD display with a sleek 4-side ultra slim bezel design, helping you create a clean and modern multi-monitor workspace.

The IPS panel delivers sharp detail, vivid colours and consistent brightness from all angles. With a fast 120Hz refresh rate, visuals remain smooth and responsive, whether you're working on complex tasks or enjoying multimedia. Flicker-free technology and a blue light reducer enhance eye comfort, especially during extended use.

Integrated speakers and a headphone socket support a clutter-free desk setup while providing convenient audio for calls. With EPEAT Silver registration, TCO Certified compliance and an Energy Label C rating, the X2791HS supports both efficient work and responsible energy use.



## Multi-screen setup for a panoramic workspace

Connect multiple ultra-slim bezel monitors to create a panoramic workspace, keep your apps in view, streamline multitasking, and boost productivity.



## Built-in audio without extra clutter

Enjoy clear, pleasant sound for calls, videos, and music while keeping your desk free of extra speakers, thanks to the integrated audio.



## Reveal hidden details with deeper contrast

With a native contrast ratio of 1500:1, this monitor brings out subtle shadow nuances and fine tonal transitions. You see more image information at a glance, making it easier to make precise creative choices during editing and colour grading. Dark areas stay crisp and distinct without blending into one another.



## Reduced eye strain & fatigue

Work, study or play longer without eye fatigue, thanks to flicker-free technology and reduced blue light emissions. These features help minimize eye strain and improve visual comfort, allowing you to stay focused and productive throughout the day.

**01** **DISPLAY CHARACTERISTICS**

<b>Design</b>	4-side slim bezel
<b>Diagonal</b>	27", 68.6cm
<b>Panel</b>	IPS panel technology LED, matte finish
<b>Native resolution</b>	1920 x 1080 @120Hz (2.1 megapixel Full HD)
<b>Aspect ratio</b>	16:9
<b>Panel brightness</b>	350 cd/m <sup>2</sup>
<b>Static contrast</b>	1500:1
<b>Advanced contrast</b>	80M:1
<b>Response time (MPRT)</b>	1ms
<b>Viewing zone</b>	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
<b>Colour support</b>	16.7mln (sRGB: 99.7%; NTSC: 72%)
<b>Horizontal Sync</b>	30 - 140kHz
<b>Viewable area W x H</b>	597.9 x 336.3mm
<b>Pixel pitch</b>	0.311mm
<b>Colour</b>	matte, black (matte, black)

**02** **INTERFACES / CONNECTORS / CONTROLS**

<b>Signal input</b>	HDMI x1 (v.1.4) DisplayPort x1 (v.1.2)
<b>HDCP</b>	yes
<b>Headphone connector</b>	yes

**03** **FEATURES**

<b>Blue light reducer</b>	yes
<b>Flicker free</b>	yes
<b>Adaptive Sync support</b>	yes
<b>Extra</b>	i-style Colour
<b>OSD languages</b>	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
<b>Control buttons</b>	Joystick: Power/Menu (Centre), Up/Signal Select, Down, Left/Submenu, Right/Volume
<b>User controls</b>	colour settings (i-Style colour, blue light reducer, RGB range, colour temperature, user preset), OSD (OSD H. position, OSD V. position, OSD time, OSD background, DDC/CI control, display information), language, extra 1 (sharpness, video mode adjust, opening logo, power LED), extra 2 (shortcut key), input select, audio settings (volume, mute audio), reset (reset all?)
<b>Speakers</b>	2 x 2W
<b>Convenience</b>	Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX

**04** **MECHANICAL**

Display position	tilt adjustments
Tilt angle	20° up; 3° down
VESA mounting	100 x 100mm
Cable management system	yes

## 05 ACCESSORIES INCLUDED

Cables	power (1.5m), HDMI (1.5m)
Other	quick start guide, safety guide

## 06 POWER MANAGEMENT

Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	14W typical, 0.5W stand by, 0.3W off mode

## 07 SUSTAINABILITY

Regulations	TCO Certified, CE, TÜV-GS, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA
Energy efficiency class (Regulation (EU) 2017/1369)	C
EPEAT Silver	*registration varies by country, go to <a href="http://www.epeat.net">www.epeat.net</a> for details
REACH SVHC	above 0.1%: Lead, Lead monoxide, Diboron trioxide

## 08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	611.5 x 427.5 x 190mm
Box dimensions W x H x D	688 x 442 x 126mm
Weight (without box)	3.8kg
Weight (with box)	5.8kg
EAN code	4948570127412
Safety name	PL2791HA

---

GALLERY

---





All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED