

# Product datasheet

Specifications



## APC Easy UPS BVX 2200VA, 230V, AVR, Schuko Sockets

BVX2200LI-GR

### Overview

Lead time

### Main

Input voltage	230 V AC 1 phase
Output voltage	230 V AC 1 phase
Rated power in W	1200 W
Rated power in VA	2200 VA
Plug standard	Schuko
Nb of power socket outlets	4 Schuko
Cable length	1.22 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User manual

### General

Max runtime	240 min
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

### Physical

Colour	Black
Height	19 cm
Width	14 cm
Depth	39 cm
Net weight	12.2 kg
Mounting support	Floor
Mounting preference	No preference

Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	140...300 V 230 V AC
Cos phi	0.54

## Output

Maximum configurable power in W	1200 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 1200 W
Graph display	1
Half load runtime	00:08:30 600 W
Maximum configurable power in VA	2200 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance

Product certifications	CE CB
Equipment protection policy	Lifetime : 50000 euros

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...3000 m
Acoustic level	40 dBA
IP degree of protection	IP20

## Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	24 V
Battery capacity	9.0 Ah
Battery life	2...3 year(s)
Replacement battery	<a href="#">APCRBC177</a> 

---

Extended runtime	0
------------------	---

## Communications & Management

---

Control panel	LED Status display with on line : on battery
Alarm	Alarm when on battery : distinctive low battery alarm

---

## Surge Protection and Filtering

---

Surge energy rate	273 J
-------------------	-------

---

## Packing Units

---

Package 1 Weight	13.2 kg
Package 1 Height	29.7 cm
Package 1 Width	23.5 cm
Package 1 Length	49.5 cm
SCC14	10731304404627

---

## Offer Sustainability

---

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	--------------------------------------------------

---

## Contractual warranty

---

Warranty	2 years repair or replace
----------	---------------------------

---