Product data sheet

Specifications



APC NetShelter Rack PDU Advanced Switched Metered, 2U, 3 Phase, 415V, 41.4kVA 60A, 18 Outlets

APDU11454SM

Main

Product or Component Type	PDU
Main Input Voltage	415 V AC 3 phase
Input current limits	60 A
Input Frequency	50/60 Hz
Main Output Voltage	415 V AC 3 phase
Input Connection Type	IEC 309 60 A
Number of power socket outlets	9 C13/C15/C19/C21 9C13/C15
PDU Type	Switched metered outlet
Protection Type	Circuit breaker
Number of rack unit	2U

Complementary

Mounting Location	Front Rear
Mounting Mode	Rack-mounted
Mounting position	Horizontal
Height	3.3 in (85 mm)
Width	17.4 in (443 mm)
Depth	29.5 in (750 mm)
Net Weight	35.9 lb(US) (16.3 kg)

Environmental

IP Degree of Protection	IP44
Relative Humidity	5…90 %
Storage Relative Humidity	5…95 %
Ambient Air Temperature for Storage	-4…140 °F (-20…60 °C)
Storage altitude	0…50000 ft (0…15240 m)
Operating altitude	0...10000 ft
Ambient Air Temperature for Operation	23…140 °F (-5…60 °C)

Ordering and shipping details

GTIN	731304775713

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	37.008 in (94 cm)
Package 1 Width	23.6 in (60 cm)
Package 1 Length	6.5 in (16.5 cm)
Package weight(Lbs)	50.3 lb(US) (22.8 kg)

Contractual warranty

Warranty (in months)	36

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Average percentage of recycled plastic content	15 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	7547f066-9302-46d9-96e9-461928dd6901
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.
PVC free	No
Silicon free	Yes

Use Longer

Lifetime extension

Upgradeability	Yes

Use Again

Repack and remanufacture

Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative






B9
L3-N
B6
L2-N
B3
L1-N
B8
L3-N
B5
L2-N
B2
L1-N
B7
L3-N
B4
L2-N
B1
L1-N