





# Rack PDU, Switched, 1U, 12A/208V, 10A/230V, (8)C13

AP7920B

О				

**Presentation** 

This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.

Lead time

#### Main

Main Input Voltage	200 V 208 V 230 V
Main Output Voltage	208 V 230 V
Input Connection Type	IEC 60320 C14
Number of rack unit	1U
Cable length	1.98 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets User manual

#### **Physical**

Colour	Black
Height	4.4 cm
Width	44.5 cm
Depth	10.8 cm
Net weight	2.27 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

#### Input

[In] rated current 12 A

Permissible voltage	200240 V
Input current limits	15 A
Load capacity	2300 VA
Network frequency	50/60 Hz

# Output

Rated current	10 A - 230 V 12 A - 208 V

Number of power socket outlets 8 IEC 60320 C13

## Conformance

Product certifications	cUL listed CE CSA GOST IRAM UL listed VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 UL 60950

## **Environmental**

Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7 cm
Package 1 Width	34.3 cm
Package 1 Length	47 cm
Package 1 Weight	3.45 kg

# Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
Optimized Energy Efficiency	Energy efficient product	

Take-back

Take-back program available

## **Contractual warranty**

Warranty

2 years repair or replace

Recommended replacement(s)