

Overview

Aruba 370 Series Access Points

High performance 802.11ac Wave 2 for outdoor environments

Weatherproof and temperature-hardened, the Aruba 370 Series Access Points deliver multi-gigabit Wi-Fi to outdoor and environmentally challenging locations. With a maximum aggregate data rate of over 2 Gbps (2.4GHz: 300Mbps; 5GHz: 1,733 Mbps), the 370 Series comes with multi-user MIMO (MU-MIMO), 4 spatial streams (4SS), and optional 160MHz channel bandwidth (VHT160) to quickly add performance and capacity to existing or new wireless networks.

Able to survive in harsh outdoor environments, the 370 Series can withstand exposure to high and low temperature extremes, windspeeds up to 165 mph, and tolerate persistent moisture, precipitation, and dust and salt sprays for extended periods of time. All electrical interfaces include industrial strength surge protection.

To simplify policy enforcement, the Aruba 370 Series uses Aruba's policy enforcement firewall (PEF) feature to encapsulate all traffic from the AP to the Mobility Controller (or Gateway) for end-to-end encryption and inspection. Policies are applied based on user role, device type, applications, and location. This reduces the manual configuration of SSIDs, VLANs and ACLs. PEF also serves as the underlying technology for Aruba Dynamic Segmentation.

The 370 Series includes Aruba's patented ClientMatch technology to eliminate sticky client issues while optimizing 802.11ac Wave 2 performance. These APs continuously gather session performance metrics to steer mobile devices to the best-available AP - even while users roam. With MU-MIMO awareness, ClientMatch can group MU-MIMO capable devices together to increase network capacity and efficiency. ClientMatch also participates in Aruba's AI-powered Mobility solution.

Like all Aruba Wi-Fi 6 APs, the 370 Series includes an integrated Bluetooth Low Energy radio to simplify the deployment and management of location services, asset tracking services, security solutions and IoT sensors. This allows organizations to leverage the 370 Series as an IoT platform, which eliminates the need for an overlay infrastructure and additional IT resources.



Aruba 370 Series Access Points

Standard Features

Unique Benefits

- WPA3 and Enhanced Open
 - Support for stronger encryption and authentication is provided via the latest version of WPA for enterprise protected networks.
 - Enhanced Open offers seamless new protection for users connecting to open networks where each session is automatically encrypted to protect user passwords and data on guest networks.
- WPA2-MPSK
 - MPSK enables simpler passkey management for WPA2 devices – should the Wi-Fi password on one device or device type change, no additional changes are needed for other devices. Requires ClearPass Policy Manager.
- VPN Tunnels
 - In Remote AP (RAP) and IAP-VPN deployments, the Aruba 318 Series can be used to establish a secure SSL/IPSec VPN tunnel to a Mobility Controller that is acting as a VPN concentrator.
- Trusted Platform Module (TPM)
 - For enhanced device assurance, all Aruba APs have an installed TPM for secure storage of credentials and keys, and boot code.
- Flexible operations and management
 - Controller-less (Instant) mode - For enhanced device assurance, all Aruba APs have an installed TPM for secure storage of credentials and keys, and boot code.
 - Mobility Controller mode - For optimized network performance, roaming and security, APs tunnel all traffic to a mobility controller for centrally managed traffic forwarding and segmentation, data encryption, and policy enforcement.
 - Other management options - Available management solutions include Aruba Central (cloud-managed) or Aruba AirWave – a multi-vendor on-premises management solution. For large installations across multiple sites, APs can be factory-shipped and can be activated with Zero Touch Provisioning through Aruba Central or AirWave. This reduces deployment time, centralizes configuration, and helps manage inventory..
- Additional Features
 - Zero Touch Provisioning - APs can be factory-shipped and zero-touch provisioned through Aruba Central or AirWave using a cloud-based service to reduce deployment time, centralize configuration, and manage inventory.
 - Advanced Cellular Coexistence - Minimizes interference from 3G/4G LTE cellular networks, distributed antenna systems (DAS), and commercial small cell or femtocell equipment.
 - Hardened, industrial design - Extends the temperature range capabilities of indoor access points for environments that lack heating and cooling. It also provides sealed connector interfaces to protect against dust and moisture.

Other Interfaces

- One 10/100/1000BASE-T Ethernet network interfaces (RJ-45)
 - Auto-sensing link speed and MDI/MDX
 - 802.3az Energy Efficient Ethernet (EEE)
- One 1000BASE-X SFP Port
- Bluetooth Low Energy (BLE) radio
 - Up to 4 dBm transmit power (class 2) and -91 dBm receive sensitivity
- Visual indicator (multi-color LED): For system and radio status
- Reset button: Factory reset (during device power up)
- Micro USB console interface
- Kensington security slot

Mounting

- AP-270-MNT-V1
 - AP-270-MNT-V2
 - AP-270-MNT-H1
 - AP-270-MNT-H2
-



Standard Features

Aruba 370 Series Specifications

- AP-374
 - 5 GHz 802.11ac 4x4 MU-MIMO (1,733 Mbps max rate)
 - o Four Nf connectors for external antenna operation
 - 2.4 GHz 802.11n 2x2 MIMO (300 Mbps max rate) radios
 - o Two Nf connectors for external antenna operation at 2.4 GHz.
 - AP-375
 - 5 GHz 802.11ac 4x4 MU-MIMO (1,733 Mbps max rate)
 - o Internal Omni Antennas 4.6 dBi
 - 2.4 GHz 802.11n 2x2 MIMO (300 Mbps max rate) radios
 - o Internal Omni Antennas 4.0 dBi
 - AP-377
 - 5 GHz 802.11ac 4x4 MU-MIMO (1,733 Mbps max rate)
 - o Internal 80°H x 80°V Directional Antennas 6.3 dBi
 - 2.4 GHz 802.11n 2x2 MIMO (300 Mbps max rate) radios
 - o Internal 80°H x 80°V Directional Antennas 6.4 dBi
-

Power

- Worst-case power consumption from the AP: 23W
 - Power sources sold separately
 - Power over Ethernet (PoE+): 802.3at-compliant
 - AC Power: 100-240 Volt 50/60Hz AC
-



Configuration Information

BTO Models

Remarks	Description	SKU
	370 Unified Outdoor Access Points	
	Aruba AP-374 (RW) 802.11n/ac Dual 2x2:2/4x4:4 Radio 6xNf Connectors Outdoor AP	JZ162A
	Aruba AP-374 (US) 802.11n/ac Dual 2x2:2/4x4:4 Radio 6xNf Connectors Outdoor AP	JZ163A
	Aruba AP-374 (EG) 802.11n/ac Dual 2x2:2/4x4:4 Radio 6xNf Connectors Outdoor AP	JZ159A
	Aruba AP-374 (IL) 802.11n/ac Dual 2x2:2/4x4:4 Radio 6xNf Connectors Outdoor AP	JZ160A
	Aruba AP-374 (JP) 802.11n/ac Dual 2x2:2/4x4:4 Radio 6xNf Connectors Outdoor AP	JZ161A
	Aruba AP-375 (RW) 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Omni Antenna Outdoor AP	JZ172A
	Aruba AP-375 (US) 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Omni Antenna Outdoor AP	JZ173A
	Aruba AP-375 (EG) 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Omni Antenna Outdoor AP	JZ169A
	Aruba AP-375 (IL) 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Omni Antenna Outdoor AP	JZ170A
	Aruba AP-375 (JP) 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Omni Antenna Outdoor AP	JZ171A
	Aruba AP-377 (RW) 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Directional Antenna Outdoor AP	JZ182A
	Aruba AP-377 (US) 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Directional Antenna Outdoor AP	JZ183A
	Aruba AP-377 (EG) 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Directional Antenna Outdoor AP	JZ179A
	Aruba AP-377 (IL) 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Directional Antenna Outdoor AP	JZ180A
	Aruba AP-377 (JP) 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Directional Antenna Outdoor AP	JZ181A
	370 TAA Unified Outdoor Access Points	
	Aruba AP-374 (RW) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio 6xNf Connectors Outdoor AP	JZ167A
	Aruba AP-374 (US) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio 6xNf Connectors Outdoor AP	JZ168A
	Aruba AP-374 (EG) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio 6xNf Connectors Outdoor AP	JZ164A
	Aruba AP-374 (IL) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio 6xNf Connectors Outdoor AP	JZ165A
	Aruba AP-374 (JP) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio 6xNf Connectors Outdoor AP	JZ166A
	Aruba AP-375 (RW) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Omni Antenna Outdoor AP	JZ177A
	Aruba AP-375 (US) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Omni Antenna Outdoor AP	JZ178A
	Aruba AP-375 (EG) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Omni Antenna Outdoor AP	JZ174A
	Aruba AP-375 (IL) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Omni Antenna Outdoor AP	JZ175A
	Aruba AP-375 (JP) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio Integrated Omni Antenna Outdoor AP	JZ176A
	Aruba AP-377 (RW) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio Integ Directional Antenna Outdoor AP	JZ187A
	Aruba AP-377 (US) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio Integ Directional Antenna Outdoor AP	JZ188A
	Aruba AP-377 (EG) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio Integ Directional Antenna Outdoor AP	JZ184A
	Aruba AP-377 (IL) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio Integ Directional Antenna Outdoor AP	JZ185A
	Aruba AP-377 (JP) FIPS/TAA 802.11n/ac Dual 2x2:2/4x4:4 Radio Integ Directional Antenna Outdoor AP	JZ186A

Mounting Accesories

Remarks	Description	SKU
	AP Mount Kits	
1	Aruba AP-OUT-MNT-V1A Outdoor AP Pole/Wall Long Mount Kit v2	R9H97A
1, 2	AP-270-MNT-V2 AP-270 Series Outdoor Pole/Wall Short Mount Kit	JW053A
2	AP-270-MNT-H1 AP-270 Series Outdoor AP Hanging or Tilt Install Mount Kit	JW054A
2	AP-270-MNT-H2 AP-270 Series Access Flush Wall or Ceiling Mount	JW055A
2	AP-270-MNT-H3 AP-270 Series Outdoor AP Hanging or Dual-Tilt Install Mount Kit	R6W11A

Configuration Rules

Rule #	Description	SKU
1	This Mount Kit is not valid if the unit is operated with an SFP module	
2	For 374, 375, 377 Std (Min 0 // max 1) User Selection (min 0 // max 1)	

- Notes:**
- For 374
 - o V2 bracket most often with AP-374. Leaves chassis 7.5 cm (3") from mounting asset
 - o H1 bracket most often used for hanging from inclined or horizontal structure.
 - o The AP-37x chassis does not ship with bracket.
 - For 375
 - o V1A bracket most often used for pole mount.
 - o V2 bracket most often used for wall mount.

Configuration Information

- H1 bracket most often used for hanging from inclined or horizontal structure.
- The AP-37x chassis does not ship with bracket
- For 377
 - H1 bracket most often with AP-377 for mounting to a wall. Allows chassis tilt.
 - V1A and V2 brackets can be used but will result in the AP-377 pointing down.
 - The AP-37x chassis does not ship with bracket.

Chassis Power Cord

For 374, 375, 377 Std (Min 0 // max 1) User Selection (min 0 // max 1)

PC-OD-AC-P-NA MST2HAC and AP-27x Weatherized AC Power 5m North Amer Cable

JW081A

PC-OD-AC-P-INT MST2HAC and AP-27x Weatherized AC Power 5m International Cable

JW080A

CKIT-OD-AC-P MST2HAC and AP-27x Custom AC Power Cable Connector Assembly Kit

JW079A

Notes: These are used to provide AC power to the AP-37x chassis AP-37x may be powered by AC, PoE, or both AC and PoE

Transceivers

Remarks Description

SKU

SFP

For 374, 375, 377 Std (Min 0 // max 1) User Selection (min 0 // max 1)

SFP-LX Extended Temperature 1000BASE-LX SFP 1310nm LC Connector Pluggable GbE XCVR

Q8N52A

SFP-SX Extended Temperature 1000BASE-SX SFP 850nm LC Connector Pluggable GbE XCVR

Q8N53A

Outdoor SFP Weathertight Strain Relief Kit

Q8N54A

- Notes:**
- Add Qty 1 of Q8N54A if this XCVR is selected
 - If this XCVR is selected, then the following Mount Kit is not compatible:
JW053A - AP-270-MNT-V2 270 Series Mt Kit

Power Options

PoE Power Options

For 374, 375, 377 Std (Min 0 // max 1) User Selection (min 0 // max 1)

PD-9501-5GCO-AC 60W 802.3bt Smart Rate Outdoor Surge Protection Midspan Injector

R7T40A

PD-9501-5GCO-DC 60W 802.3bt Smart Rate Outdoor Surge Protection Midspan Injector

R7T41A

* AP-POE-ATSR 1-Port Smart Rate 802.3at 30W midspan injector

R6P67A

- Notes:**
- *If this Power Injector is selected, bring in (Min 1 // Max 1) Localized power cord based on the Aruba Localization Menu
 - Indoor Injector provides no surge protection
 - Indoor injector requires indoor AC power cord
 - AP-37x may be powered by AC, PoE, or both AC and PoE
 - Power Cord for JW630A, R7T40A, R7T41A should be provided by installer
 - R7T40A and R7T41A do not include a power cord, power cord must be constructed by installer using the included power connector parts and assembled per the user guide by a certified installer

Power Injector Mounts

For 374, 375, 377 Std (Min 0 // max 1) User Selection (min 0 // max 1)

Aruba PD-MOUNT-OD Outdoor PoE Midspan Injectors Pole/Mast Mount Kit

JW620A

Notes: This is optional but recommended for outdoor injectors



Configuration Information

Antennas

5.0 GHz Antennas

For 374 Std (Min 0 // max 99) User Selection (min 0 // max 99)

*	ANT-2x2-5005 Pair 5GHz 5dBi Omni N-type Direct Mount Outdoor Antennas	JW026A
*	ANT-2x2-5010 Pair 5GHz 10dBi Omni N-Type Direct Mount Outdoor Antennas	JW027A
	ANT-4x4-5314 5.15-5.9GHz 14dBi 30x30deg Dual Pol MIMO Hi Gain Dir N-Type Outdoor Antenna	JX988A
	ANT-3x3-5712 4.9-5.9GHz 12.0dBi 75x25deg +/- 45deg and V Pol 3 MIMO High Gain Dir Antenna	JW033A
	Aruba ANT-4x4-D707 Dual-Band 7dBi Panel V/H/+/-45 4 Element MIMO Outdoor Antenna	SOA65A

- Notes:**
- *Must select Qty 0 or Qty 2
 - All antennas defined for AP-374 ship with bracket
 - ANT-2x2-5005, ANT-2x2-5010 are usually direct connect
 - Radio 0 has 4 connectors
 - Other antennas are N-type female connectorized

2.4 GHz Antennas

ANT-2x2-2005 Pair 2.4GHz 5dBi Omni N-type Direct Mount Outdoor Antennas

ANT-2x2-2314 2.4 GHz 14dBi 30x30deg Dual Pol MIMO High Gain Dir N-Type Outdoor Antenna

ANT-2x2-2714 2.4G 14dBi 70deg Sector Dual Pol MIMO N-type Outdoor Antenna

Aruba ANT-4x4-D707 Dual-Band 7dBi Panel V/H/+/-45 4 Element MIMO Outdoor Antenna

JW023A

JW024A

JW025A

SOA65A

- Notes:**
- All antennas defined for AP-374 ship with bracket
 - ANT-2x2-2005 is usually direct connect
 - ANT-4X4-D707 on 2.4Ghz radios will only use 2 connectors
 - Radio 1 has 2 connectors
 - Other antennas are N-type female connectorized

Cables

RF Cables

For 374 Std (Min 0 // max 6) User Selection (min 0 // max 6)

Remarks	Description	SKU
	AP-CBL-1 10ft(3m) Nm to Nf Outdoor Rated RF Cable	JW070A
	ANT-CBL-1 1m Nm to Nm Flexible Outdoor Rated RF Cable	JW068A
	ANT-CBL-2 2m Nm to Nm Flexible Outdoor Rated RF Cable	JW069A
	AFC7DL03-00 3m Nm to Nm Outdoor Rated RF Cable	JW064A
	AFC7DL04-00 4m Nm to Nm Outdoor Rated RF Cable	JW065A

- Notes:**
- Radio 0 has 4 connectors
 - Radio 1 has 2 connectors
 - No cables required for direct connect omnis

Accessories

Lightning Surge Arrestor

For 374 Std (Min 0 // max 6) User Selection (min 0 // max 6)

AP-LAR-1 Nm to Nf Outdoor DC to 6 GHz In-line Coaxial Lightning Arrestor

JW061A

- Notes:**
- Not required unless RF cables are longer than 2m in length
 - When used these are ordered in groups of 3 for each radio

Installation Materials

For 374 Std (Min 0 // max 99) User Selection (min 0 // max 99)

AINS2KKIT-00 2 Elec Tape Rolls Mastic Tape and White Tie Wraps Otdr Install Materials

JW063A

- Notes:** Not normally required for any connections at the chassis

Spare Items

Std (Min 0 // max 99) User Selection (min 0 // max 99)

For 374, 375, 377 Std (Min 0 // max 1) User Selection (min 0 // max 1)

1	Outdoor AP Covers and Glands 1-pk M25/5-pk M20 Cover/2-pk M16 Cover/5-pk M20 Gland/2-pk Ground Kit	Q8N47A
---	--	--------

2	Outdoor AP Metric to Standard M20 to 1/2 inch NPT 5-pk Thread Adapter	Q8N48A
---	---	--------

Configuration Rules

Configuration Information

Rule #	Description	SKU
1	This is a collection of extra covers and cabling glands, replicating what is in the shipping box	
2	This is a thread adapter normally used to allow direct interface for 1/2" NPT conduit	

Notes: Spares of items that are shipped with the AP-370 chassis.

Software

Remarks	Central Description	SKU
	Aruba Central AP Foundation 1 year Subscription E-STU	Q9Y58AAE
	Aruba Central AP Foundation 3 year Subscription E-STU	Q9Y59AAE
	Aruba Central AP Foundation 5 year Subscription E-STU	Q9Y60AAE
	Aruba Central AP Foundation 7 year Subscription E-STU	Q9Y61AAE
	Aruba Central AP Foundation 10 year Subscription E-STU	Q9Y62AAE
	Aruba Central AP Advanced 1yr Subscription E-STU	Q9Y63AAE
	Aruba Central AP Advanced 3yr Subscription E-STU	Q9Y64AAE
	Aruba Central AP Advanced 5yr Subscription E-STU	Q9Y65AAE
	Aruba Central AP Advanced 7yr Subscription E-STU	Q9Y66AAE
	Aruba Central AP Advanced 10yr Subscription E-STU	Q9Y67AAE
Notes:	Add the Central Cloud Skus to the Aruba Catalog as Standalone: Aruba > Network Management > Central > Cloud Services	
	Aruba Central On-Premises AP Foundation 1 year Subscription E-STU	R6U63AAE
	Aruba Central On-Premises AP Foundation 3 year Subscription E-STU	R6U64AAE
	Aruba Central On-Premises AP Foundation 5 year Subscription E-STU	R6U65AAE
	Aruba Central On-Premises AP Foundation 7 year Subscription E-STU	R6U66AAE
	Aruba Central On-Premises AP Foundation 10 year Subscription E-STU	R6U67AAE
Notes:	Add the Central On-Prem Skus to the Aruba Catalog as Standalone: Aruba > Network Management > Central > On-Prem Services	



Technical Specifications

RF Performance Table		
	Maximum transmit power (dBm) per transmit chain	Receiver sensitivity (dBm) per receive chain
802.11b 2.4 GHz		
1 Mbps	22	-95
2 Mbps	22	-93
5.5 Mbps	22	-90
11 Mbps	22	-88
802.11g 2.4 GHz and 802.11a 5 GHz 2.4 GHz and 802.11a 5 GHz		
6 Mbps	22	-93
54 Mbps	19	-75
802.11n HT20 2.4 GHz and 5 GHz		
MCS0/8	22	-93
MCS7/15	18	-71
802.11n HT40 2.4 GHz and 5 GHz		
MCS0/8	22	-90
MCS7/15	18	-68
802.11ac VHT20 5 GHz		
MCS0	22	-93
MCS9	16	-68
802.11ac VHT40 5 GHz		
MCS0	22	-90
MCS9	15	-63
802.11ac VHT80 5 GHz		
MCS0	22	-87
MCS9	15	-61
802.11ac VHT160 5 GHz		
MCS0	22	-86
MCS9	15	-57

Notes: Maximum capability of the hardware provided (excluding antenna gain). Maximum transmit power is limited by local regulatory settings.



Technical Specifications

WI-FI Radio Specifications

- AP type: Outdoor hardened, dual radio, 5 GHz 802.11ac 4x4 MIMO and 2.4 GHz 802.11n 2x2 MIMO
- Software-configurable dual radio supports 5 GHz (Radio 0) and 2.4 GHz (Radio 1)
- 5 GHz: Four spatial stream Multi User (MU) MIMO for up to 1,733 Mbps wireless data rate to up to three MU-MIMO capable client devices simultaneously
- 5 GHz: Four spatial stream Single User (SU) MIMO for up to 1,733 Mbps wireless data rate to individual 4x4 VHT80 or 2x2 VHT160 client devices
- 2.4 GHz: Two spatial stream Single User (SU) MIMO for up to 300 Mbps wireless data rate to individual 2x2 HT40 client devices
- Support for up to 256 associated client devices per radio, and up to 16 BSSIDs per radio
- Supported frequency bands (country-specific restrictions apply):
 - 2.400 to 2.4835 GHz
 - 5.150 to 5.250 GHz
 - 5.250 to 5.350 GHz
 - 5.470 to 5.725 GHz
 - 5.725 to 5.850 GHz
- Available channels: Dependent on configured regulatory domain.
- Dynamic frequency selection (DFS) maximizes the use of available RF spectrum.
- Supported radio technologies:
 - 802.11b: Direct-sequence spread-spectrum (DSSS)
 - 802.11a/g/n/ac: Orthogonal frequency-division multiplexing (OFDM)
- Supported modulation types:
 - 802.11b: BPSK, QPSK, CCK
 - 802.11a/g/n/ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM
- Transmit power: Configurable in increments of 0.5 dBm
- Maximum (conducted) transmit power (limited by local regulatory requirements):
 - 2.4 GHz band: +22 dBm per chain, +25dBm aggregate (2x2)
 - 5 GHz band: +22 dBm per chain, +28dBm aggregate (4x4)

Notes: conducted transmit power levels exclude antenna gain.
- Maximum EIRP (limited by local regulatory requirements):
 - 2.4 GHz band:
 - 374: 25 + Antenna Gain
 - 375: 29 dBm EIRP
 - 377: 31.4 dBm EIRP
 - 5 GHz band:
 - 374: 28 + Antenna Gain + TxBF Gain
 - 375: 35.6 dBm EIRP
 - 377: 36 dBm EIRP
- Advanced Cellular Coexistence (ACC) minimizes interference from cellular networks.
- Maximum ratio combining (MRC) for improved receiver performance.
- Cyclic delay/shift diversity (CDD/CSD) for improved downlink RF performance.
- Short guard interval for 20-MHz, 40-MHz, 80-MHz and 160-MHz channels.
- Space-time block coding (STBC) for increased range and improved reception.
- Low-density parity check (LDPC) for high-efficiency error correction and increased throughput.
- Transmit beam-forming (TxBF) for increased signal reliability and range.
- Supported data rates (Mbps):
 - 802.11b: 1, 2, 5.5, 11
 - 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54
 - 802.11n (2.4GHz): 6.5 to 300 (MCS0 to MCS15)
 - 802.11n (5GHz): 6.5 to 600 (MCS0 to MCS31)
 - 802.11ac: 6.5 to 1,733 (MCS0 to MCS9, NSS = 1 to 4 for VHT20/40/80, NSS = 1 to 2 for VHT160)
- 802.11n high-throughput (HT) support: HT 20/40

Technical Specifications

- 802.11ac very high throughput (VHT) support: VHT 20/40/80/160
 - 802.11n/ac packet aggregation: A-MPDU, A-MSDU
-

Mechanical

- AP-374 Dimensions/weight (excluding mount):
 - 23 cm (W) x 24 cm (D) x 19 cm (H) with aesthetic cover
 - 9.0" (W) x 9.4" (D) x 7.5" (H)
 - 2.7 kg/6 lbs
 - 23 cm (W) x 24 cm (D) x 14 cm (H) without aesthetic cover
 - 9.0" (W) x 9.4" (D) x 5.5" (H)
 - 2.4 kg/5.3 lbs
 - AP-375 Dimensions/weight (excluding mount):
 - 23 cm (W) x 24 cm (D) x 27 cm (H)
 - 9.0" (W) x 9.4" (D) x 10.6" (H)
 - 2.4 kg/5.3 lbs
 - AP-377 Dimensions/weight (excluding mount):
 - 23 cm (W) x 22 cm (D) x 13 cm (H)
 - 9.0" (W) x 8.7" (D) x 5.1" (H)
 - 2.1 kg/4.6 lbs
-

Environmental

- Operating:
 - Temperature: -40° C to +65° C (-40° F to +149° F)
 - Humidity: 5% to 95% non-condensing
 - Storage and transportation:
 - Temperature: -40° C to +70° C (-40° F to +158° F)
 - Operating Altitude: 3,000 m
 - Water and Dust
 - IP66/67
 - Salt Tolerance
 - Tested to ASTM B117-07A Salt Spray 200hrs
 - Wind Survival: Up to 165 Mph
 - Shock and Vibration ETSI 300-19-2-4
-

Regulatory

- FCC/ISED
 - CE Marked
 - RED Directive 2014/53/EU
 - EMC Directive 2014/30/EU
 - Low Voltage Directive 2014/35/EU
 - UL/IEC/EN 60950
 - EN 60601-1-1, EN60601-1-2
-

For more country-specific regulatory information and approvals, please see your Aruba representative.

Regulatory Model Numbers

- AP-374: APEX0374
 - AP-375: APEX0375
 - AP-377: APEX0377
-



Technical Specifications

Certifications

- CB Scheme Safety, cTUVus
 - UL2043 plenum rating
 - Wi-Fi Alliance certified 802.11a/b/g/n
 - Wi-Fi CERTIFIED™ ac (with wave 2 features)
-

Warranty

- **Limited lifetime warranty**
-

Minimum Operating System Software

- ArubaOS & Aruba InstantOS 8.3.0.0
-





Summary of Changes

Date	Version History	Action	Description of Change
21-Nov-2022	Version 10	Changed	Configuration Information section was updated.
01-Aug-2022	Version 9	Changed	Configuration Information section was updated.
06-Dec-2021	Version 8	Changed	Configuration Information section was updated.
15-Mar-2021	Version 7	Changed	SKUs added in Configuration Information section.
02-Nov-2020	Version 6	Changed	Configuration Information section was updated. New SKUs were added
08-Sep-2020	Version 5	Changed	Configuration Information section was updated. New SKUs were added
04-Nov-2019	Version 4	Changed	Overview and Configuration Information sections were updated. New SKUs were added
18-Dec-2017	Version 3	Changed	Minor changes made on Features and Benefits
04-Dec-2017	Version 2	Changed	Updates made on Environmental and Aruba 370 Series Specifications
06-Nov-2017	Version 1	New	New QuickSpecs



Copyright

Make the right purchase decision.
Contact our presales specialists.



© Copyright 2022 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

a00027234enw - 16091 - Worldwide - V10 - 21-November-2022