

PM1WU2-UK

APC Essential SurgeArrest 1 Outlet 230V, 2 Port USB Charger, UK



PM1WU2-UK has not been replaced. Please contact your customer care centre for more information.

Overview

| | |
|----------------------|---|
| Model Name | APC Essential SurgeArrest 1 Outlet 230V, 2 Port USB Charger, UK |
| Includes | User Manual |
| Standard Lead Time | Usually in Stock |
| Product Distribution | Bahrain , Botswana , Cyprus , Gambia , Ghana , Hong Kong , Iraq , Ireland , Jordan , Kenya , Kuwait , Malawi , Malta , Nigeria , Oman , Qatar , Saudi Arabia , Sierra Leone , TANZANIA, UNITED REPUBLIC OF , United Arab Emirates , Yemen , Zambia , Zimbabwe |

Output

| | |
|-------------------|----------------|
| Number of Outlets | 1 |
| Receptacle Style | UK BS1363 plug |

Input

| | |
|-----------------------|-----------------|
| Nominal Input Voltage | 230V |
| Input Frequency | 50 Hz +/- 5 Hz |
| Input Connections | British BS1363A |
| Maximum Input Current | 13 A |

Surge Protection and Filtering

| | |
|---|------------|
| Surge energy rating | 918 Joules |
| EMI/RFI Noise rejection (100 kHz to 10 MHz) | 30.0 dB |
| Peak Current Normal Mode | 12 kA |
| Peak Current Common Mode | 24.0 kA |
| NM Surge Response Time (ns) | 1.0 NS |

Physical

| | |
|-----------------|-----------|
| Net Weight | 0.16 kg |
| Maximum Height | 100.0 mm |
| Maximum Width | 63.0 mm |
| Maximum Depth | 4826.0 mm |
| Shipping Weight | 0.21 kg |

| | |
|--|-----------------------------|
| Shipping Height | 88.0 mm |
| Shipping Width | 70.0 mm |
| Shipping Depth | 106.0 mm |
| Master Carton Units | 13.0 |
| Master Carton Dimensions (Length x Width x Height) | 12.01 x 11.26 x 5.26 inches |
| Master Carton Weight | 2.83 kg |
| SCC Codes | 1073130433479 5 |
| Color | White |
| Units per Pallet | 1008.0 |

Environmental

| | |
|-----------------------------|--------------------------|
| Operating Environment | 0 - 40 °C |
| Operating Relative Humidity | 0 - 95 % |
| Operating Elevation | 0-3000 meters |
| Storage Temperature | -5 - 40 °C |
| Storage Relative Humidity | 0 - 95% non-condensing % |
| Storage Elevation | 0-4500 meters |

Conformance

| | |
|-----------------------------|--|
| Approvals | CE |
| Standard warranty | Lifetime (European Union countries only) |
| Equipment protection policy | Lifetime : 50000 Euros |

Sustainable Offer Status

| | |
|-------|--------------------------|
| RoHS | Compliant |
| REACH | REACH: Contains No SVHCs |