



Articonal International BV

Withuisveld 30


6226 NV Maastricht

Netherlands

articonal@support.eu

5 / 8 Port Nway Fast Ethernet Switch

Quick Installation Guide



FCC Warning

This device has been tested and found to comply with limits for a Class B digital device, pursuant to Part 2 and 15 of FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates and radiates radio frequency energy and, if not installed and used in accordance with the user's manual, it may cause interference in which case users will be required to correct interference at their own expenses.

CE Warning

This is a Class B product. In a domestic environment, this product may cause radio interference in which case the user may be required to take adequate measures.

Introduction

This switch provides 5 / 8 10/100M ports. It was designed for easy installation and high performance in an environment where traffic is on the network and the number of users increases continuously.


The pocket size was specifically designed for small to medium workgroups. It can be installed where space is limited; moreover, it provides smooth network migration and easy upgrade to network capacity.

Besides, this switch can be used in rooms with limited power outlet by supporting USB port powered operation.

Package Contents

Before you start to install this switch, please verify your package that contains the following items:

- One Fast Ethernet Switch
- One Power Adapter (Optional)
- One Quick Installation Guide
- One USB Cable
- 2 x Magnets
- 4 x anti-slip pad



Note: If any of these items is found missing or damaged, please contact your local supplier for replacement.

Key Features

- 5 / 8 Port 10/100M Nway (Auto-negotiation) Switch
- Pocket size with metal case
- Auto-learn of networking configurations
- Auto-detect full/half-duplex modes for any port
- Dedicated full-duplex 200Mbps bandwidth
- Store-and-Forward switching methods
- IEEE 802.3x flow control for full-duplex and back-pressure flow control for half-duplex
- Non-blocking & Non-head-of-line blocking full wire speed forwarding
- Auto-MDI/MDI-X function for any port
- Smart plug & play

Front Panel (LEDs)

LED Indicators of 5 / 8 Port 10/100M Switch

LED	Status	Operation
Power	On	Power is on.
	Off	Power is off.
LINK/ACT	On	Port is for connection
	Off	No connection.
	Flashing	Data is transmitting or receiving.

Technical Specifications

Standards	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3x Flow control
Features	Number of Ports: 5 / 8 MAC Address: 2K/1K Buffer Memory: 348Kb/512Kb Transmission Method: Store and Forward
Filtering/ Forwarding Rates	100Mbps port – 148,800pps 10Mbps – 14,880pps
Transmission Media	10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP
LED Indicators	Per Port: LINK/ACT Per Unit: Power
Power Supply	DC 5V/1.2A
Power Consumption	5 port: 5 watts (Max) 8 port: 6 Watts (Max)
Dimensions (L x W x H)	5-Port: 79 x 62 x 20mm 8-Port: 94 x 62 x 20mm
Weight	5-Port: 196 g / 8-Port: 224 g
Operating Temperature	0 to 45°C
Storage Temperature	-20 to 90°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class B, CE