

Rittal – The System.

Faster – better – everywhere.

Socket strip for IEC 320 connectors – DK 7240.200

Date : Jul 5, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Socket strip for IEC 320 connectors – DK 7240.200

created: 05.07.2021 on www.rittal.com/com-en



Product description

Description:	Socket strips in an aluminium duct.
Benefits:	Practical, universal fastening Providing flexibility and saving on warehousing. In the the 482.6 mm (19") section there is adequate space to route the infeed between the socket strip and the mounting angle without kinks
Material:	Aluminium section, natural anodised Socket inserts: Polycarbonate
Standards:	EN 60320-2-2
Supply includes:	Socket strip 2 mounting brackets Assembly parts
Note:	Depending on the application, we recommend use of a charging current reserve to prevent incorrect activation due to starting-current spikes Variable attachment distance within a range of 25 mm, the distance given is hole centre – hole centre of mounting bracket

Product description

Design:	Without switch
Dimensions:	Height: 44 mm Depth: 44 mm Length: 482.6 mm
Rated operating voltage:	250 V (AC), 50 Hz

Installation options:	Components with a 25 mm pitch pattern IT wall-mounted distributor, at the rear, horizontal (adequate width provided) Enclosure frame 482.6 mm (19") level
Mounting dimensions:	452.5 mm Tolerance: ± 25 mm
Type of electrical connection:	Wire end ferrules
Rated voltage:	230 V AC, 50 Hz
Rated current (max.):	16 A
Equipment (electrical):	Number of sockets: 12 Jack/socket (type): IEC 320 socket C13 No. of sockets and type: 12 x C13 Colour of socket: Grey Length of connection cable: 2 m
Connection cable (type):	H05VV-F3G1.5
Packs of:	1 pc(s).
Weight/pack:	0.86 kg
Copper weight (kg per piece):	0
EAN:	4028177237537
Customs tariff number:	85369095
ETIM 7.0:	EC000330
ETIM 6.0:	EC000330
eCl@ss 8.0/8.1:	27142604
eCl@ss 6.0/6.1:	27142604
Product description:	DK Socket strip, 10 A IEC 320 connector C13, 12-way, 250 V, 16 A, LHD: 482,6x44x44 mm, Without switch
Approvals	
Certificates:	EAC
Declarations:	Declaration of conformity

