## **MK120**

## Corded Keyboard and Mouse Combo





A durable duo that brings comfort, style and simplicity together. You'll be comfortable with the sleek yet sturdy keyboard thanks to the low-profile, whisper-quiet keys and standard layout. And the high-definition optical mouse puts comfort and control in your hands with smooth, accurate tracking and a comfortable, ambidextrous shape.

### PRODUCT BENEFITS

#### **KEYBOARD**

- Standard layout with full-size F-keys and number pad
- 19 mm pitch, 2.8 mm key travel
- Ultra-silent keys (<55 dB)
- Personalized comfort: 0° flat angle or 8° tilt angle
- Long life UV-coated, abrasion-resistant keys designed to last over 10 million keystrokes
- Spill-resistant up to 60 ml
- Bright LED status notification lights for Caps, Scroll and Number Lock
- 105 keys
- Sleek yet sturdy with bold, bright white characters which make the keys easier to read

#### **MOUSE**

- Optical tracking for smooth, responsive cursor control, easy text selection, and effortless scrolling
- The high-definition optical mouse puts comfort and control in your hands with smooth, accurate tracking
- Ambidextrous design for right and left-handed people

#### **KEYBOARD & MOUSE**

- 3 year warranty
- USB plug-and-play simplicity-works right out of the box, no software required

### **SPECIFICATIONS**

Compatibility  Spill Resistant  YES  Warranty 3 years  Service Life 5 million key operations per key  Key Print (Durability) Connectivity USB Profile Thin  Tit Legs YES  Tit Angles  Keyboard Layout Palm Rest NO  Battery Life Corded Hot Keys NO  Illuminated Keys Illuminated Keys Illuminated Caps Lock Integrated LCD NO  Number Pad YES  Noumber of Keys  Cable Length 1.5 m (KB) 1.8 m (M)  Mouse Tracking Optical  Mouse Scrolling Ambidextrous Design DPI 1000  Product Weight Dimensions (W x D x H) Total Weight (with packaging) Packaging Unit Packaging Unit Packaging Unit Packaging Unit Place  Not mediate Vere Simpler Vere Simple	Certification*  *Certified across multiple countries worldwide. List available upon request.	• CE		
Warranty Service Life Thin Tilt Legs Tilt Angles Service Life Service	Compatibility	Windows (XP, 7, 8, 10 and later)		
Service Life 5 million key operations per key Key Print (Durability) Tampo + UV coating Connectivity USB Profile Thin Tilt Legs YES Tilt Angles O° flat and 8° tilt Keyboard Layout Standard/Full size Palm Rest NO Battery Life Corded Hot Keys NO Illuminated Keys NO Illuminated Caps Lock YES Illuminated Num Lock YES Integrated LCD NO Number Pad YES Number of Keys 105 Cable Length 1.5 m (KB) 1.8 m (M) Mouse Tracking Optical Mouse Scrolling Ratchet Wheel Ambidextrous Design YES DPI 1000 Product Weight 550 g (KB) 90 g (M) Dimensions (W x D x H) 38.1 x 28 x 132.1 mm (M) Total Weight (with packaging) 860 g Packaging Dimensions 525 x 163 x 49 mm Storage Temperature -40°C to 60°C Operating Temperature 0°C to 40°C  Reliability Nature 100 Packaging Unit Moster package: 10 Pallet: 27 Colours Black Key Technology Plunger	Spill Resistant	YES		
Key Print (Durability) Connectivity USB Profile Thin Tilt Legs YES Tilt Angles O° flat and 8° tilt Keyboard Layout Standard/Full size Palm Rest NO Battery Life Corded Hot Keys NO Illuminated Keys Illuminated Caps Lock Illuminated Num Lock Integrated LCD NO Number Pad YES Number of Keys 105 Cable Length Mouse Scrolling Ambidextrous Design DPI Dimensions (W x D x H) Total Weight (with packaging) Packaging Dimersions Storage Temperature O°C to 40°C Operating Temperature Packaging Unit Packaging Unit Colled Packaging Unit Mouse Plack VES Number of Keys NO	•	3 years		
Connectivity USB Profile Thin Tilt Legs YES Tilt Angles 0° flat and 8° tilt Keyboard Layout Standard/Full size Palm Rest NO Battery Life Corded Hot Keys NO Illuminated Keys NO Illuminated Caps Lock YES Illuminated Num Lock YES Integrated LCD NO Number Pad YES Number of Keys 105 Cable Length 1.5 m (KB) 1.8 m (M) Mouse Tracking Optical Mouse Scrolling Ratchet Wheel Ambidextrous Design YES DPI 1000 Product Weight 550 g (KB) 90 g (M)  Dimensions (W x D x H) 450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M) Total Weight (with packaging) 860 g Packaging Dimensions 525 x 163 x 49 mm Storage Temperature -40°C to 60°C Operating Temperature 0°C to 40°C  Master Packaging Unit Layout Master package: 10 Packaging Unit Packaging Unit Packaging Plunger		5 million key operations per key		
Profile Thin  Tilt Legs YES  Tilt Angles 0° flat and 8° tilt  Keyboard Layout Standard/Full size  Palm Rest NO  Battery Life Corded  Hot Keys NO  Illuminated Keys NO  Illuminated Caps Lock YES  Illuminated Num Lock YES  Integrated LCD NO  Number Pad YES  Number of Keys 105  Cable Length 1.5 m (KB) 1.8 m (M)  Mouse Tracking Optical  Mouse Scrolling Ratchet Wheel  Ambidextrous Design YES  DPI 1000  Product Weight 550 g (KB) 90 g (M)  Dimensions (W x D x H) 450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M)  Total Weight (with packaging) 860 g  Packaging Dimensions 525 x 163 x 49 mm  Storage Temperature -40°C to 60°C  Operating Temperature 0°C to 40°C  MITF* > 150′000 hours  *Mean Time To Failure of electrical components  Thin Marker Package: 10 Packaging Unit Master package: 10 Pallet: 27  Colours Black  Key Technology Plunger		Tampo + UV coating		
Tilt Legs YES  Tilt Angles 0° flat and 8° tilt  Keyboard Layout Standard/Full size  Palm Rest NO  Battery Life Corded  Hot Keys NO  Illuminated Keys NO  Illuminated Caps Lock YES  Illuminated Num Lock YES  Integrated LCD NO  Number Pad YES  Number of Keys 105  Cable Length 1.5 m (KB) 1.8 m (M)  Mouse Tracking Optical  Mouse Scrolling Ratchet Wheel  Ambidextrous Design YES  DPI 1000  Product Weight 550 g (KB) 90 g (M)  Dimensions (W x D x H) 450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M)  Total Weight (with packaging) 860 g  Packaging Dimensions 525 x 163 x 49 mm  Storage Temperature -40°C to 60°C  Operating Temperature 0°C to 40°C  MTTF > 150'000 hours  *Mean Time To Failure of electrical components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLY, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit Master package: 10 Pallet: 27  Colours Black  Key Technology	,			
Tilt Angles  Nofe flat and 8° tilt  Keyboard Layout  Standard/Full size  Palm Rest  NO  Battery Life  Corded  Hot Keys  NO  Illuminated Keys  NO  Illuminated Caps Lock  Illuminated Num Lock  Integrated LCD  NO  Number Pad  YES  Number of Keys  105  Cable Length  1.5 m (KB) 1.8 m (M)  Mouse Tracking  Optical  Mouse Scrolling  Ratchet Wheel  Ambidextrous Design  Product Weight  Dimensions (W x D x H)  Total Weight (with packaging)  Packaging Dimensions  Storage Temperature  Operating Temperature  OPC to 40°C  Operating Temperature  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SUY, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit  Colours  Black  Key Technology  Plunger				
Keyboard Layout  Palm Rest  NO  Battery Life  Corded  Hot Keys  NO  Illuminated Keys  Illuminated Caps Lock  Illuminated Num Lock  Integrated LCD  NO  Number Pad  YES  Number of Keys  Delling  Ambidextrous Design  Product Weight  Dimensions (W x D x H)  Total Weight (with packaging)  Packaging Dimensions  Storage Temperature  Operating Temperature  NUB ARS (SK)  Reliability  NO  Standard/Full size  NO  NO  NO  NO  NO  NO  NO  NO  NO  N				
Palm Rest Battery Life Corded Hot Keys NO Illuminated Keys NO Illuminated Caps Lock Illuminated Num Lock Integrated LCD NO Number Pad YES Number of Keys 105 Cable Length 1.5 m (KB) 1.8 m (M) Mouse Tracking Optical Mouse Scrolling Ambidextrous Design DPI 1000 Product Weight 550 g (KB) 90 g (M)  Dimensions (W x D x H) Total Weight (with packaging) Storage Temperature 40°C to 60°C Operating Temperature O°C to 40°C  MITF* > 150'000 hours *Mean Time To failure of electrical components Layout Naster package: 10 Palket: 27 Colours Black Key Technology Plunger				
Battery Life Corded Hot Keys NO Illuminated Keys NO Illuminated Caps Lock YES Illuminated Num Lock YES Integrated LCD NO Number Pad YES Number of Keys 105 Cable Length 1.5 m (KB) 1.8 m (M) Mouse Tracking Optical Mouse Scrolling Ratchet Wheel Ambidextrous Design YES DPI 1000  Product Weight 550 g (KB) 90 g (M) Dimensions (W x D x H) 450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M) Total Weight (with packaging) 860 g Packaging Dimensions 525 x 163 x 49 mm Storage Temperature -40°C to 60°C Operating Temperature 0°C to 40°C  MTTF* > 150′000 hours *Mean Time To Failure of electrical components Components Layout Master package: 10 Pallet: 27 Colours Black Key Technology Plunger				
Hot Keys NO  Illuminated Keys NO  Illuminated Caps Lock YES  Illuminated Num Lock YES  Integrated LCD NO  Number Pad YES  Number of Keys 105  Cable Length 1.5 m (KB) 1.8 m (M)  Mouse Tracking Optical  Mouse Scrolling Ratchet Wheel  Ambidextrous Design YES  DPI 1000  Product Weight 550 g (KB) 90 g (M)  Dimensions (W x D x H) 450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M)  Total Weight (with packaging) 860 g  Packaging Dimensions 525 x 163 x 49 mm  Storage Temperature -40°C to 60°C  Operating Temperature 0°C to 40°C  MTTF* > 150′000 hours *Mean Time To Failure of electrical components  Layout Master package: 10 Pallet: 27  Colours Black  Key Technology Plunger				
Illuminated Keys  Illuminated Caps Lock  Illuminated Num Lock  Integrated LCD  NO  Number Pad  YES  Number of Keys  105  Cable Length  1.5 m (KB) 1.8 m (M)  Mouse Tracking  Optical  Mouse Scrolling  Ratchet Wheel  Ambidextrous Design  Product Weight  Dimensions (W x D x H)  Total Weight (with packaging)  Packaging Dimensions  Storage Temperature  Operating Temperature  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit  Colours  Black  Key Technology  Plunger	,			
Illuminated Caps Lock  Illuminated Num Lock  Integrated LCD  NO  Number Pad  YES  Number of Keys  105  Cable Length  1.5 m (KB) 1.8 m (M)  Mouse Tracking  Optical  Mouse Scrolling  Ratchet Wheel  Ambidextrous Design  YES  DPI  1000  Product Weight  550 g (KB) 90 g (M)  Dimensions (W x D x H)  450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M)  Total Weight (with packaging)  Packaging Dimensions  525 x 163 x 49 mm  Storage Temperature  -40°C to 60°C  Operating Temperature  0°C to 40°C  MITF* > 150'000 hours *Mean Time To Failure of electrical components components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit  Master package: 10 Pallet: 27  Colours  Black  Key Technology	•			
Illuminated Num Lock Integrated LCD NO Number Pad YES Number of Keys 105 Cable Length 1.5 m (KB) 1.8 m (M) Mouse Tracking Optical Mouse Scrolling Ratchet Wheel Ambidextrous Design Product Weight 550 g (KB) 90 g (M)  Dimensions (W x D x H) 450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M)  Total Weight (with packaging) Packaging Dimensions 525 x 163 x 49 mm Storage Temperature -40°C to 60°C Operating Temperature  O°C to 40°C  MITF* > 150'000 hours *Mean Time To Failure of electrical components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit Master package: 10 Pallet: 27  Colours Black Key Technology Plunger	•			
Integrated LCD NO Number Pad YES Number of Keys 105 Cable Length 1.5 m (KB) 1.8 m (M) Mouse Tracking Optical Mouse Scrolling Ratchet Wheel Ambidextrous Design YES DPI 1000 Product Weight 550 g (KB) 90 g (M)  Dimensions (W x D x H) 450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M) Total Weight (with packaging) 860 g Packaging Dimensions 525 x 163 x 49 mm Storage Temperature -40°C to 60°C Operating Temperature 0°C to 40°C  MITF* > 150'000 hours *Mean Time To Failure of electrical components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit Master package: 10 Pallet: 27 Colours Black Key Technology Plunger	•			
Number Pad  Number of Keys  105  Cable Length  1.5 m (KB) 1.8 m (M)  Mouse Tracking  Optical  Mouse Scrolling  Ratchet Wheel  Ambidextrous Design  Product Weight  Dimensions (W x D x H)  Total Weight (with packaging)  Packaging Dimensions  Storage Temperature  Operating Temperature  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit  Colours  Reliabilet: 27  Colours  Black  Key Technology  Phical  1.5 m (KB) 1.8 m (M) 1				
Number of Keys105Cable Length1.5 m (KB) 1.8 m (M)Mouse TrackingOpticalMouse ScrollingRatchet WheelAmbidextrous DesignYESDPI1000Product Weight550 g (KB) 90 g (M)Dimensions (W x D x H)450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M)Total Weight (with packaging)860 gPackaging Dimensions525 x 163 x 49 mmStorage Temperature-40°C to 60°COperating Temperature0°C to 40°CMTTF* > 150'000 hoursMTTF* > 150'000 hours*Mean Time To Failure of electrical components*Mean Time To Failure of electrical componentsLayoutNLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDICPackaging UnitMaster package: 10 Pallet: 27ColoursBlackKey TechnologyPlunger				
Cable Length  1.5 m (KB) 1.8 m (M)  Mouse Tracking Optical  Mouse Scrolling Ratchet Wheel  Ambidextrous Design Product Weight  Dimensions (W x D x H)  Total Weight (with packaging) Packaging Dimensions Storage Temperature Operating Temperature  Coperating Temperature  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLY, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit  Master package: 10 Pallet: 27  Colours  Black  Key Technology  Pathology  Ratchet Wheel  Acthory  Retall MBB, SGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLY, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Pallet: 27  Colours  Plunger				
Mouse ScrollingRatchet WheelAmbidextrous DesignYESDPI1000Product Weight550 g (KB) 90 g (M)Dimensions (W x D x H)450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M)Total Weight (with packaging)860 gPackaging Dimensions525 x 163 x 49 mmStorage Temperature-40°C to 60°COperating Temperature0°C to 40°CMTTF* > 150'000 hours *Mean Time To Failure of electrical componentsReliability*Mean Time To Failure of electrical componentsLayoutNLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDICPackaging UnitMaster package: 10 Pallet: 27ColoursBlackKey TechnologyPlunger				
Ambidextrous Design  Product Weight  Dimensions (W x D x H)  Total Weight (with packaging)  Packaging Dimensions  Storage Temperature  Operating Temperature  Colours  Packaging Unit  Master package: 10 Pallager  Packaging Unid  Packaging	Mouse Tracking	Optical		
DPI 1000  Product Weight 550 g (KB) 90 g (M)  Dimensions (W x D x H) 450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M)  Total Weight (with packaging) 860 g  Packaging Dimensions 525 x 163 x 49 mm  Storage Temperature -40°C to 60°C  Operating Temperature 0°C to 40°C  MTTF* > 150′000 hours *Mean Time To Failure of electrical components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit Master package: 10 Pallet: 27  Colours Black  Key Technology Plunger	Mouse Scrolling	Ratchet Wheel		
Product Weight  550 g (KB) 90 g (M)  Dimensions (W x D x H)  450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M)  Total Weight (with packaging)  860 g  Packaging Dimensions  525 x 163 x 49 mm  Storage Temperature  -40°C to 60°C  Operating Temperature  0°C to 40°C  MTTF* > 150'000 hours *Mean Time To Failure of electrical components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit  Master package: 10 Pallet: 27  Colours  Black  Key Technology  Plunger	Ambidextrous Design	YES		
Product Weight 90 g (M)  Dimensions (W x D x H) 450 x 155 x 23.6 mm (KB) 38.1 x 28 x 132.1 mm (M)  Total Weight (with packaging) 860 g  Packaging Dimensions 525 x 163 x 49 mm  Storage Temperature -40°C to 60°C  Operating Temperature 0°C to 40°C  MTTF* > 150'000 hours *Mean Time To Failure of electrical components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit Master package: 10 Pallet: 27  Colours Black  Key Technology Plunger	DPI	1000		
Total Weight (with packaging)  Packaging Dimensions  Storage Temperature  Operating Temperature  O"C to 40"C  MTTF* > 150'000 hours  *Mean Time To Failure of electrical components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit  Master package: 10  Pallet: 27  Colours  Black  Key Technology  *860 g  860 g  867 g  *N° Total Weight (M)  **Mean Time To Failure of electrical components  **Mea	Product Weight			
Packaging Dimensions       525 x 163 x 49 mm         Storage Temperature       -40°C to 60°C         Operating Temperature       0°C to 40°C         MTTF* > 150′000 hours         *Mean Time To Failure of electrical components         NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC         Packaging Unit       Master package: 10 Pallet: 27         Colours       Black         Key Technology       Plunger	Dimensions (W x D x H)			
Storage Temperature -40°C to 60°C  Operating Temperature 0°C to 40°C  MTTF* > 150′000 hours  *Mean Time To Failure of electrical components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit Master package: 10  Pallet: 27  Colours Black  Key Technology Plunger	Total Weight (with packaging)	860 g		
Operating Temperature  O°C to 40°C  MTTF* > 150'000 hours  *Mean Time To Failure of electrical components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit  Master package: 10  Pallet: 27  Colours  Black  Key Technology  Plunger	Packaging Dimensions			
Reliability  MTTF* > 150'000 hours  *Mean Time To Failure of electrical components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit  Master package: 10 Pallet: 27  Colours  Black  Key Technology  Plunger	Storage Temperature	-40°C to 60°C		
Reliability  *Mean Time To Failure of electrical components  NLB, BGR, CZE, ETI, FRA, DEU, ELL, HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit  Master package: 10 Pallet: 27  Colours  Black  Key Technology  Plunger	Operating Temperature	0°C to 40°C		
Layout  HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS, US INT'L, PAN-NORDIC  Packaging Unit  Master package: 10 Pallet: 27  Colours  Black  Key Technology  Plunger	Reliability	*Mean Time To Failure of electrical		
Pallet: 27  Colours Black  Key Technology Plunger	Layout	HUN, ITA, HEB, ARA, PTG, SKY, HRV-SLV, ESP, UK, CH, TUR, RUS,		
Key Technology Plunger	Packaging Unit			
	Colours	Black		
Operating Instructions Not included	Key Technology	Plunger		
	Operating Instructions	Not included		



# **MK120**



# Corded Keyboard and Mouse Combo

Product Name	Part Number	EAN Code	Keyboard Layout	Product Color
MK120	920-002534	5099206020429	Belgian	Black
MK120	920-002535	5099206020436	Bulgarian	Black
MK120	920-002536	5099206020443	Czech	Black
MK120	920-002538	5099206020467	Estonian	Black
MK120	920-002539	5099206020474	French	Black
MK120	920-002540	5099206020481	German	Black
MK120	920-002541	5099206020498	Greek	Black
MK120	920-002542	5099206020504	Hungarian	Black
MK120	920-002543	5099206020511	Italian	Black
MK120	920-002545	5099206020535	Hebrew	Black
MK120	920-002546	5099206020542	Arabic	Black
MK120	920-002547	5099206020559	Portuguese	Black
MK120	920-002548	5099206020566	Slovakian	Black
MK120	920-002549	5099206020573	Croatian-Slovene	Black
MK120	920-002550	5099206020580	Spanish	Black
MK120	920-002552	5099206020603	UK English	Black
MK120	920-002559	5099206020634	Swiss	Black
MK120	920-002560	5099206020641	Turkish	Black
MK120	920-002561	5099206020658	Russian	Black
MK120	920-002562	5099206020665	US International (NSEA packaging)	Black
MK120	920-002563	5099206020672	US International (EER packaging)	Black
MK120	920-002823	5099206023383	Pan Nordic	Black