


Key Features

Bright Images in Any Environment |
Immersive 3D Viewing | Optimized Audio
| PC-free Projection | Wireless
Presentation



Product Description

The ViewSonic PG603W projector features WXGA resolution and a brightness output of 3600 ANSI Lumens for projecting clear, detailed images in brightly lit environments. PG603W has wireless sharing capabilities and allows you to share content from laptops and other smart devices from anywhere in the room via the projector's LAN/Wi-Fi display with vPresenter Pro app. Smart device content can also be mirrored directly to the PG603W through USB connection for a simplified way to share content. The projector's integrated USB reader allows you to plug in thumb drives through the USB port to display image files such as JPG and BMP, as well as Word, PowerPoint, and Excel files without the need for a PC. In addition, the energy-saving SuperEco mode reduces power consumption and extends lamp life to a lengthy 15,000 hours for dependable long-term projection.



SPECIFICATION

Projection system:	0.65" WXGA
Native Resolution:	1280x800
DC type:	DC3
Brightness:	3600lm
Contrast Ratio with SuperEco mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light source life (Nor/SuperEco):	5000/15000
Lamp Watt:	200W
Lens:	F=2.56-2.68, f=22-24.1 mm
Projection Offset:	100% +/-5%
Throw Ratio:	1.55-1.70
Image size:	30" - 300"
Throw Distance:	1m-10.98m(100" @3.34m)
Keystone:	H: +/-20° , V: +/-30°
Optical Zoom:	1.1x
Audible Noise (Eco):	27dB
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

INPUT

Computer in (share with component):	1
Composite:	1
Audio-in (3.5mm):	1
HDMI (HDCP):	1 (Back) (HDMI 1.4/ HDCP 1.4)

OUTPUT

Monitor out:	1
Audio out (3.5mm):	1
Speaker:	10W
USB type A (Power):	2 (1 x reader 5V/0.5A & 1 x optional wifi dongle)

CONTROL

RS232:	1
RJ45:	1
USB type mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V +/- 10%, 50/60Hz AC
Power Consumption:	Normal: 270W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.3kg
Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord:	1
VGA cable:	1
Remote Control:	1 (w/ laser pointer)
QSG & CD:	QSG: 1 / CD: NA

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-109
Warranty Card:	Yes (CN Only)
Air Filter:	RSPL
Carry Bag:	PJ-CASE-008