





# Rack PDU, Basic, 1U, 16A, 208& 230V, (10) C13 & (2) C19

AP9559

			W

Lead time

#### Main

<u> </u>	
Main Input Voltage	120 V 208 V 230 V
Main Output Voltage	120 V 208 V 230 V
Input Connection Type	IEC 60320 C20
Number of rack unit	1U
Cable length	2.50 m
Number of cables	1
Provided equipment	User manual Rack mounting brackets

## **Physical**

Colour	Black
Height	4.4 cm
Width	44.7 cm
Depth	5.7 cm
Net weight	0.98 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

#### Input

Permissible voltage	90250 V
Max line current	16 A
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz

## Output

Number of power socket outlets	10 IEC 60320 C13
•	2 IEC 60220 C40

#### Conformance

Product certifications	cUL listed CE
	UL listed
	VDE
	Victoria

#### **Environmental**

Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.5 cm
Package 1 Width	48.3 cm
Package 1 Length	15.2 cm
Package 1 Weight	2.355 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## **Contractual warranty**

Warranty 2 years repair or replace	arranty	2 years repair or replace	
------------------------------------	---------	---------------------------	--