

Product datasheet

Specifications



Rack PDU, Metered, 2U, 32A, 230V, (12) C13 & (4) C19

AP7822B

Overview

Lead time

Main

Main Input Voltage	200 V 208 V 230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60309 32 A 2P + E
Number of rack unit	2U
Cable length	3.66 m
Number of cables	1
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets User manual

Physical

Height	8.8 cm
Width	44.4 cm
Depth	11.2 cm
Net weight	3.36 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	12 IEC 60320 C13 4 IEC 60320 C19
---------------------------------------	-------------------------------------

Conformance

Product certifications	C-Tick CE GOST IRAM MIC VDE VCCI
Standards	FCC part 15 class A ICES-003

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14 cm
Package 1 Width	36.8 cm
Package 1 Length	50.8 cm
Package 1 Weight	5.42 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)