

Data Sheet FUJITSU Thin Client FUTRO S540

Ultra-compact Affordable Thin Client

The FUTRO S540 is an ultra-compact affordable Thin Client device for companies that need powerful end-points with an optimal mix of industry leading OS, Thin Client device management consoles and flexible hardware options helping you provide secure computing and full productivity options for your employees.

eLux® RP 6 Thin Client OS and Scout Enterprise Management Suite® 15

Enables you to save on costs upfront and keep your IT infrastructure secure and up-to-date with continuous security patch releases

■ Unicon offers a flexible licensing model that includes the eLux OS and Scout Enterprise Management Suite with long term support for the latest updates

Enterprise-grade Security

Enables you to provide a secure end-point device that helps prevent unauthorized access to sensitive enterprise data

 Centralized administration and granular access controls coupled with built-in BIOS Security, Write Filter Protection and Kensington lock support

Full productivity

Enables your workforce to be more productive with UC&C and multiple display options and multiple connectivity options that can get work done faster and more efficiently

UC&C ready with multi-monitor support for up to two 4K displays and ideal mix of modern (Type-C) and legacy interfaces

Investment Protection

Helps you run your Thin Clients on the latest and most secure versions of the eLux RP and Scout Enterprise Management Suite

Scout Subscription helps provide perpetual updates and upgrades to eLux RP 6 and Scout Enterprise Management Suite 15

Lean IT ready

Helps you modernize your workspaces by promoting a Lean IT, clean desk and ergonomic approach without compromising on performance

■ Small footprint, Fanless design, Power-over-Ethernet (PoE) option and optimal Performance-to-Power ratio

Enables you to mount the Flexible Thin Client device using VESA interfaces behind the monitor











Technical details Components

Memory modules	4 GB (1 module(s) 4 GB) DDR4, 2,400 MHz, SO DIMM	
	8 GB (1 module(s) 8 GB) DDR4, 2,400 MHz, SO DIMM	
Graphics	DP to DVI-D (single link) Adapter Cable	
	Display Port to VGA Adapter	
Hard disk drives (internal)	SSD SATA, 64 GB, M.2 module, Flash drive (MLC technology), 124 TBW*	
nero disir dinves (internet)	SSD SATA, 32 GB, M.2 module, Flash drive (MLC technology), 62 TBW*	
	SSD SATA, 16 GB, M.2 module, Flash drive (MLC technology), 31 TBW*	
	SSD SATA, 8 GB, M.2 module, Flash drive (MLC technology), 15 TBW*	
Hard disk notes	Important Notice for M.2 Module Use: Due to MLC Technology the device only supports a defined maximum number of Terabytes written. Any and all warranty for such devices is limited to this maximum Terabytes written. Please notice the section "restricted warranty" in our warranty book. Fujitsu therefore strongly recommends to activate the write filter of the M.2 module once the configuration is finished. This activation ensures the durability of the flash module and is also mandatory to ensure a highest level of IT security (e.g. against virus attacks). In case of a need to enable further write cycles the write filter can then be deactivated again at any time. *Terabytes written (TBW) calculated based on JESD-218 SSD Client workload	
	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.	
Interface add on cards/components (optional)		
	USB 3.1 (gen1) Type-C	
	Power-over-Ethernet module, IEEE802.3at (max. 25.5W system power)	
	Internal speaker	
	Intel® Dual Band Wireless-AC 9260	
Base unit	FUTRO S540	
Operating system and software (Linux)		
Operating system	eLux® RP	
Functions	eLux® RP 6 Updates and optional software packages are available at www.myelux.com	
Manageability	Scout Enterprise, flash memory management, embedded operating system update and system monitoring, managing devices by location, group or user, individual operating system composition with ELIAS (Scout Enterprise license required)	
Operating system and software (Windows)		
Operating system	Windows® 10 IoT Enterprise (Win10IoT)	
functions	Internet Explorer Citrix Receiver VMware® Horizon Client	
Manageability	managing devices by location, group or user	
Mainboard		
Nainboard type	D3544-B	
, ·	miniSTX	
ormfactor		
	Intel® Celeron® processor J4005 (Dual Core, 2.0 GHz, up to 2.7 GHz, Intel® UHD Graphics 600) (,)	
Processor	Intel® Celeron® processor J4005 (Dual Core, 2.0 GHz, up to 2.7 GHz, Intel® UHD Graphics 600) (,) 1 SO DIMM (DDR4, 2400 MHz)	
Formfactor Processor Memory slots Supported capacity RAM (max.)		

Page 2 / 5 www.fujitsu.com/fts/FUTRO

Matahaad			
Mainboard PIOC features	DIOS Flack FDDOM undata by cafturare		
BIOS features	BIOS Flash EPROM update by software Recovery BIOS		
	Unified Extensible Firmware Interface (UEFI)		
Audio type	On board		
Audio codec	Realtek ALC671		
Interfaces			
Audio: line-out	1		
Front audio: microphone	1		
Front audio: headphone	1		
USB 2.0 total	4 rear		
USB 3.1 Gen1 (USB 3.0) total	2 front + 1x Type-C rear as option		
USB front	2		
USB rear	4 + 1 (optional)		
USB internal	1 pin header		
DisplayPort	2x DP1.2a		
Ethernet (RJ-45)	1		
Graphics brand name	Intel® UHD Graphics 600		
Graphics color depth	32 bit colors		
Shared video memory	up to 1.5 GB		
TFT resolution (DisplayPort)	up to 4,096 x 2,160 @ 60Hz		
Graphics features	DirectX® 12		
diapnics leadures	OpenGL® 4.4		
	Open CL® 1.2		
	OpenGL® ES 3.1		
<u> </u>	Vulkan™		
Graphics notes	Graphics resolution and features depending on operating system and management solution.		
Hard disk			
Hard disk notes	Important Notice for M.2 Module Use: Due to MLC Technology the device only supports a defined maximum number of Terabytes written.		
	Any and all warranty for such devices is limited to this maximum Terabytes written. Please notice the section "restricted"		
	warranty" in our warranty book.		
	Fujitsu therefore strongly recommends to activate the write filter of the M.2 module once the configuration is finished.		
	This activation ensures the durability of the flash module and is also mandatory to ensure a highest level of IT security (e.g. against virus attacks). In case of a need to enable further write cycles the write filter can then be deactivated again		
	at any time.		
	*Terabytes written (TBW) calculated based on JESD-218 SSD Client workload		
	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.		
Electrical values			
Power consumption long idle	5.01 W		
Power consumption sleep mode power	1.2 W (WoL enabled)		
Power consumption off mode power	0.2 W (WoL disabled)		
Rated voltage range	100 V - 240 V (AC Input)		
Rated frequency range	50 Hz - 60 Hz		
Operating voltage range	100 V - 240 V (AC Input)		
Operating line frequency range	50 Hz - 60 Hz		
Dimensions / Weight / Environmental			
Dimension with stand (W x D x H)	76 x 175 x 158 mm		
Dimensions (W x D x H)	36 x 165 x 147 mm		
Operating position	Vertical / horizontal		
Weight	575 g		
Weight notes	Actual weight may vary depending on configuration		
Operating ambient temperature	10 - 35 ℃		

Page 3 / 5 www.fujitsu.com/fts/FUTRO

Dimensions / Weight / Environmen	ıtal
Operating relative humidity	5 - 85 % (relative humidity)
Compliance	
Product	FUTRO S540
Model	TCS4-D3544
Germany	GS
Europe	CE EPEAT® Gold (in progress)
USA/Canada	FCC part 15B (Class B) and part 15C/E (depending on wireless configuration)
Japan	VCCI Class B
Russia	EAC
China	CCC (planned)
Australia/New Zealand	RCM
Compliance notes	Energy Star compliance may vary depending on actual configuration
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Security	
Physical Security	Kensington Lock support
System and BIOS Security	Trusted Platform Module (TPM 2.0), optional without TPM User and supervisor BIOS password
Warranty	
Warranty period	2 years (depending on country)
Warranty type	Bring-In Service (for countries within region EMEIA, for all other countries depending on local regulations)
Warranty Terms & Conditions Product Related Services - the perf	http://support.ts.fujitsu.com/warranty fect extension
Recommended Service	- 9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

		Order Code: S26361-F2391-L200
		Order Code: S26361-F2601-L522
		Order Code: S26361-F2601-L523
Wireless Keyboard Set LX901	The Wireless Keyboard LX901 is a top of the line des lifestyle orientated customers, who want only the b	



The Wireless Keyboard LX901 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption.

Page 4 / 5 www.fujitsu.com/fts/FUTRO

More information

Fujitsu products, solutions & services

In addition to FUJITSU Thin Client FUTRO S540, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Thin Client FUTRO S540, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/FUTRO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html

Copyright 2018 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2018-09-03 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright 2018 Fujitsu Technology Solutions GmbH