Overview

HP Chromebook x360 11 G3 EE



- 1. Webcam LED
- 2. Webcam
- 3. Internal Microphone
- 4. Touchpad
- 5. Microphone (Optional)
- 6. 5MP Webcam (Optional)
- 7. Webcam LED (Optional)

Left

- 8. Volume Button
- 9. Power Light
- 10. Power Button
- 11. USB 3.1 Type-A[™] Gen 1
- 12. USB 3.1 Type-C[™] Gen 1 support charging, power delivery, video, data
- 13. Nano Security Lock Slot

Overview



Right

- 4. USB 3.1 Type-A[™] Gen 1 Port
- 5. MicroSD[™] Memory Card Reader
- 6. Stereo Headphone / Microphone Combo Jack

At A Glance

Lock Key

USB 3.1 Type-C[™] Gen 1 Port

AC Adapter and Battery Light

(Support Charging, Power Delivery, Video, Data)

1.

2.

3.

- Corning® Gorilla® Glass damage-resistant cover glass
- Enjoy affordable, convenient mobile productivity with Latest Intel® Celeron® N4020 and N4120 processors
- Designed to pass MIL STD 810 G tests, 76 cm drop on concrete and 122 cm drop on plywood, and enhanced USB-C[™] connectors to stand against daily uses of plug and unplug¹
- 2 USB-C[™] ports (supports Power Delivery, DisplayPort[™], data)
- Choice of up to 8GB memory and 64GB eMMc storage
- Spill and pick resistant keyboard with HP Improved Anchored Key Design
- All-day battery life and spend less time charging with HP Fast Charge technology²
- Flexible 360°hinge, 2nd 5MP world-facing camera (Optional) and HP EMR pen (Optional) support blended-learning in laptop, tablet, tent or stand mode
- Enjoy Android[™] Apps* on Chrome OS^{™3}
- Your Chromebook boots up within 10 seconds and you can be browsing online and working in Google Apps just moments later
- Intel® 2x2 AC WLAN with MU-MIMO and HP Extended Range Wireless Lan for stable connection in dense environment
- Keyboard that can be repeatedly wiped down with common household cleaning wipes.
- Easy for small hands to grip and handle with Unique textured surface
- I. MIL-STD-810G testing is not intended to demonstrate fitness of U.S. Department of Defense (DoD) contract requirements or for

Overview

military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

- 2. Recharges up to 90% within 90 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 90% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance.
- 3. Sold separately or as an optional feature.

NOTE: See important legal disclosures for all listed specs in their respective features sections.

Options and Accessories (sold separately and availability may vary by country)

PRODUCT NAME

HP Chromebook x360 11 G3 EE

OPERATING SYSTEM

Preinstalled Chrome OS™

PROCESSOR

Intel[®] Celeron[®] N4020 with Intel[®] UHD Graphics 600 (1.1 GHz base frequency, up to 2.8 GHz boost frequency, 4 MB cache, 2 cores)^{1,2}

Intel[®] Celeron[®] N4120 with Intel[®] UHD Graphics 600 (1.1 GHz base frequency, up to 2.6 GHz boost frequency, 4 MB cache, 4 cores)^{1,2}

Intel[®] Celeron[®] N4000 with Intel[®] UHD Graphics 600 (1.1 GHz base frequency, up to 2.6 GHz boost frequency, 4 MB cache, 2 cores)^{1,2}

Intel[®] Celeron[®] N4100 with Intel[®] UHD Graphics 600 (1.1 GHz base frequency, up to 2.4 GHz boost frequency, 4 MB cache, 4 cores)^{1,2}

Processor Family

Intel® Celeron® processor (N4020, N4120, N4100, N4000)

1. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance 2. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

CHIPSET

Chipset is integrated with processor

GRAPHICS

Integrated Intel[®] UHD Graphics 600³

Supports Support HD Decode, DX12, and HDMI 1.4b

3. HD content required to view HD images.

DISPLAY

Options and Accessories (sold separately and availability may vary by country)

Touch

29.46 cm (11.6") diagonal HD IPS eDP BrightView WLED-backlit TOP+ touch screen with Corning® Gorilla® Glass 3, 220 nits, 69% NTS((1366 x 768)^{3,4,5}

29.46 cm (11.6") diagonal HD IPS eDP BrightView WLED-backlit TOP+ touch screen with Corning[®] Gorilla[®] Glass 3 and Digitizer, 220 nits, 69% NTSC (1366 x 768)^{3,4,5}

Display Size 11.6"

29.46 cm (11.6")

3. HD content required to view HD images.

4. Sold separately or as an optional feature.

5. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

STORAGE AND DRIVES

Primary Storage 32 GB eMMC 5.0⁶ 64 GB eMMC 5.0⁶

6. For storage drives, GB = 1 billion bytes. Actual formatted capacity is less. Up to 8.1 GB is not user available

MEMORY

Maximum Memory 8 GB LPDDR4-2400 SDRAM

Memory

8 GB LPDDR4-2400 SDRAM 4 GB LPDDR4-2400 SDRAM

Memory Slots Memory soldered on board Dual channel support

NETWORKING/COMMUNICATIONS

WLAN

Intel[®] Dual Band Wireless-AC 9560 802.11 ac (2x2) Wi-Fi[®] and Bluetooth[®] 5.0 Combo, non-vPro^{™7} MU-MIMO supported HP Extended Range Wireless Lan supported

Chromecast

Chromecast Support⁸

7. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited.

8. Chromecast must be purchased separately.

AUDIO/MULTIMEDIA

Options and Accessories (sold separately and availability may vary by country)

Audio HD Audio Dual Speakers Integrated Microphone

Camera

720p HD camera³ 5 MP Rear Camera (World Facing secondary camera, Fixed Focus)⁴

3. HD content required to view HD images.

4. Sold separately or as an optional feature.

KEYBOARD / POINTING DEVICES

Keyboard

Full Size Textured island-style Keyboard, spill-resistant & HP Improved Anchored Key Design

Pointing Device

Touchpad with multi-touch gesture support. Taps enabled as default

SOFTWARE AND SECURITY

Preinstalled Software

Store up to 100 GB with Google Drive (2-year subscription included)⁹ HP Classroom Manager¹⁰

Manageability Features

Chrome Enterprise Upgrade^{11, 12} Chrome Education Upgrade^{11, 12}

Security Management

Google H1 Security Chip Nano Security lock slot¹¹

9. Google Drive offer is tied to this device and is non-transferable. If this device is returned, the extra storage will be revoked. In order to redeem this offer, you will need to be on Chrome OS[™] 23 or later. Internet access is required and not included. Additional information about storage plan refunds, renewals, cancellations and expiration is available at the Google website: https://support.google.com/chromebook/answer/2703646?hl=en.

10. HP Classroom Manager is sold separately. Control and device locking from the teacher's desktop requires purchase of HP Classroom Manager.

11. Sold separately.

12. Requires one-time setup, subscription, Google Admin Console, and your organization's domain. Please see https://support.google.com/a/answer/60216.

POWER

Options and Accessories (sold separately and availability may vary by country)

Power Supply

HP Smart 45 W Type-C[™] AC power adapter

Primary Battery

HP Long Life 2-cell, 47.36 Wh Li-ion polymer¹³ HP Fast Charge Technology (90% in 90 minutes)¹⁴

Power Cord

3-wire plug - 1m

Battery life

Up to 13 hours*

13. Battery is internal and not replaceable by customer. Serviceable by warranty.

14. Recharges up to 90% within 90 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 90% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance.

* Testing conducted by HP using Google Chrome OS power_LoadTest. Battery life will vary and the maximum capacity of the battery will naturally decrease with time and usage. See http://www.chromium.org/chromium-os/testing/power-testing for test details. Fu charge battery life will decrease after Adaptive Battery Optimizer activation.

ENVIRONMENTAL

Environmental Data	Eco-Label Certifications & declarations	registration status in yo • TCO or TCO Certified Edg • China Energy Conservati	more of these marks: gement Program (FEMP) in the United States. See http ur country. e	://www.epeat.net for	
	System Configuration	The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook"?.			
	Energy Consumption (in accordance with US ENERGY STAR® test method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz	
	Normal Operation (Sort idle)	3.108 W	3.288 W	3.012 W	
	Normal Operation (Long idle)	0.888 W	1.068 W	0.912 W	
	Sleep	0.360 W	0.420 W	0.360 W	
	Off	0.336 W	0.396 W	0.336 W	
		Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk			

Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz
Normal Operation			
(Short idle)	10.63 BTU/hr	11.24 BTU/hr	10.3 BTU/hr
Normal Operation			
(Long idle)	3.04 BTU/hr	3.65 BTU/hr	3.12 BTU/hr
Sleep	1.23 BTU/hr	1.44 BTU/hr	1.23 BTU/hr
Off	1.15 BTU/hr *NOTE: Heat dissipation is calc level is attained for one hour.	1.35 BTU/hr ulated based on the measur	1.15 BTU/hr ed watts, assuming the s
Declared Noise	Sound Power		Sound Pressure
Emissions (in accordance with ISO 7779 and ISO 9296)	(L _{WAd} , bels)		(L _{pAm} , decibels)
Typically Configured - Idle	2.2		22
Fixed Disk - Random writes	2.2		22
Optical Drive -	4.8		42
Sequential reads Longevity and	This product can be upgrade	d possibly ovtonding its	enful life by covered year
Upgrading	This product can be upgraded, possibly extending its useful life by several years Upgradeable features and/or components contained in the product may include:		
	 1 ExpressCard/54 slot 1 IEEE 1394 Port 2 SODIMM memory slots Optional expansion base docking station 1 multi-bay II storage port Interchangeable HDD?? Spare parts are available throughout the warranty period and or for up to "5"? years after the end of production.		
Batteries	This battery(s) in this produc	t comply with EU Directive	2006/66/EC
	Batteries used in the product do not contain:		
	Mercury greater the1ppm by weight		
	Cadmium greater than 20ppm by weight		
	Battery description: GH02047PL		
	Battery type: Li-Ion/Li-Ion Polymer		
	Battery description: 6-cell high capacity Lithium-Ion battery (optional 8 cell available)		
	Battery type:		

Information	 This HP pr Electronic This produ California; This produ Silver level Plastics pa ISO11469 This produ according to 	ective - 2011/65/EC. oduct is designed to comply with the Waste Electri Equipment (WEEE) Directive - 2002/96/EC. ct is in compliance with California Proposition 65 (S Safe Drinking Water and Toxic Enforcement Act of ct is in compliance with the IEEE 1680 (EPEAT) sta , see http://www.epeat.net ints weighing over 25 grams used in the product are and ISO1043. ct contains 11.6% post-consumer recycled plastic to IEEE 1680.1-2018 standard, criterion 4.2.1.1. ct is 97.2% recycle-able when properly disposed of	State of 1986). andard at th marked pe (by wt.)
Packaging Materials	External:	PAPER/Corrugated	226 g
0.0	Internal:	PLASTIC/Polyethylene low density - LDPE	7 g
		PAPER/Molded Pulp	121 g
RoHS Compliance	The corrugated content.	kaging material contains at least xx% recycled con paper packaging materials contains at least xx% re fully with materials regulations. We were among the	ecycled
	 companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam. We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances-including PVC, BFRs, and certain phthalates-in future RoHS legislation that pertains to electrical and electronics products. We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve. To obtain a copy of the HP RoHS Compliance Statement, see HP RoHS position statement. 		
Material Usage	limits (refer to the http://www.hp.co gen_specification Asbestos Certain Azo Certain Bron plastics Cadmium Chlorinated Bis(2-Ethyll Benzyl buty Dibutyl phtl Disobutyl p Formaldehy Halogenate Lead carbor	o Colorants minated Flame Retardants - may not be used as flame I Hydrocarbons Paraffins hexyl) phthalate (DEHP) vl phthalate (BBP) halate (DBP) ohthalate (DIBP)	n/

	 Mercuric Oxide Batteries Nickel - finishes must not be used on the external surface designed to be
	 frequently handled or carried by the user. Ozone Depleting Substances Polybrominated Biphenyls (PBBs) Polybrominated Biphenyl Ethers (PBBEs) Polybrominated Biphenyl Oxides (PBBOs) Polychlorinated Biphenyl (PCB) Polychlorinated Terphenyls (PCT) Polyvinyl Chloride (PVC) - except for wires and cables, and certain retail packaging has been voluntarily removed from most applications. Radioactive Substances Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
Packaging Usage HP follows these guidelines to decrease the environmental impact of packaging:	
	 Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials. Eliminate the use of ozone-depleting substances (ODS) in packaging materials. Design packaging materials for ease of disassembly. Maximize the use of post-consumer recycled content materials in packaging materials. Use readily recyclable packaging materials such as paper and corrugated materials. Reduce size and weight of packages to improve transportation fuel efficiency. Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.
End-of-life Management and Recycling	Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled recovered or disposed of in a responsible manner.
	The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers . These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.
HP, Inc. Corporate	For more information about HP's commitment to the environment:
Environmental Information	Global Citizenship Report
	http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html
	Eco-label certifications
	http://www8.hp.com/us/en/hp-information/environment/ecolabels.html
	ISO 14001 certificates: http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842 and
	http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf

WEIGHTS & DIMENSIONS

Options and Accessories (sold separately and availability may vary by country)

Product Weight Starting at 3.19 lb¹⁵ Starting at 1.45 kg¹⁵

Product Dimensions (w x d x h) 11.61 x 8.08 x 0.82 in 29.5 x 20.53 x 2.09 cm

15. Weight will vary by configuration.

PORTS/SLOTS

Ports

2 USB 3.1 Type-C[™] Gen 1 (supports Power Delivery, DisplayPort[™], data) 2 USB 3.1 Gen 1 1 Stereo headphone/microphone combo jack

Expansion Slots 1 Micro SD multi-format digital media reader Supports SD, SDHC, SDXC

SERVICE AND SUPPORT

HP Services offers 1-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life batteries which will have same 1-year limited warranty as the platform. Refer to http://www.hp.com/support/batterywarranty/ for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: http://www.hp.com/go/cpc.¹⁶

16. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit http://www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

COMPATIBILITY

Options and Accessories (sold separately and availability may vary by country)

HP EMR Pen	2EB40AA
HP USB-C to RJ45 Adapter	V7W66AA
HP USB-C to VGA Adapter	N9K76AA
HP USB-C to DisplayPort Adapter	N9K78AA
HP USB-C Dock G5	5TW10AA

CERTIFICATION AND COMPLIANCE

ENERGY STAR® certified EPEAT® 2019 Silver¹⁷ Low halogen¹⁸ TCO 8.0 Certified

17. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit http://www.epeat.net f more information.
 18. External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may no be Low Halogen.

SYSTEM UNIT

Stand-Alone Power Requirements	USB-C 45 W adapter		
(AC Power)	Nominal Operating Voltage	15 V	
	Average Operating Power	<4.0 W with PLT test	
	Integrated Graphics	HD Graphics 600 12EUs HD Graphics 600 12EUs	
	Max Operating Power	< 45 W	
Temperature	Operating	41° to 95° F (5° to 35° C)	
	Non-operating	-4° to 140° F (-20° to 60° C)	
Relative Humidity	Operating	10% to 90%	
	Non-operating	5% to 95%	
Shock	Operating	40 G, 2 ms, half-sine	
	Non-operating	240 G, 2 ms, half-sine	
Random Vibration	Operating	1.043 grms	
	Non-operating	3.5 grms	
Altitude (unpressurized)	Operating	-50 to 10,000 ft (-15 to 3,048 m)	
	Non-operating	-50 to 40,000 ft (-15 to 12,192 m)	
Planned Industry Standard	UL	Yes	
Certifications	FCC Compliance	Yes	
	ENERGY STAR®	Yes ¹⁹	
	EPEAT [®] 2019	Yes, Silver in U.S. ²⁰	
	ICES	Yes	
	Australia /	Yes	
	NZ RCM Compliance	Yes	
	КС	Yes	

Yes
Yes
Yes
Yes
Yes

Configurations of the HP ChromeBook x360 11 G3 EE that are ENERGY STAR[®] qualified are identified as HP ChromeBook x360 11 G3 EE ENERGY STAR on HP websites and on http://www.energystar.gov.
 Based on US EPEAT[®] registration according to IEEE 1680 1-2018 EPEAT[®] EPEAT[®] status varies by country. Visit http://www.energy.

20. Based on US EPEAT[®] registration according to IEEE 1680.1-2018 EPEAT[®]. EPEAT[®] status varies by country. Visit http://www.epeat.n for more information.

DISPLAYS

Note: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary eith higher or lower.

nigher of tower.		
11.6 inch diagonal HD	Outline Dimensions (W \times H \times D)	284.85 X 189.84 (mm)
(1366 x 768) BrightView	Active Area	256.125 x 144.0 (mm)
WLED UWVA 50% NTSC 22	0 _{Weight}	320 g max
nits eDP 1.2 w/o PSR slim TOP+ OBZ	Diagonal Size	11.6 (inch)
	Thickness	4.2 max w PCBA
	Interface	eDP 1.2
	Surface Treatment	BrightView
	Touch Enabled	yes
	Contrast Ratio	800:1 (typical)
	Refresh Rate	60 HZ
	Brightness	220 nit typical (Panel Only)
	Pixel Resolution	1366 x 768 (HD)
	Format of LCD Pixel Arrangement	RGB
	Backlight	LED
	Color Gamut Coverage	50% of NTSC
	Color Depth	6 bit
	Viewing Angle	UWVA 85/85/85/85

STORAGE AND DRIVES*

Options and Accessories (sold separately and availability may vary by country)

32 G eMMC	Drive Weight	0.2 g
	Rotation speed	32 GB / 64 GB
	Cache Buffer	1.4 mm
	Height	11.5 x 13 mm
	Width	MMC protocol
	Transfer Rate	Up to 250 MB/s
	Seek Time	Up to 70 MB/s
	Logical Blocks	32 GB (31,268,536,320 Bytes) / 64 GB (62,537,072,640 Bytes)
	Operating Temperature	0 to 70
	Security Features	HS400
64 G eMMC	Drive Weight Rotation speed Cache Buffer NAND Type/Size Height Interface Transfer Rate Seek Time Logical Blocks	0.2 g 32 GB / 64 GB 1.4 mm 11.5 x 13 mm MMC protocol Up to 250 MB/s Up to 70 MB/s 32 GB (31,268,536,320 Bytes) / 64 GB (62,537,072,640 Bytes) 0 to 70
	Operating Temperature	HS400

For storage drives, GB = 1 billion bytes. Actual formatted capacity is less. Up to 8.1 GB is not user available

NETWORKING/COMMUNICATIONS

Intel® 9560 802.11a/b/g/n/ac (2 x 2) Wi-Fi® and Bluetooth® 5.0 Combo ¹ non-vPro	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11ac IEEE 802.11ac IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11h IEEE 802.11k IEEE 802.11r IEEE 802.11v
	Interoperability	Wi-Fi certified
	Frequency Band	 802.11b/g/n 2.402 - 2.482 GHz
		 802.11a/n/ac 4.9 - 4.95 GHz (Japan) 5.15 - 5.25 GHz 5.25 - 5.35 GHz 5.47 - 5.725 GHz

Data Rates	 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz,
	40MHz & 80MHz)
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
Security ³	 IEEE compliant 64 / 128 bit WEP encryption for a/b/g mode only AES-CCMP: 128 bit in hardware 802.1x authentication WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification IEEE 802.11i WAPI
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power ²	 802.11b: +18.5dBm minimum 802.11g: +17.5dBm minimum 802.11a: +18.5dBm minimum 802.11a: +18.5dBm minimum 802.11n HT20(2.4GHz): +15.5dBm minimum 802.11n HT40(2.4GHz): +14.5dBm minimum 802.11n HT20(5GHz): +15.5dBm minimum 802.11n HT40(5GHz): +14.5dBm minimum 802.11ac VHT80(5GHz): +11.5dBm minimum 802.11ac VHT160(5GHz): +11.5dBm minimum
Power Consumption	 Transmit mode: 2.0 W Receive mode: 1.6 W Idle mode (PSP) 180 mW (WLAN Associated) Idle mode: 50 mW (WLAN unassociated) Connected Standby/Modern Standby: 10 mW Radio disabled: 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity ³	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard with CNVi Interface
Dimensions	1. Type 2230: 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
Weight	1. Type 2230: 2.8 g 2. Type 126: 1.3 g
Operating Voltage	3.3 v +/- 5%

	Temperature	Operating: 14° to 158° F (-10° to 70° C) Non-operating: -40° to 176° F (-40° to 80° C)
	Humidity	Operating: 10% to 90% (non-condensing) Non-operating: 5% to 95% (non-condensing)
	Altitude	Operating: 0 to 10,000 ft (3,048 m) Non-operating: 0 to 50,000 ft (15,240 m)
	LED Activity	LED Amber - Radio OFF LED OFF - Radio ON
HP Integrated Module with	Bluetooth 4.0/4.1/4.2/5.0 W	ireless Technology
	Bluetooth Specification	4.0/4.1/4.2/5.0 Compliant
	Frequency Band	2402 to 2480 MHz
	Number of Available Channels	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
	Signaling Data Rate	Legacy: 3 Mbps signaling data rate ¹ 2.17 Mbps BLE: 1 Mbps signaling data rate 0.2 Mbps 1. Actual throughput may vary. Legacy: Synchronous Connection Oriented links, 3, 64 kbps, voice channels
		Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
	Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
	Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
	Bluetooth Software Supported Link Topology	Linux kernel version
	Power Management	Intel CNVi/BRI HW power management
	Certifications	FCC (47 CFR) Part 15C, Section 15.247 & 15.249
	Power Management Certifications	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
	Bluetooth Profiles Supported	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 -Link Layer Privacy LE Privacy 1.2 -Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)

Options and Accessories (sold separately and availability may vary by country)

1. Wireless access point and Internet service is required. Availability of public wireless access point is limited.

2. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

3. Check latest software/driver release for updates on supported security features.

4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/(OFDM modulation).

POWER

45 W PD AC adapter	Dimensions (H × W × D)	95 mm x 43 mm x 27.5 mm	
	Weight	200 g +/-10% Not including power cord. Power cord varies by country	
	Input	100 to 240 VAC	
		Input Efficiency	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V: 81.5% 9V: 86.7% 12V: 87.41% 15V: 87.8%
		Input frequency range	47 ~ 63Hz
		Input AC current	Max. 1.4 A at 90 Vac
	Output	Output power	5V/15W 9V/27W 12V/36W 15V/45W
		DC output	5V/9V/12V/15V
		Hold-up time	5ms at 115 Vac input
		Output current limit	<5.0A by each outputs
	Connector	USB Type-C™	
	Environmental Design	Operating temperature	32°F to 95°F (0°C to 35°C)
		Non-operating (storage)	-4°F to 185°F (-20°C to 85°C)
		temperature	
		Altitude	0 to 16,400 ft (0 to 5000m)
		Humidity	20% to 95%
		Storage Humidity	10% to 95%
	EMI and Safety Certifications	Worldwide safety standar Agency approvals - C-UL-I CISPR22 Class B, CCC, NOM	with LVD and EMC directives ds - IEC60950, EN60950, UL60950, Class1, SELV; JS, NORDICS, DENAN, EN55022 Class B, FCC Class B, 1-1 NYCE. rs at 25°C ambient condition.
HP 2-cell Long Life Li-Ion	Dimensions (H × W × L)	5.2 x 240.8 x 76.4 mm (0.204 x 9.48 x 3 inch)	
(47 Whr)	Weight	0.19 kg (0.418 lb)	
	Cells/Type	2cell Lithium-Ion Polymer	cell / 4473A9
	Voltage	7.7 V	
	Amp-hour capacity	6.15 Ah	
	Watt-hour capacity	47.3 Wh	
	Operating (Charging)	32° to 113° F (0° to 45° C)	
	Operating (Discharging)	14° to 122° F (-10° to 60° C)	
	Warranty	1-year	
	Optional Travel Battery Available	No	

Category	Description	Part Number
Cases	HP Business Slim Top Load	2SC65AA
	HP Essential Top Load Case (up to 15.6")	H2W17AA
	HP Essential Backpack (up to 15.6")	H1D24AA
	HP Reversible Neoprene Sleeve	7ZE81AA
Docking	HP USB-C Travel Dock G2	7PJ38AA
	HP E24d G4 Advanced Docking monitor	6PA50AA
	HP E27d G4 Advanced Docking monitor	6PA56AA
Input/output	HP 3-Button Laser Mouse	H4B81AA
	HP Ultra Mobile Wireless Mouse	H6F25AA
	HP USB Optical Travel mouse	G1K28AA
	HP Essential USB Mouse	2TK37AA
	HP Slim USB KB & Mouse	ТбТ8ЗАА
	HP USB-C to HDMI 2.0 Adapter	1WC36AA
	HP USB-C to DisplayPort Adapter	N9K78AA
	HP USB-C to USB 3.0 Adapter	N2Z63AAA
	HP USB-C to RJ45 Adapter	V7W66AA
	HP USB-C to VGA Adapter	N9K76AA
	HP USB-C Travel Hub G2	7PJ38AA
	Stereo 3.5mm Headset	T1A66AA
	HP EMR Pen	2EB40AA
Power	HP 45W Type -C Straight Type	1MZ01AA
	HP USB-C Notebook Power Bank	2NA10AA
Storage	HP External USB Optical Drive	F2B56AA
Security	HP Nano Keyed Cable Lock	1AJ39AA
	HP Sure Key Cable lock	6UW42AA

Summary of Changes

Date of change:	Version History:		Description of change:
January 22, 2020	V1 to V2	Added	Environmental Tab
February 6, 2020	V2 to V3	Updated	Compatibility section (HP Pen)
February 21, 2020	V3 to V4	Updated	Docking Section
March 17, 2020	V4 to V5	Updated	Accessories Section

Copyright © 2020 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel[®], Core[®], and Intel vPro[™] are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort[™] and the DisplayPort[™] logo are trademarks owned by the Video Electronics Standards Association (VESA[®]) in the United States and other countries. USB Type-C[™] and USB-C[™] are trademarks of USB Implementers Forum. SD, SDHC and SDXC are registered trademarks of SD-3C in the United States, other countries or both. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. © 2019 Google LLC All rights reserved. Google and the Google Logo are registered trademarks of Google LLC.