

# Rittal – The System.

Faster – better – everywhere.

## Blanking panel, 482.6 mm (19") Tool-free attachment – DK 7151.305

Date : Dec 15, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Blanking panel, 482.6 mm (19") Tool-free attachment – DK 7151.305

created: 15.12.2020 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Description:</b>	The blanking panel is used to seal unused areas within the 482.6 mm (19") mounting level. Quick tool-free attachment means that it is easily integrated anywhere, and can also be removed again if necessary. The consistent use of blanking panels ensures targeted air routing in partially populated racks.
<b>Material:</b>	Plastic Fire protection: Self-extinguishing , to UL 94 HB, halogen-free
<b>Colour:</b>	RAL 9005
<b>Supply includes:</b>	Blanking panel, 3 U, with integral quick-fastening

## Product features

<b>Dimensions:</b>	Width: 482.6 mm Width: 19"
<b>Build height:</b>	3 U
<b>Packs of:</b>	3 pc(s).
<b>Weight/pack:</b>	1.16 kg
<b>Copper weight (kg per piece):</b>	0
<b>EAN:</b>	4028177709263

<b>Customs tariff number:</b>	39269097
<b>ETIM 7.0:</b>	EC000456
<b>ETIM 6.0:</b>	EC000456
<b>eCl@ss 8.0/8.1:</b>	27189217
<b>eCl@ss 6.0/6.1:</b>	27181001
<b>Product description:</b>	DK Blanking panel, 482.6 mm (19"), 3 U, Toolless fixing, RAL 9005
<b>Approvals</b>	
<b>Certificates:</b>	EAC