



With paper handling up to A3 size, the Epson LX-1350 is the ideal printer to deal with lighter duties on a larger scale.

With paper handling up to A3 size, the Epson LX-1350 is the ideal printer to deal with lighter duties on a larger scale.

This wide-carriage 9-pin printer fits perfectly into a range of environments including data reporting, listings and point-of-sale. It is 337 cps fast, very reliable and cost efficient and has a range of options so you can create the perfect high quality printer to match your changing business requirements.

### Flexible working

Handle light duties in style with printing up to A3 size, 5-part forms (1 original + 4 copies) and 337 cps (12 cpi) speed.

### Get connected

Enjoy no-fuss support for a range of office equipment with auto switching between USB, parallel and serial sources.

### Optional extras

Choose from a wide range of options to match changing needs, including a 50 cut-sheet feeder, and roll paper holder.

### KEY FEATURES

- Wider format  
Fast, reliable 9-pin printing up to A3
- High productivity  
Print up to 337 characters per second (12 cpi)
- Multi-part flexibility  
Print up to 5-part forms (1 original 4 copies)
- Paper handling  
Top, bottom, front and rear paper paths
- Easy connectivity  
Auto switch between USB, parallel, serial sources

## PRODUCT SPECIFICATIONS

TECHNOLOGY	
Number of Pins	9 pins
Number of columns	136 columns
PRINT	
Printing Speed	HighSpeed-Draft: 10 cpi: 347 chars/s, 12 cpi: 357 chars/s, Draft: 10 cpi: 260 chars/s, 12 cpi: 312 chars/s, NLQ: 10 cpi: 65 chars/s, 12 cpi: 78 chars/s
Barcodes	Coda bar (NW-7), Code 128, Code 39, EAN-13, EAN-8, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, POSTNET, UPC-A, UPC-E
Carbon Copies	4 plus one original
Printing Resolution	240 x 144 dpi
CONNECTIVITY	
Interfaces	USB 2.0 Type A, Bidirectional parallel, RS-232
PAPER / MEDIA HANDLING	
Document Feed	Single sheet rear, Continuous paper rear, Paper output rear
Paper Formats	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes
Paper Thickness Continuous	0,065 mm - 0,39 mm
Paper	
Paper Thickness Multi Part	0,14 mm - 0,39 mm
Paper Thickness Single Sheet	0,065 mm - 0,14 mm
GENERAL	
Energy Use	33 W, 1,1 W (standby)
Supply Voltage	AC 220 V - 240 V
Product dimensions	546 x 275 x 164 mm (Width x Depth x Height)
Product weight	6,6 kg
Temperature	Operation 5° C - 35° C, Storage 5° C - 35° C
Compatible Operating Systems	Windows 2000, Windows 7, Windows 8, Windows 98, Windows Server 2008 R2, Windows XP
Included Software	Epson Status Monitor
Mean Time Between Failures	10.000 Hours
Print Head Life	400 Million Strokes/Wire
Sound Pressure	Operation: 53 dB (A)
Memory	128 kB included
Ribbon Yield	4000000 characters Black Draft
OTHER FEATURES	
Emulations	ESC/P, IBM PPDS
Input Data Buffer	128 kB
OTHER	
Warranty	24 months Carry in Optional warranty extension available

## LOGISTICS INFORMATION

SKU	C11CD24301
EAN code	8715946540504
Country of Origin	Indonesia
Layer	3 Units

## LX-1350

### WHAT'S IN THE BOX

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities (CD)
- Software (CD)
- Warranty document
- Power cable
- Ribbon

### SUPPLIES

- SIDM Black Ribbon Cartridge (C13S015642)

### OPTIONAL ACCESSORIES

- Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series  
C12C811141

Epson Deutschland GmbH  
Otto-Hahn-Str. 4  
D-40670 Meerbusch  
Info-Line: 02159 92 79 500  
Telefax: +49 (0) 2159/538-3000  
www.epson.de

Epson in Österreich  
Info-Line: 01 253 49 78 333  
www.epson.at  
Epson in der Schweiz  
Info-Line: 022 592 7923  
www.epson.ch

Alle Marken und eingetragenen Warenzeichen sind das Eigentum der Seiko Epson Corporation oder der jeweiligen Rechteinhaber.  
Diese Produktinformationen können ohne vorherige Ankündigung geändert werden.

**EPSON**®