INFORMATION



34’’ IPS UWQHD curved monitor with USB-C Dock, LAN, KVM and 15cm height-adjustable stand

The 34" iiyama XCB3492WQSNP ultrawide monitor combines a 3440x1440 resolution with a 3800R curved IPS panel, delivering expansive screen space, consistent colours and wide viewing angles for comfortable multitasking.

The integrated USB-C dock, KVM switch and LAN connection simplify connectivity, while DisplayPort-out enables easy multi-monitor setups through daisy chaining. A 15cm height-adjustable stand and eye-care technologies ensure lasting comfort and productivity.

FEATURES



Easy multi-device control with KVM

Easily switch between multiple computers using one monitor, keyboard, and mouse, making multitasking smooth and efficient.




Expand your workspace with a dual monitor setup

Pair your 34-inch ultrawide monitor with a 24-inch vertical monitor to create an efficient dual screen workspace. Use the ultrawide display for your main tasks while the portrait monitor keeps emails, Teams, dashboards, market data, documents or monitoring tools visible at a glance.



USB-C dock for tidy desk & easy connectivity

Connect everything with just one cable — handle video, data, and power while keeping your desk clean and organized.



Multitasking with ultra-wide QHD

Get more space to multitask, compare documents side by side, or fully immerse in your content without switching windows.

SPECIFICATION

01 DISPLAY CHARACTERISTICS

Design	curved
Diagonal	34", 86.7cm
Panel	IPS LED, matte finish
Curved	3800R
Native resolution	3440 x 1440 @100Hz (4.9 megapixel UWQHD)
Aspect ratio	21:9
Panel brightness	350 cd/m²
Static contrast	1500:1
Advanced contrast	80M:1
Response time (GTG)	3ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	1.07B 10bit (8bit + Hi-FRC) (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 160kHz
Viewable area W x H	799.8 x 334.8mm, 31.5 x 13.2"
Pixel pitch	0.233mm
Frame Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x2 (v.2.0) DisplayPort x1 (v.1.4) USB-C x1 (PD 95W)
Signal output	DisplayPort x1 (Daisy Chain MST max. 3440x1440)
USB HUB	x4 (2x Type A v.3.2 Gen 1 (5Gbps, 4.5W) 2x Type C (5Gbps, 7.5W))
USB-C DOCK	x1 (Power delivery 95W, LAN, DP out, USB v.3.2 (Gen 1, 5Gbit))
HDCP	yes
Headphone connector	yes
RJ45 (LAN)	x1

03 FEATURES

KVM switch	yes
Flicker free	yes
Adaptive Sync support	yes
Extra	Eye Comfort
HDR	ready, HDR10
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL, UA
Control buttons	Navigation Button, Power, (Center: MainMenu/Execution), Front (Move Down/Submenu), Rear (Move Up/Input Select), Left (Move Left/Volume Down), Right (Move Right/Volume Up)

User controls	picture adjust (brightness, contrast, Eco, HDR, ACR, Adpative Sync, X-res technology, black tuner), colour settings (6-axis, i-Style colour, gamma, RGB range, colour temp., user preset), PiP/PbP (PiP/PbP mode, sub source, PiP position, PiP size, swap, audio input), OSD (H. position, V. position, time, background, display information, MAC address), language, miscellaneous (sharpness, video mode adjust, opening logo, power LED, USB-C speed, USB charge, KVM, DDC/CI control, MST DP-out), input select, audio settings (volume, mute audio), recall
Speakers	2 x 5W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	height, swivel, tilt
Height adjustment	150mm
Swivel stand	90°; 45° left; 45° right
Tilt angle	23° up; 5° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power (1.8m), USB (1.8m), HDMI (1.5m), DP (1.8m), USB-C (1.0m)
Other	quick start guide, safety guide

06 POWER MANAGEMENT


Power supply unit	internal
Power supply	AC 100 - 240V, 50/60Hz
Power usage	31W default, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations	CE, TÜV-GS, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA, TCO Edge
Energy efficiency class (Regulation (EU) 2017/1369)	F
EPEAT Silver	*registration varies by country, go to www.epeat.net for details
REACH SVHC	above 0.1%: Lead, Lead monoxide, Diboron trioxide

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D	816.5 x 434 (584) x 245.5mm
Box dimensions W x H x D	910 x 480 x 160mm
Weight (without box)	9.8kg
Weight (with box)	14.4kg
EAN code	4948570127887


4xM4 SCREW HOLE
(VESA MOUNT)
100.0
100.0
50.0
399.5
249.5
519.5
175.5
384.0
78.5
409.0
434.0 (384.0)
79.5
239.5
110.0
143.0

GALLERY

























All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. **© IIYAMA CORPORATION. ALL RIGHTS RESERVED**