

DATASHEET

Extension Cable C20 180° - C19 180°, Black, 5.0 m, 3 x 1.50 mm²



General data

Plug IEC60320/C20 to jack IEC60320/C19
16 A / 250 V VDE tested

Allgemeine Daten

Number of cores	3
Colour outer sheath	black
Spiralized cable	False
With cord switch	False
Material outer sheath	Polyvinyl chloride (PVC)

Mechanische Eigenschaften

Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female

Kabelmantel

Temperature resistance	0 - 70 °C
------------------------	-----------

Elektrische Eigenschaften

Protective conductor	True
Nominal voltage	250 V

Normen, Zulassungen, Zertifizierungen

This datasheet was created automatically on 10-07-2023 . Technical changes reserved.



DATASHEET

Extension Cable C20 180° - C19 180°, Black, 5.0 m, 3 x 1.50 mm²

Oil resistant (acc. EN 60811-2-1) | False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length Leiternennquerschnitt Außendurchmesser ca.		
EK519.1	Extension Cable C20 180° - C19 180°, Black, 1.0 m, 3 x 1.50 mm ²	black	1.0 m	1,50 mm ²	8,6 mm
EK519.1,8	Extension Cable C20 180° - C19 180°, Black, 1.8 m, 3 x 1.50 mm ²	black	1.8 m	1,50 mm ²	8,6 mm
EK519.2,5	Extension Cable C20 180° - C19 180°, Black, 2.5 m, 3 x 1.50 mm ²	black	2.5 m	1,50 mm ²	8,6 mm
EK519.5	Extension Cable C20 180° - C19 180°, Black, 5.0 m, 3 x 1.50 mm ²	black	5.0 m	1,50 mm ²	8,6 mm

This datasheet was created automatically on 10-07-2023 . Technical changes reserved.

