

IFP INTERACTIVE DISPLAYS



INFORMATION

75" OS-Free Professional Touch Display for Maximum Security and Full IT Control

The ProLite TN7505A-B1AG is a large-format professional touch display, without an operating system, designed for environments where security, reliability and control are non-negotiable. Despite its minimalist structure, the TN6505A is exceptionally easy to use: simply connect your source and it works. The responsive multi-touch panel, 4K UHD resolution and high brightness deliver a precise and professional experience for collaboration, presentations and interactive applications. Built-in annotation allows users to write directly on the screen with a pen, marking up presentations or any on-screen content in real time for clear and effective communication. The TN8605A is the ideal choice for banks, courts, defence organisations, IT departments, universities and other high-security or compliance-driven environments where simplicity, transparency and trust are essential.



Aesthetics which Elevate Any Environment

Modern, minimal, and made to elevate any environment—this design blends seamlessly into classrooms and boardrooms alike. It's not just a display; it's a statement. Clean lines, premium finish, and a presence that enhances focus and professionalism without stealing the spotlight.




DeepContrast-IR+

The state-of-the-art DeepContrast-IR+ technology ensures accurate and precise touch responses, enabling effortless interaction and annotation.



Standalone Solution & Connectivity

The OPS PC Slot offers a convenient standalone solution, allowing easy integration without the need for additional devices. The USB-C connection provides seamless connectivity, enabling quick data transfer, video output, and power through a single cable for enhanced versatility and ease of use.



Wall Mount

The included wall mount bracket ensures secure and stable installation of your display. Designed for easy setup, it supports VESA compatibility and offers a sleek, space-saving solution. Its durable construction guarantees reliability, making it ideal for classrooms, offices, and meeting rooms.

01 **DISPLAY CHARACTERISTICS**

| | |
|----------------------------|---|
| Diagonal | 74.52", 189.273cm |
| Panel | IPS, AG coating & Anti-Bacteria coating, haze 25% |
| Touch Glass | Anti-Glare glass with Anti-Gloss treatment, Anti-Bacterial coating, Ultra Smooth writing, Optical Bonding |
| Panel | IPS |
| Native resolution | 3840 x 2160 (8.3 megapixel 4K UHD) |
| Aspect ratio | 16:9 |
| Panel brightness | 500 cd/m ² |
| Brightness | 450 cd/m ² (max.) |
| Static contrast | 1200:1 |
| Response time (GTG) | 5ms |
| Viewing zone | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Horizontal Sync | 30 - 135kHz |
| Viewable area W x H | 1650.0 x 928.0mm, 65.0 x 36.5" |

02 **TOUCH**

| | |
|------------------------------------|---|
| Touch technology | DeepContrast-IR+ |
| Touch accuracy | +- 1mm |
| Touch interface | USB |
| Supported operating systems | All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section. |
| Palm rejection | yes |

03 **INTERFACES / CONNECTORS / CONTROLS**

| | |
|-------------------------------|---|
| Analog signal input | VGA x1 (FHD) |
| Digital signal input | HDMI x2 (CEC/ARC) DisplayPort x1 USB-C x1 (Power Delivery 65W, DP-Alt, Data, Touch) |
| Audio input | Mini jack x3.5 mm |
| Monitor control input | RS-232c x1 RJ45 (LAN) x2 |
| Audio output | Mini jack x1 Speakers 2 x 20W (Subwoofer 1x 20W) |
| Monitor control output | OPS Slot x1 (Intel OPS80 standard) |
| USB ports | x1 2.0 (2x 3.2 (USB-B up for touch HDMI1/DP/VGA)) |
| RS-232c | x1 |
| RJ45 (LAN) | x2 ((in/out)) |

04 **FEATURES**

Integrated software No operating System

PiP yes

PbP yes

05 GENERAL

OSD languages EN, DE, FR, ES, IT, RU, JP, NL

User controls Color temp., image mode (including eye protection mode), sound mode, no signal standby (Off / 1 min. / 3 min. / 5 min. / 15 min. / 30 min.), meeting mode, time scheduler, key lock, PIP & PBP, brightness / contrast.

06 MECHANICAL

Fanless design yes

VESA mounting 800 x 400mm

Operation temperature range 0°C - 40°C

Storage temperature range - 20°C - 60°C

07 ACCESSORIES INCLUDED

Cables RS-232c

Other 4x Stylus, Webcam bracket, Wall mount, HDMI 3m, USB 3m, Power

Remote control yes (batteries included)

08 POWER MANAGEMENT

Power supply unit internal

Power usage 175W typical, 0.5W stand by, 0.3W off mode

09 SUSTAINABILITY

Regulations CB, CE, TÜV-Bauart, EAC, RoHS support, ErP, WEEE, REACH, UKCA

Energy efficiency class (Regulation (EU) 2017/1369) G

10 DIMENSIONS / WEIGHT

Product dimensions 1710.2 x 1036.3 x 120.4mm
W x H x D

Weight (without box) 54.5kg

EAN code 4948570127078



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © IIYAMA CORPORATION. ALL RIGHTS RESERVED