

160W 6 Port USB Charging Station

Part No.: 73436



Description

- Simultaneous charging of up to 6 tablets, smartphones and/or a laptop or Macbook with up to 140W or other USB Type A and Type C devices
- Max. 5V 2.4A charging per USB Type A port, max. 30W or 140W charging per USB Type C port
- Supports USB Power Delivery: 2x PD 3.0 up to 30W each and 1x PD 3.1 up to 140W
- Battery Charging Standard 1.2 supports fast charging, Apple Charging Protocol, QC 3.0/4.0 and Samsung AFC supported
- 2 year warranty

The Lindy 160W 6 Port USB Charging Station allows charging up to 3 USB Type A and 3 Type C devices like tablets, smartphones or a laptop or Macbook. Each USB Type A port can provide up to 5V 2.4A, two USB Type C ports can provide up to 30W each and one even up to 140W to satisfy the most power hungry devices. If all 6 ports are occupied and/or when total power draw is higher than 160W, load balancing will occur.

With its smart charging function and support of many different protocols like QC 3.0 and 4.0 (only Type C ports), Samsung AFC and Apple 5V 2.4A Charging Protocol and BC 1.2 (only Type A ports), this USB Charging Station can recognise the connected device to automatically adjust the charging current for a fast and safe charge.

USB Power Delivery Revision 3.1 enables higher power to applications up to 140W, including larger notebooks, gaming PCs, Macbooks, workstations or Docking Stations. Another 2 Type C PD 3.0 ports with up to 30W each allow fast, flexible and safe charge of smartphones and tablets.

This USB Charging Station also provides overcurrent, overvoltage and short-circuit protection to avoid excessive current damaging the device.

Plastic dividers can be assembled and stood on the top of the unit, which allows different widths for different tablets or mobile phone sizes. This product is perfect for use in schools, libraries, hotels, restaurants or any location that uses multiple devices. Country specific power cables are provided for seamless use of the charging station, ideal for global events or integration into installations abroad.

Technical details

Specifications

- Interface: USB
- Compatibility: 3x USB Type A ports and 3x USB Type C for USB Type A and C devices
- Power Requirements: 20V 8A
- Output Power: 140.8W
- Power Delivery: 2 Type C PD ports up to 30W each, 1 Type C PD port up to 140W
- Special Features: BC 1.2; Smart Charging; QC 3.0/4.0; Samsung AFC; Apple 5V 2.4A Charging Protocol; PD 3.0/PD2.0/PPS Charging Protocol, PD3.1/PD2.0/PPS/EPR 28V Protocol; Overcurrent, overvoltage and short-circuit protection, LED indicators

Connectors

- Input: 3x USB Type A (Female), 3x USB Type C (Female)

Physical properties

- Dimensions (approx.) WxDxH: 185x113x35mm (7.28x4.45x1.38in)
- Connector Material: -
- Housing Material: Plastic, Aluminium alloy
- Net Weight: 0.93kg (2.05lb)
- Operating Temperature: 5°C - 35°C (41°F - 95°F)
- Storage Temperature: -20°C - 50°C (-4°F - 122°F)
- Humidity: 20% - 80% RH (non-Condensing)
- Colour: Black, grey

Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 269x156x95mm (10.59x6.14x3.74in)
- Gross Weight: 1.64kg (3.62lb)
- Warranty (Years): 2
- Certificated: CE, FCC, LVD, RoHS, REACH, California Proposition 65

Package Contents

- USB Charging Station
- 10 plastic separators

- 20V 8A PSU with 5.5/2.5mm DC cable, 0.9m (2.95ft)
- 4 country specific power cables (Schuko/US/UK/AUS to IEC C5), 0.9m (2.95ft)
- LINDY Manual

Purchasing information

- No.: 73436
- EAN: 4002888734363

© LINDY 2023