



USB Type C to Triple Display Converter

Part No.: 43297

Description

- Converts a USB Type C port to an HDMI, DVI or VGA port
- Requires DisplayPort Alternate Support by the USB Port/Bus
- Supports resolutions up to 3840x2160@30Hz RGB (HDMI) / 1920x1200@60Hz (DVI) / 1920x1080@60Hz (VGA)
- Plug and Play, no drivers required
- 2 year warranty

The Lindy USB Type C to Triple Display Converter allows users to connect either an HDMI, DVI or VGA screen to a Macbook, ultrabook or notebook with USB DisplayPort Alternate Mode. With its lightweight, low profile design, the adapter easily fits into a notebook bag and simply expands any available connectivity options, so users can connect to the most commonly used digital and analogue video equipment, without having to carry multiple adapters - ideal for BYOD applications.

The converter is powered by the USB Bus, therefore no external power supply is needed. Installation is simple as no drivers are required and Type-C's reversible design has been developed to work regardless of which way the cable is inserted into the port.

Technical details

Specifications

- AV Interface: USB Type C to HDMI & DVI & VGA
- Interface Standard: HDMI 1.4, DVI, VGA
- Supported Bandwidth: 10.2Gbps
- Maximum Input Resolution: 3840x2160@30Hz RGB (HDMI) / 1920x1080@60Hz (VGA) / 1920x1200@60Hz (DVI)
- Maximum Output Resolution: 3840x2160@30Hz RGB (HDMI) / 1920x1080@60Hz (VGA) /

- 1920x1200@60Hz (DVI)
- Chipset: VL100, IT6562FN, PS8222B
- Compatibility: USB Type C or Thunderbolt 3 equipped computers with DisplayPort Alternate Mode support
- Power Delivery: -
- HDCP Support: -
- Supported Audio: -
- Separate Audio Ports: -
- Special Features: DisplayPort Alternate Mode

Connectors

- Inputs: 1 x USB Type C (Male)
- Outputs: 1 x HDMI (Female), 1 x DVI (Female), 1 x VGA (Female)
- Power: Bus-powered

Physical Properties

- Dimensions (approx.) WxDxH: 45x14.2x85mm (1.77x0.56x3.35in)
- (Fixed) Cable Length: 120mm (4.72in)
- Housing Material: Aluminium Shell
- Net Weight: 0.068kg (0.15lb)
- Operating Temperature: 0°C - 45°C (32°F - 113°F)
- Storage Temperature: -10°C - 70°C (14°F - 158°F)
- Humidity: 10 - 85% RH (non-condensing)
- Power Requirements: -
- Colour: Grey

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 174x194mm (6.85x7.64in)
- Gross Weight: 0.08kg (0.18lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS & REACH, California Proposition 65

Package Contents

- USB Type C to Triple Display Converter
- Lindy Manual

Purchasing information

- No.: 43297
- EAN: 4002888432979

© LINDY 2021