EFB-Elektronik GmbH
Striegauer Str. 1
33719 Bielefeld
Fon: +49 (0) 521 - 40 41 8 - 0
Fax: +49 (0) 521 - 40 41 8 - 50





U-DQ(ZN) BH SC/SC 50/125µ OM2

- Characteristics and advantages of Trunk cables:
- 2 up to 48 fibers per cable (other Trunks available on request)
- Pre-assembled, polished and factory-tested
- Both-sided assembled with stepped plug whips
- Ready to use, no need for expensive splice- and measuring equipment
- With Premium or Standard cable divider at customers choice
- Attenuation protocol for each assembled connector included in delivery
- All possible combinations of connectors like LC, E2000, SC and ST available
- Identification with cable markers
- Delivery depending on length and type: one way drum or cable ring

Category:	OM2
Colour outer sheath:	black
Crossed:	No
With rodent protection:	yes
Flame retardant:	According to EN 50265-2-1
Halogen free (according to EN 50267-2-3):	yes
Cable type connector connection 2:	Universal cable

Article no.	Title	Number of fibres	Connector connection 1	Number of connectors connection 1	Connector connection 2	Number of connectors connection 2	Length m
O8301.1	U-DQ(ZN) BH SC/SC 4G	4	SC	4	SC	4	1.0

	50/125µ 1m, 8xSC						
O8321.1	U-DQ(ZN) BH SC/SC 8G 50/125µ 1m, 16xSC	8-28	SC	8-28	SC	8-28	1.0
O8341.1	U-DQ(ZN) BH SC/SC 12G 50/125µ 1m, 24xSC	6	SC	6	SC	6	1.0
O8382.1	U-DQ(ZN) BH SC/SC 24G 50/125µ 1m, 48xSC	24	SC	24	SC	24	1.0

accessory


Cable Gland, Standard


Drawing-In Tube, Standard


Cable Divider, Drawing-In and Plug Protection Tube

print