

Technical Specifications

HP Series 5 Pro 23.8 inch FHD USB-C Monitor - 524pu




1. Power Button

Front
2. Power LED

Technical Specifications

HP Series 5 Pro 23.8 inch FHD USB-C Monitor - 524pu



Back

- | | | | |
|----|--|-----|--|
| 1. | Joypad OSD button | 7. | DisplayPort™ 1.4-out |
| 2. | Security Cable Slot | 8. | RJ-45 (10/100/1000 Mbps) (Network Port) |
| 3. | Power Connector | 9. | SuperSpeed USB Type-A 5Gbps signaling rate |
| 4. | HDMI 2.0 Port | 10. | SuperSpeed USB Type-C® 5Gbps signaling rate (Up to 15W USB Power Delivery) |
| 5. | DisplayPort™ 1.4 | 11. | SuperSpeed USB Type-A 5Gbps signaling rate |
| 6. | SuperSpeed USB Type-C® 5Gbps signaling rate (up to 100W USB Power Delivery, Alt Mode DisplayPort™ 1.4) | 12. | SuperSpeed USB Type-A 5Gbps signaling rate (charging) |

Technical Specifications


Model: 9D9V7AA

Panel Specifications	Display Size (Diagonal)	23.8" (60.5 cm)
	Viewable Diagonal Size	23.8" (60.47 cm)
	Panel Technology	IPS
	Curvature	Flat
	Max Refresh Rate	100 Hz
	Native Resolution	FHD (1920 x 1080)
	Panel Bit Depth	8 bit (6 bit + FRC)
	Aspect Ratio	16:9
	Brightness (Typical)	350 nits
	Display Contrast Ratio (Static)	1500:1
	Display Contrast Ratio (Dynamic)	10000000:1 = 10M:1
	Flicker Free	Yes
	Pixel Pitch	0.2745 x 0.2745 mm
	Pixels Per Inch (PPI)	93 PPI
	Display Colors	Up to 16.7 million colors supported *Number of colors through A-FRC technology.
	Backlight Lamp Life Minimum (To Half Brightness - In Hours)	30,000 hours
	Backlight Type	Edge-lit, WLED
	Screen Treatment	Anti-glare
	Hardness	3H
	Haze	25%
Color	Response Time (Typical)	5ms GtG (with overdrive)
	Horizontal Viewing Angle (Typical Cr>10)	178°
	Vertical Viewing Angle (Typical Cr>10)	178°
Color Management	Panel Active Area Metric (W X H)	52.70 x 29.65 cm
	Panel Active Area Imperial (W X H)	20.75x11.67 in
	NOTE: Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.	
Monitor Specifications	Color	sRGB 100%
	Color Space	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2
	RGB Channel Adjust	Yes, Gain
Monitor Specifications	Default Color Temperature	Standard (6500K)
	Bezel Type	3-sided borderless
	Color Of Stand	Natural Silver and Jet Black
	Color Of Head	Jet Black
	Tilt	-5 to +23°
	Swivel	±45°
	Pivot	±90
	Height Adjust Range	150 mm
Monitor Specifications	Vesa Mounting	100mm x 100mm
	Security Lock	Security lock-ready

Technical Specifications

	Detachable Stand	Yes
	Warranty	3/3/0 for LA, NA, EMEA, APJ; (3/3/3 in select APJ Countries)
	Low Blue Light	Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified)
	Zero Bright Dot Guarantee	No
	Management Software	HP Client Management Script Library*, HP Display Center** <i>* The Client Management Script Library must be downloaded to the connected PC to run CMSL commands. Some limitations may apply to legacy displays. Visit support.hp.com to download HP CMSL.</i> <i>**Host PC requires Windows 10 or higher. HP Display Center is available for download on the Microsoft store for Windows or support.hp.com for Windows and MacOS.</i>
On Screen Display (OSD)	On Screen Display	Brightness+, Color, Input, Image, Power, Menu, Management, Information, Exit
	Native Resolution	FHD (1920 x 1080)
	Maximum Resolution	FHD (1920 x 1080 @ 100 Hz)
	Preset Graphic Modes/Supported Resolutions	720x400@70Hz
		640x480@60hz
		640x480@75hz
		800x600@60hz
		800x600@75hz
		1024x768@60Hz
		1024x768@75Hz
		1280x720@60Hz
		1280x800@60Hz
		1280x1024@60Hz
		1280x1024@75hz
		1440x900@60Hz
		1600x900@60Hz
		1680x1050@60Hz
		1920x1080@60Hz
		1920x1080@75Hz
		1920x1080@100Hz
	Minimum Vertical Scan Rate	50 Hz
	Maximum Vertical Scan Rate	100 Hz
	Minimum Horizontal Scan Rate	30 kHz
	Maximum Horizontal Scan Rate	115 kHz
	Maximum Pixel Clock	300 MHz
	User Programmable Modes	Yes, 17
	User-Assignable Function Buttons	Yes, 4 (6 options)
	Languages	English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese, S-Chinese and Russian
Connector Types	DisplayPort™	1 DisplayPort™ 1.4
	DisplayPort™ Out	1 DisplayPort™ 1.4-out
	HDMI	1 HDMI 2.0

Technical Specifications

	HDCP	Yes, DisplayPort™, HDMI and USB Type-C®
	USB Type-C® Video Input & Data Transfer	1 SuperSpeed USB Type-C® 5Gbps signaling rate (up to 100W USB Power Delivery, Alt Mode DisplayPort™ 1.4)
	USB Type-C® Data Transfer Only	1 SuperSpeed USB Type-C® 5Gbps signaling rate (Up to 15W USB Power Delivery)
	USB- A	3 SuperSpeed USB Type-A 5Gbps signaling rate (1 charging)
	Ethernet	1 RJ-45 (10/100/1000 Mbps)
Special Features	Switch	Monitor Power button Next Active Input / Up button Information / Down button Brightness / Left button Color / Right button Menu / Enter button Through HP Client Management Script Library, In-Band MAC Address Pass Through (MAPT), Out-of-Band MAC Address Pass Through (MAPT), In-Band Wake on LAN (WOL), Out-of-Band Wake on LAN (WOL), PXE Boot
	Remote Manageability	17
	User Presets	Yes
	User Updateable Firmware	Single Power On, Daisy Chain
	Other Special Features	
Power & Operating Specs	Power Supply	Internal
	Power Source	100 – 240 VAC 50/60 Hz
	Power Consumption- Max	198 W
	Energy Saving/Stand By Mode	0.5 W
	Power Consumption - Typical	22 W
Energy Star Data	Operational Mode at 100 VAC	14.5 W
	Operational Mode at 115 VAC	14.5 W
	Operational Mode at 230 VAC	14.5 W
EU Energy Efficiency Class (ErP LOT-5)	On-mode Power Consumption for Standard Dynamic Range (SDR)	14.7 W
	ErP LOT5 Energy Efficiency Class for Standard Dynamic Range (SDR)	
Operating Conditions	Operating Temperature - Celsius	5~35°C
	Operating Temperature - Fahrenheit	41– 95°F
	Non-Operating Temperature - Celsius	–40 – 65°C
	Non-Operating Temperature - Fahrenheit	–40 – 149°F
	Operating Humidity	20 – 80% Relative Humidity (non-condensing)
	Non-Operating Humidity	5~95%RH
	Operating Altitude Metric	0~5,000m
	Non-operating Altitude Metric	0~12,192m
	Operating Altitude Imperial	0~16,400ft
	Non-operating Altitude Imperial	0~40,000ft

Technical Specifications

Certifications and Complies	Low Halogen	Yes*
		* External power supplies, WWAN modules, power cords, cables and peripherals excluded. Service parts obtained after purchase may not be Low Halogen.
	Agency Approvals and Certifications	WW application CB/KC/NOM/TUV-S/ISO 9241-307/EAC/cTUVus/PSB/ISC/CCC/CECP/SEPA/TCO/TCO Certified Edge/BSMI/GS/TUV HW Low Blue Light/TUV Flicker Free/UAE/Ukraine/BIS/NRCS/CE/FCC/VCCI/BSMI/EMF/KCC/ICES/RCM/PSE/Australian-New Zealand DoC/Energy Star/Vietnam MEPS/Australian-New Zealand MEPS/Korea MEPS/Ukraine EE/CEL/California CEC/WEEE Windows 11 (x64 only), Windows 10 (x64 only) Yes EPEAT® Gold in United States*
	Microsoft WHQL Certification ENERGY STAR® Certified EPEAT® Registered Regions need to verify by country	*EPEAT® Gold NOTE: Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit www.epeat.net for more information.
	China Energy Label TCO Certified Edge TCO Certified SmartWay Transport Partnership - NA only	CEL Grade 1 Yes Yes Yes (NA sku)
Contains Recycled Materials	Recycled Plastics	85% ITE-derived closed loop plastic* Contains Ocean-Bound Plastic** *Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard ** All plastic parts contain ocean-bound plastic. Percentage of ocean-bound plastic contained in each component varies by product.
	Recycled Metal	At least 40% recycled metal including 90% recycled aluminum in the stand* * Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.
	Recycled Glass	Contains 20% recycled glass in the monitor panel* * Percentage of recycled glass in the monitor panel varies by product. Recycled glass is expressed as a percentage of the total weight of the glass.

Technical Specifications

	Recyclable Packaging (Box, packing materials)	Outside Box and corrugated cushions are 100% sustainably sourced and recyclable* Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable**	
		<i>*100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.</i>	
		<i>**Molded pulp cushions contains 100% recycled wood fiber and organic materials.</i>	
Unit Product/Package Specifications	Product Dimensions (Unpacked with stand) (W x D x H)	Metric 53.94 x 18.95 x 50.32 cm	Imperial 21.24 x 7.46 x 19.81 in
	Product Dimensions (Packed) (W x D x H)	62.1 x 14.0 x 39.3 cm	24.45 x 5.51 x 15.47 in
	Display Head Dimensions (Unpacked without stand) (W x D x H)	53.94 x 4.72 x 31.43 cm	21.24 x 1.86 x 12.37 in
	Base Area Footprint (w x d mm)	242 x 189.50 mm	9.53 x 7.46 in
	Bezel Measurements	Top: NA Sides: NA Bottom: 9.25 mm	Top: NA Sides: NA Bottom: 0.37 in
	Product Weight (Unpacked with stand)	5.93 kg	13.07 lb
	Product Weight (Packed)	8.42 kg	18.57 lb
	Product Weight (Head Only)	4.33 kg	9.55 lb
	Pallet Information		
	Pallet Dimensions (L x W x H mm)	Slip Sheet: 1140 x 620 x 1990 mm (20' ft & 40' ft) Slip Sheet: 1140 x 620 x 2386 mm (40' HQ) Pallet: 1140 x 620 x 2110 mm (20' ft & 40' ft) Pallet: 1140 x 620 x 2509 mm (40' HQ)	Slip Sheet: 44.88 x 24.41 x 78.35 inch (20' ft & 40' ft) Slip Sheet: 44.88 x 24.41 x 93.94 inch (40' HQ) Pallet: 44.88 x 24.41 x 83.07 inch (20' ft & 40' ft) Pallet: 44.88 x 24.41 x 98.78 inch (40' HQ)
	Pallet Total Weight	Slip Sheet: 312 kg (20' ft & 40' ft) Slip Sheet: 379 kg (40' HQ) Pallet: 321 kg (20' ft & 40' ft) Pallet: 388 kg (40' HQ)	Slip Sheet: 687.8 lbs (20' ft & 40' ft) Slip Sheet: 835.6 lbs (40' HQ) Pallet: 707.7 lbs (20' ft & 40' ft) Pallet: 855.4 lbs (40' HQ)
	Pallet Layers	Slip Sheet: 5 layers (20' ft & 40' ft) Slip Sheet: 6 layers (40' HQ) Pallet: 5 layers (20' ft & 40' ft) Pallet: 6 layers (40' HQ)	
	Pallet Product per Layer	8 per layer (slip sheet & pallet) Slip Sheet: 40 sets (20' ft & 40' ft) Slip Sheet: 48 sets (40' HQ)	
	Total Products per Pallet	Pallet: 40 sets (20' ft & 40' ft) Pallet: 48 sets (40' HQ)	

Technical Specifications

	Container Load, 20-Foot	720 sets (slip sheet & pallet)
	Container Load, 40-Foot	1520 sets (slip sheet & pallet)
	Container Load, 40-Foot HighQ	1824 sets (slip sheet & pallet)
What's in the box?	AC power cord (1.83m) 5.9ft USB 3.2 C-C cable (1.8m) Warranty Quick Setup Poster	
User Guide and Warranty Languages	User Guide Languages	Arabic, Bahasa Indonesia, Bulgarian, Chinese-S, Chinese-T, Czech, Danish, Dutch, English, Estonian, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Kazakh, Korean, Latvian, Lithuanian, Norwegian, Polish, Portuguese (Brazilian), Portuguese (Iberian), Romanian, Russian, Serbian, Slovak, Slovenian, Spanish, Swedish, Thai, Turkey, Ukrainian
	Warranty Languages	English US (EN), English AP (EN-AP), English LA (EN-LA), English UK (EN-GB), Arabic (AR) -17x, Bahasa Indonesia (ID), Bosnian (BS), Bulgarian (BG), Chinese-S (CN), Chinese-T (TW), Croatian (HR), Czech (CS), Danish (DA), Dutch (NL), Estonian (ET), Finnish (FI), French Canadian (FC), French European (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese (JA), Kazakh (KK), Korean (KO), Latvian (LV), Lithuanian (LT), Norwegian (NO), Polish (PL), Portuguese, Brazilian (BR), Portuguese, Iberian (PT), Romanian (RO), Russian (RU), Serbian (SR), Slovak (SK), Slovenian (SL), Spanish, Castilian (ES-ES), Spanish, Latin America (ES-MX), Swedish (SV), Thai (TH), Turkish (TR), Ukrainian (UK), Vietnamese (VI)

Technical Specifications

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.

Summary

Change Log			
	V1 to V2		
	V2 to V3		
	V3 to V4		