

Rittal – The System.

Faster – better – everywhere.

Cable routing bars, 482.6 mm (19") attachment – DK 7111.224

Date : Jun 15, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Cable routing bars, 482.6 mm (19") attachment – DK 7111.224

created: 15.06.2021 on www.rittal.com/com-en



Product description

Description:	For structured routing of entire cable bundles, the cable bars may be secured to a variety of different positions inside the enclosure.
Applications:	For horizontal cable routing within the distributor level. Thanks to their open mounting holes, they can also be retrospectively slotted onto the 482.6 mm (19") system punchings of the mounting level at any time and secured with the existing mounting screws of the installed components.
Material:	Support: Sheet steel Cable routing bars, connection combs: Plastic UL 94-V0
Colour:	RAL 9005
Supply includes:	Cable routing bars Connection combs
Note:	Size of individual chambers (WxD) approx. 34 x 100 mm

Product description

Units:	4 U
Number of connection combs:	2
Packs of:	4 pc(s).
Weight/pack:	0.73 kg

Copper weight (kg per piece):	0
EAN:	4028177550377
Customs tariff number:	73269098
ETIM 7.0:	EC000322
ETIM 6.0:	EC000322
eCl@ss 8.0/8.1:	27400604
eCl@ss 6.0/6.1:	27400604
Product description:	DK Cable routing bars, 482.6 mm (19") attachment, 4 U
Approvals	
Certificates:	NA