



QDA-U2MP	
Supported Dirves	2 x M.2 2280 PCIe 3.0 x4 NVMe SSD
Host Interface	U.2 (SFF-8639) PCIe 3.0 x4
Supported Operating Systems	<ol> <li>QTS 4.4.2 (or later)</li> <li>Windows: Windows 7, 8.1, 10, Windows Server 2012 R2</li> <li>Ubuntu</li> </ol>
Dimension	100.4 × 69.85 × 15 mm
Weight	0.14 kg
Note	The connected drive may not reach its optimal performance due to protocol translation and some overhead.  Consult your PC system provider if the PC operating system supports U.2 NVMe
	SSD.
Architecture Diagram	Asmedia 2812 Gen3 PCle Switch  U.2 PCle NVMe Gen3 x4  SSD 2  M.2 2280 PCle NVMe Gen3 x4  SSD 1  Asmedia 2812  Asmedia 2812  PCle NVMe Gen3 x4  SSD 1  M.2 2280 PCle NVMe Gen3 x4

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. \* Sound Level Test

Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.