

BE24EQK

DisplayPanel Size: Wide Screen 23.8"(60.5cm) 16:9

Color Saturation : 72% NTSC

Panel Type : IPS

True Resolution : 1920x1080

Display Viewing Area(HxV) : 527.04 x 296.46 mm

Display Surface : Non-glare

Pixel Pitch : 0.275mm

Brightness(Max) : 300 cd/m²

Contrast Ratio (Max) : 1000:1

ASUS Smart Contrast Ratio (ASCR) : 100000000:1

Viewing Angle (CR_≥10) : 178°(H)/178°(V)

Response Time : 5ms (Gray to Gray)

Display Colors : 16.7M

Flicker free : Yes

Video FeatureTrace Free Technology : Yes

SPLENDID Video Intelligence Technology

Skin-Tone Selection : 3 Modes

Color Temperature Selection : 4 Modes

QuickFit (modes) : Yes (Modes)

Webcam(Built-in) : 2.0M Pixel(Rotatable)

Low Blue Light : Yes

HDCP support : Yes, 1.4

Audio FeaturesBuilt-in Microphone (Array Type)

Stereo Speakers : 2W x 2 Stereo RMS

I/O PortsSignal Input : HDMI, D-Sub, DisplayPort

PC Audio Input : 3.5mm Mini-Jack

Earphone jack : 3.5mm Mini-Jack

USB Port(s) : 1 x upstream

Signal FrequencyAnalog Signal Frequency : 30 ~83 KHz (H) /50 Hz(V)

Digital Signal Frequency : 30 ~83 KHz (H) /50 ~76 Hz(V)

Power Consumption

Power Consumption:<15W*

Power Saving Mode:<0.5W

Power Off Mode:0W(hard switch)

Voltage: 100–240V, 50 / 60 Hz

Mechanical Design

Chassis Colors : Black

Tilt : -5°~+20°

VESA Wall Mounting : 100x100mm

Security

Kensington lock

Dimensions

Phys. Dimension(with Stand)(WxHxD): 540 x 426 x 195 mm

(with stand)

Phys. Dimension(without Stand ,For VESA Wall Mount)(WxHxD): 540 x 355 x

53 mm

Box Dimension (WxHxD): 610 x 494 x 168 mm

Weight

Net: 4.6kg (with stand) , 3.9kg (without stand),

Gross: 6.4kg

Accessories

VGA cable(Optional)

Audio cable(Optional)

Power cord

DisplayPort cable (Optional)

USB cable

Quick start guide

HDMI cable (Optional)

Warranty Card

Regulation Approval

Energy Star®, BSMI, CB, CCC, CE, CEL level , C-

Tick, CU, ErP, FCC, ISO-9241-307, J-MOSS, KCC, PSE, RoHS, TCO8.0, UL/cUL,

VCCI, WEEE, WHQL (Windows 10, Windows 8.1, Windows 7), MEPS, TUV

Flicker-free , KC , eStandby, TUV Low Blue Light, ICES-3, EU energy label

Note

*measuring a screen brightness of 200 nits without audio/ USB/ Card

reader connection



- All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.
- PCB color and bundled software versions are subject to change without notice.
- Brand and product names mentioned are trademarks of their respective companies.