

Rittal – The System.

Faster – better – everywhere.

Network rack TX CableNet with vented door – TX 7888.120

Date : Jun 14, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Network rack TX CableNet with vented door – TX 7888.120

created: 14.06.2021 on www.rittal.com/com-en



Product description

Benefits:	Vented surface area approx. 78 % perforated Site-variable cable routing Safe cable entry whilst maintaining the critical cable bending radius "Waterfall" cable routing concept: Simple, safe cable routing from the roof – Convenient laying rather than cumbersome pulling Convenient access: Side panels and doors are easily fitted and removed for fast access to the inner rack area Vented doors support the installation of active and passive network components TS- and VX-compatible accessories Comprehensive range of accessories for bespoke interior configuration
Material:	Sheet steel
Surface finish:	Enclosure frame: Dipcoat-primed Enclosure panels: Powder-coated
Colour:	RAL 7035
Supply includes:	Enclosure frame with doors and welded roof plate Two 482.6 mm (19") mounting angles, front and rear Sheet steel front door, vented, 130° hinges Sheet steel rear door, vented, one-piece, 130° hinges Fastener front and rear: Designer handle with security lock 3524 E IPPC pallet Side panels, lockable, including security lock 3524 E
Note:	Depending on how and where it is sited, the door opening angle may vary for selected applications
Basic material:	Sheet steel

Product description

Dimensions: Width: 800 mm
Height: 2200 mm
Depth: 1000 mm

Installation height for components: 47 U

Distance between levels as delivered: 645 mm

Construction variants: With side panels

Construction doors: Vented

Load capacity: 5000 N

Packs of: 1 pc(s).

Weight/pack: 88 kg

EAN: 4028177963412

Customs tariff number: 94032080

ETIM 7.0: EC002499

ETIM 6.0: EC002499

eCl@ss 8.0/8.1: 27180207

eCl@ss 6.0/6.1: 27180207

Product description: Network Rack TX CableNet, 800x2200x1000 mm, 47 U, with side panels, RAL 7035

Approvals

Declarations: Declaration of conformity