

Cat.6A/ClassEA Installation link S/FTP PIMF



Cat.6A FRNC-B



Description

Robust special rubber cable drum, complete with Cat.7 S/FTP installation cable, integrated outlet Cat.6A 1 x RJ45 with dust cap and 1 x Cat.6A RJ45. Very well suited to mobile use, for exhibitions, presentations, outside broadcasting vans, measuring sections etc. A standardised installation section in accordance with structured cabling Cat.6A / Class EA.

General data

Category	6A (TIA)
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Pin assignment	1:1
Anti-kink sleeve	plugged in
Colour anti-kink sleeve	black
Dust cover	yes
Locking lever	False

Mechanical characteristics

Bending radius	4 x OD
----------------	--------

Kabelaufbau

Raw cable	Cat.7
Cable structure	S/FTP
Cable construction	4x2
AWG-size/strands per core	23
Conductor Material	Copper

This datasheet was created automatically on 26-07-2019 . Technical changes reserved.



Cat.6A/ClassEA Installation link S/FTP PIMF

Kabelmantel

Jacket material	FRNC
Colour outer sheath	orange
Flame-retardant	acc. IEC60332-1
Low smoke	acc. IEC61034

Environmental conditions

Temperature Range (Operation)	-20 – 60 °C
Temperature Range (Installation)	0 – 50 °C

Electrical characteristics

NVP value	79 %
-----------	------

Available variants

Article no.	Title	Length
K9201.50	Cat.6A/classEA Installation link, S/FTP, 50m on drum	50.0 m
K9201.90	Cat.6A/classEA Installation link, S/FTP, 90m on drum	90.0 m