

# Product datasheet

Specifications



APC Back-UPS Pro, 2200VA/  
1320W, Tower, 230V, 2x UK and  
2x IEC C13 outlets, RGB Lights,  
Pure Sine Wave, Midnight (Black)

BGM2200B-UK

## Overview

Lead time

## Main

Main Input Voltage	230 V AC 1 phase
Other Input Voltage	230 V
Main Output Voltage	230 V 1 phase
Rated power in W	1320 W
Rated power in VA	2200 VA
product or component type	Uninterruptible power supply (UPS)
Input Connection Type	UK
output connection type	2 United Kingdom 2 IEC 60320 C13
Cable length	1.5 m
Number of cables	1
Battery type	Lead-acid battery

## Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Battery voltage	24 V
Overcurrent protection	13 A
Battery charger power	12 W rated
Battery life	3...5 year(s)

## General

Provided equipment	safety guide USB cable power cable
product web sub-family	Gaming performance

Number preinstalled power module	0
Number of power module free slots	0
Redundant	No

## Physical

Colour	Black
Height	292.1 mm
Width	104.1 mm
Depth	408.9 mm
net weight	12.32 kg
mounting support	Floor
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

## Input

Network frequency	50/60 Hz +/- 3 Hz
Plug standard	UK
Input voltage limits	168...302 V
Maximum input current	12 A
Switching current capacity	15 A
Input harmonic distortion	Less than 3 % for full load
Input protection type	Circuit breaker and fuse

## Output

Maximum configurable power in W	1320 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Full load runtime	00:30:00
Half load runtime	00:05:30
Maximum configurable power in VA	2200 VA
Transfer time	8 ms typical : 10 ms maximum

## Conformance

Product certifications	CE CB
Equipment protection policy	Lifetime : 50000 euros

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...3048.0000000000 m
Acoustic level	45 dBA
IP degree of protection	IP20

## Communications & Management

Free slots	0
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rate	1080 J
Noise suppression	Full time multi-pole noise filtering : 5% of IEEE surge let-through : zero clamping response time: instantaneous

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	35.5 cm
Package 1 Length	48 cm
Package 1 Weight	14.46 kg
SCC14	20731304634786

## Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[How we assess product sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

 **Rohs Exemption Information** Yes

## Certifications & Standards

**Reach Regulation** [REACH Declaration](#)

**Eu Rohs Directive** Compliant with Exemptions

**China Rohs Regulation** [China RoHS declaration](#)

**Environmental Disclosure** [Product Environmental Profile](#)

**Circularity Profile** [End of Life Information](#)

Image of product / Alternate images

Alternative

---



Image of product in real life situation

